
## राजस्थान राज्य क्रीडा परिषद





क्रमांक : एफ-8/स.अ. / SMS Stadium / मरम्मत कार्य / 2020-21 /2433 दिनांक : 17/3/2021

## निविदा सूचना संख्या 33 / 2021-22

राजस्थान राज्य क्रीडा परिषद, जयपुर की ओर से सवाई मानसिंह स्टेडियम, जयपुर परिसर में पैन्टिंग एवं विद्युत मरम्मत कार्यों हेतु राज्य/केन्द्र सरकार अथवा राज्य/केन्द्र सरकार के अधिकृत संगठनों के विभागों में पंजीकृत संवेदक, जो कि राजस्थान सरकार के उपयुक्त श्रेणी के संवेदकों के समकक्ष हो, से ई—प्रोक्यूरमेंट प्रक्रिया हेतु आनलाइन निविदाएं आमंत्रित की जाती है।

निविदा से संबंधित अन्य आवश्यक विवरण वेबसाईट http://sppp.rajasthan.gov.in, http://eproc.rajasthan.gov.in व www.rssc.in पर देखा जा सकता है।

सचिव



#### RAJASTHAN STATE SPORTS COUNCIL

## **TENDER DOCUMENT**

#### FOR

Annual maintenance work (Electrical) in S.M.S.Stadium, Jaipur.

NIT NO. : NIT No. 33 /20211-22.

ESTIMATED COST : Rs. 30.00 Lacs

EARNEST MONEY : Rs. 60,000/-

DATE OF SALE / DOWNLOADING : From Wednesday March 17, 2021, 17:00 Hours to

Wednesday March 30, 2021, 13:00 Hours

DATE OF RECEIPT (D.D. & : From Wednesday March 17, 2021, 17:00 Hours to

DOCUMENTS) Wednesday March 30, 2021, 15:00 Hours

DATE OF OPENING OF TENDER : Wednesday March 30, 2021 AT 16:00 Hours

COMPLETION PERIOD : 01 (One) Year

COST OF TENDER : Rs. 500/- in favour of Secretary, RSSC, Jaipur

PROCESSING FEES Rs 500/- in favour of MD, RISL, Jaipur



#### IMPORTANT DATES AND OTHER INFORMATION

## Secretary, Rajasthan State Sports Council. Jaipur

Important Dates of Bids for Annual maintenance work (Electrical) in S.M.S.Stadium, Jaipur

Completion Period	01 Year
2. Date of Issue of Notice Inviting Tender	Wednesday March 17, 2021
Period and Places of Sale/ Download of Bidding Documents -	From Wednesday March 17, 2021, 17:00 Hours to Wednesday March 30, 2021, 13:00 Hours
	http://sppp.rajasthan.gov.in, http://eproc.rajasthan.gov.in & www.rssc.in
4. Deadline for uploading	From Wednesday March 17, 2021, 17:00 Hours to Wednesday March 30, 2021, 13:00 Hours
5. Time and Date for Opening of Bids	Wednesday March 30, 2021, AT 16:00 Hours
6. Place of Opening of Bids	Rajasthan State Sports Council, SMS Stadium, Jaipur-302005
7. Officer Inviting Bids	Designation: Secretary, Rajasthan State Sports Council. Jaipur.
	Address: SMS Stadium, Jaipur-302005
8. Rate are based on BSR	Rates are Based BSR-2013 & Amendments on PWD Electrical Circle & BSR-2019 and its all Corrigendums
9 Earnest money to be deposited	As per NIT



## Instructions and information to bidder regarding Fee, EMD etc.

District	Name of Work Package No.	Estimated Cost (Rs.)	Earnest Money	Time Allowed for completion	End date and time for downloading Tender	Time and date of opening of tender	Place of Sale of documents	Class of contractor.
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
Jaipur	Annual maintenance work (Electrical) in S.M.S.Stadium, Jaipur	30.00 Lacs	Rs. 60,000/-	01 Year	Wednesday March 30, 2021, 13:00 Hours	Wednesday March 30, 2021, AT 16:00 Hours	http://sppp.rajasthan.gov.in, http://eproc.rajasthan.gov.in & www.rssc.in	"A" & above for Electrical work

- 1. The Tender Fee and earnest money as mentioned above should be deposited in the appropriate form as per the tender documents in favour of Secretary, Rajasthan State Sports Council. Jaipur payable at Jaipur and Processing Fees Rs 500/- in favour of MD, RISL, Jaipur payable at Jaipur and must be uploaded scan copy of Registration of Firm, Demand Draft of Tender Cost, Processing Fee & Earnest Money and GST Number on the site
- 2. The tender can be viewed and downloaded from web site http://sppp.rajasthan.gov.in, http://eproc.rajasthan.gov.in & www.rssc.in
- The authorized tender documents are available for inspection in the office of Rajasthan State Sports Council, SMS Stadium, Jaipur from all working days.

TH

## Annexure A: Compliance with the Code of Integrity and No Conflict of

Any person participating in a procurement process shall-

- (a) Not offer any bribe, reward or gift or any material benefit either directly or indirectly in exchange for an unfair advantage in procurement process or to otherwise influence the procurement process;
- (b) Not misrepresent or omit that misleads or attempts to mislead so as to obtain a financial or other benefit or avoid an obligation;
- (c) Not indulge in any collusion, Bid rigging or anticompetitive behavior to impair the transparency, fairness and progress of the procurement process;
- (d) Not misuse any information shared between the procuring entity and the bidders with an intent to gain unfair advantage in the procurement process;
- (e) Not indulge in any coercion including impairing or harming or threatening to do the same, directly or indirectly, to any party or to its property to influence the procurement process;
- (f) Not obstruct any investigation or audit of a procurement process;
- (g) Disclose conflict of interest, if any; and
- (h) Disclose any previous transgressions with any entity in India or any other country during the last three years or any debarment by any other procuring entity.

#### Conflict of interest.-

The Bidder participating in a bidding process must not have a Conflict of Interest.

A Conflict of interest is considered to be a situation in which a party has interests that could improperly influence that party's performance of official duties or responsibilities, contractual obligations, or compliance with applicable laws and regulations.

- (i) A bidder may be considered to be in conflict of interest with one or more parties in the bidding process if, including but not limited to:
- (a) Have controlling partners/shareholders in common; or
- (b) Receive or have received any direct or indirect subsidy from any of them; or
- (c) Have the same legal representative for purposes of the bid; or
- (d) have a relationship with each other, directly or through common third parties, that puts them in a position to have access to information about or influence on the bid of another bidder, or influence the decisions of the procuring Entity regarding the bidding process; or
- (e) The bidder participates in more than one bid in a bidding process. Participation by a bidder in more than one bid will result in the disqualification of all bids in which the bidder is involved. However, this does not limit the inclusion of the same subcontractor, not otherwise participating as a bidder, in more than one bid; or
- (f) the bidder or any of its affiliates participated as a consultant in the preparation of the design or technical specifications of the goods, Works or services that are the subject of the Bid; or
- (g) Bidder or any of its affiliates has been hired (or proposed to be hired) by the procuring entity as engineer-in-charge/consultant for the contract.



# Annexure B: Declaration by the Bidder regarding Qualifications Declaration by the Bidder

In relation to my/o	ur Bid submitted	to			for procure	ement of
i	n response	to	their	Notice	inviting	Bids
NoDated.	I/we		her	eby declare	under Secti	on 7 of
Rajasthan Transpar	ency in Public P	rocureme	nt Act, 201	2 that:		

- I/we possess the necessary professional, technical, financial and managerial resources and competence required by the Bidding Document issued by the Procuring Entry;
- I/we have fulfilled my/our obligation to pay such of the taxes payble to the union and the state government or any local authority as specified in the Bidding Document.
- I/we are not insolvent, in receivership, bankrupt or being wound up, not have
  my/our affairs administered by a court or a judicial officer, not have my/our
  business activities suspended and not the subject of legal proceedings for any of the
  foregoing reasons;
- 4. I/we do not have, and our directors and officers not have, been convicted of any criminal offence related to my/our professional conduct or the making of false statements or misrepresentations as to my/our qualifications to enter into a procurement contract within a period of three years preceding the commencement of this procurement process, or not have been otherwise disqualified pursuant to debarment proceedings;
- I/we do not have a conflict of interest as specified in the Act, Rules and the Bidding Document, which materially affects fair competition;

Date:	Signature of bidde
Place:	Name:
	Designation:
	Address:



#### Annexure C: Grievance Redressed during Procurement Process

The designation and address of the First Appellate Authority is Dy. Secretary Youth Affairs & Sports Department Govt. of Rajasthan. The designation and address of the Second Appellate Authority is **Principal Secretary** Youth Affairs & Sports Department Govt. of Rajasthan, Jaipur.

#### (1) Filing an appeal:-

if any bidder or prospective bidder is aggrieved that any decision, action or omission of the procuring entity is in contravention to the provisions of the Act or the rules or the guidelines issued thereunder, he may file an appeal to First Appellate authority, as specified in the Bidding document within a period of ten days from the date of such decision or action, omission, as the case may be, clearly giving the specific ground or grounds on which he feels aggrieved:

Provided that after the declaration of a bidder as successful the appeal may be filed only by a bidder who has participated in procurement proceedings:

Provided further that in case a procuring entity evaluates the technical bids before the opening of the financial bids, an appeal related to the matter of financial bids may be filed only by a bidder whose technical bid is found to be acceptable.

- (2) The officer to whom an appeal is filed under Para (1) shall deal with the appeal as expeditiously as possible and shall endeavour to dispose it of within thirty days from the date of the appeal.
- (3) If the officer designated under Para (1) fails to dispose of the appeal filed within the period specified in Para (2), or if the bidder or prospective bidder or the procuring entity is aggrieved by the order passed by the first appellate authority, the bidder or prospective bidder or the procuring entity, as the case may be, may file a second appeal to second appellate authority specified in the bidding document in this behalf within fifteen days from the expiry of the period specified in Para (2) or of the date of receipt of the order passed by the first appellate authority, as the case may be.

#### (4) Appeals not to lie in certain cases:-

No appeal shall lie against any decision of the procuring entity relating to the following matters, namely:-

- (a) Determination of need of procurement
- (b) Provisions limiting participation of bidders in the bid process
- (c) The decision of whether or not to enter into negotiations
- (d) Cancellation of a procurement process
- (e) Applicability of the provisions of confidentiality

#### (5) Form of Appeals:-

(a) An appeal under Para (1) or (3) above shall be in the annexed form along with as many copies as there are respondents in the appeal.



- (b) Every appeal shall be accompanied by an order appealed against, if any, affidavit verifying the facts stated in the appeal and proof of payment of fee,
- (c) Every appeal may be presented to first appellate authority or second appellate authority, as the case may be, in person or though registered post or authorized representative.

#### (6) Fee for filing Appeal:-

- (a) Fee for first appeal shall be rupees two thousand five hundred and for second appeal shall be rupees ten thousand, which shall be non-refundable.
- (b) The fee shall be paid in the form of bank demand draft or banker's cheque of a scheduled bank in India payable in the name of appellate authority concerned.

#### (7) Procedure for disposal of Appeal:-

- (a) The first appellate authority or second appellate authority as the case may be, upon filing of appeal, shall issue notice accompanied by copy of appeal, affidavit and documents, if any, to the respondents and fix date of hearing
- (b) On the date fixed for hearing, the first appellate authority of second appellate authority, as the case may be shall-
  - (i) Hear all the parties to appeal present before him; and
  - (ii) Peruse or inspect documents, relevant records or copies thereof relating to the matter.
- (c) After hearing the parties, perusal or inspection of documents and relevant records or copies thereof relating to the matter, the appellate authority concerned shall pass an order in writing and provide the copy of order to the parties to appeal free of cost.
- (d) The order passed under sub-clause (c) above shall also be placed on the state public procurement portal.



#### Annexure D: Additional Conditions of Contract

#### 1. Correction of arithmetical errors

Provided that a Financial Bid is substantially responsive, the Procuring Entity will correct arithmetical errors during evaluation of Financial Bids on the following basis:

- i. If there is a discrepancy between the unit price and the total price that is obtained by multiplying the unit price and quantity, the unit price shall prevail and the total price shall be corrected, unless in the opinion of the Procuring Entity there is an obvious misplacement of the decimal point in the unit price, in which case the total price as quoted shall govern and the unit price shall be corrected;
- ii. It there is an error in a total corresponding to the addition or subtraction of subtotals, the subtotals shall prevail and the total shall be corrected; and
- iii. If there is a discrepancy between words and figures, the amount in words shall prevail, unless the amount expressed in words is related to an arithmetic error, in which case the amount in figures shall prevail subject to (i) and (ii) above.

If the Bidder that submitted the lowest evaluated Bid does not accept the correction of errors, its Bid shall be disqualified and its Bid Security shall be forfeited or its Bid Securing Declaration shall be executed.

#### 2. Procuring Entity's Right to Vary Quantities

- (i) At the time of award of contract, the quantity of Goods, Works or services originally specified in the Bidding Document may be increased or decreased by a specified percentage, but such increase or decrease shall not exceed Five percent, of the quantity specified in the Bidding Document. It shall be without any change in the unit prices or other terms and conditions of the Bid and the conditions of contract.
- (ii) If the Procuring Entity does not procure any subject matter of procurement or procures less than the quantity specified in the Bidding Document due to change in circumstances, the Bidder shall not be entitled for any claim or compensation except otherwise provided in the Conditions of Contract.
- (i) In case of procurement of Goods or services, additional quantity may be procured by placing a repeat order on the rates and conditions of the original order. However, the additional quantity shall not be more than 50% of the value of Goods of the original contract and shall be within one month from the date of expiry of last supply. If the supplier fails to do so, the Procuring Entity shall be free to arrange for the balance supply by limited Bidding or otherwise and the extra cost incurred shall be recovered from the supplier.

## 3. Dividing quantities among more than one Bidder at the time of award (In case of procurement of Goods)

As a general rule all the quantities of the subject matter of procurement shall be procured from the Bidder, whose Bid is accepted. However, when it is considered that the quantity of the subject matter of procurement to be procured is very large and it may not be in the capacity of the Bidder, whose Bid is accepted, to deliver the entire quantity or when it is considered that the subject matter of procurement to be procured is of critical and vital nature, in such cases, the quantity may be divided between the Bidder, whose Bid is accepted and the second lowest Bidder or even more Bidders in that order, in a fair, transparent and equitable manner at the rates of the Bidder, whose Bid is accepted.



## राजस्थान राज्य क्रीडा परिषद

15 A YEARS OF THE MAHATMA

सवाई मानसिंह स्टेडियम, जनपथ, जयपुर

कार्यालय दूरभाष नं0 0141-2744283, फैक्स नं0 0141-2740568, ईमेल आईडी-rsscjaipur@gmail.com

बोली की शर्तें

विशेष टिप्पणी :- बोलीदाताओं को इन शर्तों को सावधानी पूर्वक पढ़ना चाहिए तथा अपनी ई-बोलियां भेजते समय इनकी पूर्ण रूपेण पालना करनी चाहिए।

- 1. तकनीकी प्रस्तावों में सफल बोलीदाताओं के ही वित्तीय प्रस्ताव खोले जावेगें जो निविदादाता तकनीकी बिड में सफल नहीं पाये गये उनकी वित्तीय बोली नहीं खोली जायेगी।
- 2. कोई भी फर्म/संवेदक यदि जी.एस.टी. अधिनियम के अन्तर्गत पंजीकृत नहीं है तो वह बोली नहीं देगा। इनके अभाव में बोलियों पर विचार नहीं किया जायेगा। जी. एस. टी. देयता प्रमाण पत्र दिसम्बर, 2020 तक का संलग्न करना आवश्यक है।
- 3. दरें जी. एस. टी. तथा केन्द्र व राज्य सरकार द्वारा देय समस्त करों सहित देनी होगी।
- 4. बोली ऑन-लाईन प्रस्तुत की जावेगी एवं निर्दिष्ट कॉलमों में प्रविष्टी की जावेगी।
- 5. दरें गन्तव्य स्थान तक एफ.ओ.आर. सवाई मानसिंह स्टेडियम जयपुर के आधार पर होगीं अर्थात परिवहन संबंधी कोई राशि परिषद द्वारा पृथक से देय नहीं होगी।
- 6. बोलियां उपापन अधिनियम / पारदर्शिता अधिनियम के तत्संबंधी प्रावधानों (धारा-28 आदि) के अध्यधीन रहते हुये उनके खोले जाने की दिनांक से एक वर्ष की अविध के लिए विधि मान्य होंगी।
- बोलीदाता अपनी संविदा या उसके किसी भाग को किसी अन्य एजेन्सी के लिए नहीं सौंपेगा या उपभाडे पर नहीं देगा।
- 8. बोलीदाता का उसके प्रतिनिधि की ओर से प्रत्यक्ष अथवा अप्रत्यक्ष रूप से अपना पक्ष समर्थन करना एक प्रकार की अनर्हता होगी। हित विरोधी धारा 80 होगी।
- 9. विहित समय एवं तारीख के पश्चात् जो भी बोलियां प्राप्त होंगी उन्हें किसी स्थिति में स्वीकार नहीं किया जावेगा।
- 10. यदि बोलीदाता ऐसी कोई शर्त आरोपित करता है जो उसमें वर्णित शर्तों के अतिरिक्त है या उनके विरोध में है तो उसकी बोली को संक्षिप्त रूप में कार्यवाही कर रद्द कर दिया जावेगा।
- 11. तकनीकी बोली के साथ बोलीदाता को निम्न दस्तावेज संलग्न करने अनिवार्य होगे (जिसके आधार पर तकनीकी बिड का मूल्याकंन किया जायेगा) :--
  - बोली में अंकित पते के प्रमाण हेतु पानी/बिजली/टेलीफोन/मोबाईल के बिल, पेन कार्ड, पासपोर्ट, आधार कार्ड अथवा ड्राईविंग लाईसेन्स में से कोई एक की प्रमाणित छाया प्रतियां।

that

ii. बोलीदाता / फर्म का विगत 1 वित्तीय वर्ष में टर्न ओवर 30.00 लाख से कम नहीं होना चाहिये। इस हेतु बोलीदाता को उक्त वर्ष के लेखा विवरण एवं आयकर विवरणी की प्रति संलग्न करनी होगी।

iii. गत 2 वर्षों में किये गये राजकीय विभागों में किये गये विद्युत कार्य का एकल कार्य राशि रूपये 15.00 लाख न्यूनतम का अनुभव होना आवश्यक होगा। इसके प्रमाणीकरण हेतु कार्यादेश एवं कार्य के सन्तोषजनक होने का

प्रमाण पत्र आदि आवश्यक दस्तावेज संलग्न करने होगे।

v. बोलीदाता को माल एवं सेवाकर (GST) के रजिस्ट्रेशन की प्रति संलग्न करनी होगी।

v. अमानत राशि एवं बोली प्रपत्र शुल्क का डी.डी. संलग्न करना होगा।

#### 12. बयाना राशि :-

(क) बोली से पूर्व (2% बोली सूचना के अनुसार) नियमानुसार बयाना राशि ऑन—लाईन प्रस्तुत की जायेगी। इसके बिना बोलीओं पर विचार नहीं किया जायेगा। यह राशि सचिव, राजस्थान राज्य क्रीड़ा परिषद, जयपुर के पक्ष में बैंक ड्राफ्ट/बैंकर्स चैक में से किसी रूप में जमा करायी जा सकती है।

(ख) असफल बोलीदाता की बयाना राशि बोली को अंतिम रूप से स्वीकार करने के

बाद यथा संभव शीघ्र लौटा दी जावेगी।

(ग) अनुमोदन की प्रतीक्षा करने वाली या रद्द की गई या संविदाओं के पूर्ण हो जाने के कारण परिषद कार्यालय के पास जमा बयानाराशि / प्रतिभूति निक्षेप को नवीन निविदा के लिए बायाना राशि / प्रतिभूति राशि के प्रति समायोजित नहीं किया जायेगा।

13. बयाना राशि का समपहरण: वयाना राशि को निम्नलिखित मामलों में समपहरत

कर लिया जायेगा:-

(क) जब बोलीदाता बोली खोलने के बाद किन्तु बोली को स्वीकार करने के पूर्व प्रस्ताव को वापस लेता है या उसमें उपान्तरण करता है।

(ख) जब बोलीदाता विर्निष्ट समय के भीतर विहित करार को निष्पादित नहीं

करता है

(घ)

(ग) जब बोलीदाता प्रदायगी के लिए आदेश देने के बाद प्रतिभूति राशि जमा नहीं कराता हो।

जब वह निर्धारित समय के अन्तर्गत आदेशों के अनुसार कार्य करने में असफल रहता है अथवा संतोषजनक सेवाएं देने में असमर्थ रहता है।

## 14. करार एवं प्रतिभूति निक्षेप :--

- (क) सफल बोलीदाता को आदेश दिनांक से 7 दिन की अवधि के भीतर नियमानुसार मूल्य के नॉन ज्यूडिशियन स्टॉम्प पेपर पर (जिसका व्यय स्वयं बोलीदाता द्वारा वहन किया जावेगा) एक करार-पत्र निष्पादित करना होगा तथा प्रावधित मूल्य जिसके लिए बोली स्वीकार की गई है।
- (ख) बोली के समय जमा कराई गई बयाना राशि को प्रतिभूति की राशि के लिए समायोजित किया जायेगा।
- (ग) बयाना / प्रतिभूति राशि पर परिषद द्वारा कोई ब्याज का भुगतान नहीं किया जायेगा।



- (घ) प्रतिभूति राशि के रूप में नकद रसीद पत्र/शिड्यूल बैंक का ड्राफ्ट/ बैंकर्स चैक मान्य होंगे।
- 15. प्रतिभूति राशि का समपहरण :— प्रतिभूति की राशि को पूर्ण अथवा आंशिक रूप से निम्नलिखित मामलों में समपहरत किया जायेगा:—
  - (क) जब संविदा की किसी शर्त / अथवा शर्तों का उल्लंघन किया गया हो।
  - (ख) जब बोलीदाता सम्पूर्ण कार्य संतोषजनक ढंग से करने में असफल रहा हो।
  - (ग) प्रतिभूति निक्षेप को समपहरत करने के मामले में युक्तियुक्त नोटिस दिया जावेगा इस सम्बन्ध में परिषद के अधिकारी का निर्णय अन्तिम होगा।
  - (घ) कार्य में असफल रहने पर परिषद द्वारा वैकल्पिक व्यवस्था किये जाने पर उसमें जो भी व्यय होगा बोलीदाता से उसकी प्रतिभूति राशि में से अथवा उसको देय बिल की राशि के भुगतान में से की जायेगी। यदि वसूली करना सम्भव न हो तो राजस्थान पी.डी.आर.एक्ट या प्रवृत्त अन्य किसी कानून के अन्तर्गत कार्यवाही की जावेगी।
- 16. करार पत्र को पूर्ण करने एवं उस पर स्टाम्प लगाने का व्यय बोलीदाता द्वारा वहन किया जायेगा तथा परिषद को उस करार पत्र की निष्पादित स्टाम्प शुदा प्रति पडत निःशुल्क प्रस्तुत की जायेगी।
- 17. परिषद के प्राधिकृत अधिकारी या उसका विधिवत् प्राधिकृत प्रतिनिधि सभी युक्तियुक्त उचित समयों पर ठेकेदार के परिसर में जायेगा तथा वह विनिर्माण की प्रक्रिया के दौरान या उसके बाद जैसे भी हो किसी भी समय सामग्री का निरीक्षण एवं जांच करने की शक्ति रखेगा।
- 18. परीक्षण प्रभार परिषद द्वारा वहन किये जायेंगे। यदि बोलीदाता अत्यावश्यक तत्काल परीक्षण कराना चाहता है या यदि परिणामों से यह ज्ञात होता है कि प्रदाय किया गया सामान विहित स्तरों या विनिर्देशों के अनुसार नहीं है तो परीक्षण प्रभार बोलीदाता द्वारा वहन किये जायेंगे।
- 19. अनुमोदित कार्य के लिए यह समझा जाएगा कि उसने कार्य किये जाने वाले विनिर्देशों की सावधानीपूर्वक जांच कर ली है यदि उसे इन शर्तों, विनिर्देशों, रेखाचित्रों आदि के किसी भाग के आशय के बारे में कोई सन्देह हो तो वह संविदा पर हस्ताक्षर करने से पूर्व परिषद से स्पष्टीकरण प्राप्त करेगा।
- 20. सफल बोलीदाता को कार्य आदेश जारी तिथि के 10 दिवस के अन्दर कार्य प्रारम्भ करना होगा।
- 21. यदि निविदा सूचना में दर्शित मात्रा से अधिक के लिए आदेश दिया जाता है, तो निविदादाता अपेक्षित कार्य करने के लिए बाध्य होगा। पुनः आदेश भी निविदा में दी गयी शर्तों पर दिए जा सकेंगें परन्तु शर्त यह है, कि ऐसे पुनआदेश मूल रूप से खरीदी गयी मात्रा की 50 प्रतिशत तक के अतिरिक्त प्रदाय के लिए ही होगें।
- 22. <u>गारन्टी</u> :-गारन्टी नियमानुसार होगी।
- 23. परिसमापित नुकसानी :--
  - (1) परिसमापित नुकसानी के साथ कार्य अवधि में वृद्धि करने के मामले में, वसूली राजस्थान लोक उपापन पारदर्शिता अधिनियम, 2012 एवं राजस्थान लोक उपापन पारदर्शिता नियम 2013 के प्रावधान अनुसार होगी।
  - (2) यदि प्रदायकर्ता किन्ही बाधाओं के कारण संविदान्तर्गत कार्य का प्रदाय पूरा करने के लिए समय में वृद्धि कराना चाहता है, तो वह लिखित में परिषद को आवेदन करेगा। किन्तु वह उसके लिए निवेदन बाधा के घटित होने

Tel

पर तुरन्त उसी समय करेगा न कि प्रदाय पूर्ण होने की निर्धारित तारीख के बाद करेगा।

- (3) यदि कार्य प्रदाय करने में उत्पन्न हुई बाधा बोलीदाता के नियन्त्रण से परे कारणों से हुई हो तो कार्य की अवधि में वृद्धि परिसमापित नुकसानी सहित या रहित की जा सकेगी।
- 24. वसूली:—परिसमापित नुकसानी, कम प्रदाय, टूट—फूट, रद्द की गई वस्तुओं के लिए वसूली साधारण रूप से बिल में से की जाएगी। संवेदक कम प्रदाय, टूट—फूट, रद्द किए गए कार्यों की सीमा तक राशि को भी रोका जा सकेगा तथा यदि सेवा सन्तोषजनक ढंग से उनको कार्य करता है तो परिसमापित नुकसानी के साथ वसूली उसे देय राशि एवं विभाग के पास उपलब्ध प्रतिभूति निक्षेप से की जाएगी। यदि वसूली करना सम्भव न हो तो राजस्थान पी डी आर एक्ट या प्रवृत्त अन्य कानून के अन्तर्गत कार्रवाई की जाएगी।

25. भुगतान :-

- (क) बोलीदाता द्वारा क्रेता अधिकारी को उचित प्रारूप में लोक उपापन नियमों के अनुसार बिल प्रस्तुत करने पर भुगतान किया जायेगा। सभी प्रेषण प्रभार बोलीदाता द्वारा वहन किये जायेंगे। किसी भी सूरत में अग्रिम भुगतान नहीं किया जायेगा।
- (ख) विवादास्पद मदों में राशि का 10 प्रतिशत से 25 प्रतिशत तक को रोका जायेगा तथा उस विवाद का निपटारा हो जाने पर उसका भुगतान कर दिया जायेगा।
- (ग) उन मामलों में, जिनमें परीक्षण करने की जरूरत है, भुगतान तभी किया जायेगा जब उनका परीक्षण कर लिया जाये तथा प्राप्त हुए परीक्षण परिणाम विहित निर्देशों के अनुरूप हों।
- 26. यदि कार्य की तात्कालिक आवश्यकता के कारण पूर्ण या आंशिक रूप में उन कार्यों को बदलना साध्य नहीं समझा जाए तो राजस्थान राज्य क्रीडा परिषद द्वारा बोलीदाता को सुनवाई किये जाने का एक उचित अवसर देकर, ऐसे कारणों से जो अभिलिखित किये जायेंगे, अनुमोदित दरों में से उपयुक्त राशि की कटौती करेगा। इस प्रकार की गई कटौती अन्तिम होगी।
- निविदादाता करार को निष्पादित करते समय निम्नलिखित दस्तावेज प्रस्तुत करेगा :-
  - (i) यदि भागीदारी फर्म हो तो "पार्टनरशिप डीड" की अनुप्रमाणित प्रति।
  - (ii) यदि भागीदारी फर्म रजिस्ट्रार ऑन फर्म्स के पास पंजीकृत हो तो पंजीयन संख्या एवं उसका वर्ष।
  - (iii) एक मात्र स्वामित्तव के मामले में आवास एवं कार्यालय का पता, टेलीफोन नम्बर।
  - (iv) कम्पनी के मामले में कम्पनी के रजिस्ट्रार के द्वारा जारी किया गया प्रमाण–पत्र।
- 28. संविदा के निर्वचन, आशय या संविदा की शर्तों के उल्लंघन के सम्बन्ध में या अन्य किसी भी प्रकार का विवाद होने पर परिषद का निर्णय अन्तिम होगा।
- 29. समस्त विधिक कार्यवाहियां यदि संस्थित किया जाना आवश्यक हो तो जयपुर स्थित न्यायालय में ही की जाएगी। अन्यत्र नहीं की जाएगी।



30. बोलीदाता द्वारा अपलोड किये जाने वालो दस्तावेजों पर नम्बरिंग होनी चाही एवं चैक लिस्ट भर कर प्रस्तुत करनी होगी।

31. सचिव, राजस्थान राज्य क्रीडा परिषद, जयपुर को बिना कारण बताये किसी भी

बोली को स्वीकार / अस्वीकार करने का अधिकार होगा।

32. जी.एफ. एण्ड ए.आर.,राजस्थान लोक उपापन पारदर्शिता अधिनियम, 2012 एवं राजस्थान लोक उपापन पारदर्शिता नियम 2013 के प्रावधान लागू होगें।


> बोलीदाता के हस्ताक्षर (मय नाम पता एवं मोहर)



### घोषणा

मैने/हमने सवाई मानसिंह स्टेडियम, जयपुर में विद्युत हेतु (मय सामग्री) की बोली के नियम एवं शर्तों को भली—भॉति पढ व समझ लिया है। मुझे/हमारी फर्म को किसी भी विभाग द्वारा ब्लेक—लिस्ट नहीं किया गया है। इन शर्तो एवं नियमों के अधीन मैं/हम सवाई मानसिंह स्टेडियम, जयपुर में विद्युत कार्य करने हेतु सहमत एवं वचनबद्व हूं/है। यदि मेरे/हमारे द्वारा की किसी बोली की शर्तों, नियमों अथवा आदेशों का उल्लंघन किया जावेगा तो सक्षम अधिकारी द्वारा मेरे/हमारे विरुद्ध बोली के नियम/शर्तों के उल्लंधन की कार्यवाही करने के लिए अधिकृत होगा। इस सम्बन्ध में मुझे/हमें सक्षम/अधिकृत अधिकारी द्वारा लिया गया निर्णय मान्य होगा तथा इसमें मुझे/हमको कोई आपत्ति/हस्तक्षेप नहीं है।

हस्ताक्षर	बोलीदाता	
नाम/पत	T	
टेलीफोन	नं	
दिनांक		



#### General Instructions for Filling of Bid

The complete bidding document has been published on the website www.rssc.in, http://sppp.raj.nic.in, http://eproc.raj.gov.in, for the purpose of downloading.

- Bidders who wish to participate in this bidding process must register on www.rssc.in & http://sppp.raj.nic.in,
- 2. To participate in online bidding process, Bidders must procure a Digital Signature Certificate (Type III) as per Information Technology Act-2000 using which they can digitally sign their electronic bids. Bidders can procure the same from any CCA approved certifying agency, i.e. TCS, safe crypt, Node etc. Bidders who already have a valid Digital Signature Certificate (DSC) need not procure a new DSC.
- 3. Bidder (authorized signatory) shall submit their offer on-line in Electronic formats both for Technical and financial proposal. However, DD for Tender Fees, EMD payable in favor of SECRETARY RAJASTHAN STATE SPORTS COUNCIL, JAIPUR, payable at Jaipur and Processing Fees payable in favor of Managing Director, RAJCOMP Info Services Limited, payable at JAIPUR. Tender fee, EMD and processing fee DD Should be submitted physically at the office of RAJASTHAN STATE SPORTS COUNCIL, JAIPUR, and Scanned copy of same should also be uploaded along with the technical bid.
- 4. RAJASTHAN STATE SPORTS COUNCIL, JAIPUR will not be responsible for delay in online submission due to any reason. For this, bidders are requested to upload the complete bid well advance in time so as to avoid Last hours issues like slow speed; choking of web site due to heavy load or any other unforeseen problems.
- 5. Bidders are also advised to refer "Bidders Manual Kit" available at e-Proc website for further details about the e-tendering process.
- 6. No contractual obligation, whatsoever shall arise from the bidding process unless and until a formal contract is signed and executed between the tendering authority and the successful Bidder.

SECRETARY



#### **UNDERTAKING BY THE BIDDER**

This is to certify that I/we before signing this tender have read and fully understood all the terms and conditions contained herein and undertake myself/ourselves to abide by them. I/We have signed all the pages in acceptance of the terms and conditions.

I/We also undertake that I/We will not adopt any malpractices at any stage of bidding/execution.

Signature of the Bidder with Seal Name:
Designation:
Address:



## BIDDER'S AUTHORIZATION CERTIFICATE (to be filled by the bidder)

To,
{Tendering Authority},
I/ We{Name/Designation} hereby
declare/ certify that
documents on behalf of the company/ firm in dealing with Tender with RAJASTHAN
STATE SPORTS COUNCIL, JAIPUR.
He/ She is also authorized to attend meetings & submit technical & commercia
information/ clarifications as may be required by you in the course of processing the Bid.
For the purpose of validation, his/ her verified signatures are as under.
Thanking you,
Name of the Bidder: - Verified Signature:
Authorized Signatory: -
Seal of the Organization: -
Date:
Place:



## CHECKLIST OF DOCUMENTS SUBMITTED

S. No.	Documents to be submitted	Submitted	Not Submitted	Page No.
1.	Scanned Copies of tender document fee, EMD and processing fees		90 (4)	E 8
2.	Copy of Registration of firms (A & Above Class Certificate by Work Department of Govt.)		a a	
3.	Copy of GST Registration	\$ 4.85	a a	h 19
4.	Copy of PAN Card	2 ° 4	19	H V
5.	Proof of Work Order and Work Satisfactory of Electrical work (Minimum work order Rs. 50% of Tender cost) in financial Year 2018-19, 2019-20.	E 25		
6.	Financial Year 2019-20 audited statement and Turn Over must be at least equal to this tender cost from Chartered Accountant in proof of Electrical work.		e e	
7.	Annexure A to D duly signed in context to RTPP Rules – 2013.			KY <sub>T.M.</sub>
8.	Authorization certificate If the tender is signed other than owners		2	S 8
9.	Copy of GST paid certificate for the month of November, 2020 in gstr-3b Performa	2 1 = 1 = 1 = 1 = 1 = 1 = 1 = 1 = 1 = 1		N. NI DI
10.	Tender document and Technical Bid and undertaking all three duly signed	*		`
11.	Any other Document	5		100

Signature of Bidder Seal of Establishment Full Name of Bidder with address and date



### **G Schedule**

Name of work :-- Annual maintenance work (Electrical) in S.M.S.Stadium, Jaipur.

Rates are Based BSR-2013 & Amendments on PWD Electrical Circle & BSR-2019, Jaipur

S. No.	Qua	ntity	Particulars		te	Amount
1	with 1.5 sq. mm flexible copper con size FR PVC insulat 1.1 kV grade (IS:6 ( IS:14927 P - II ) tiles,18 SWG M.S. thick ISI marked screws, cup was		Wiring of light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper conductor 1.1 kV grade and 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper earth conductor 1.1 kV grade (IS:694) of approved make on surface ISI marked (IS:14927 P - II) PVC casing capping & it's accessories, round tiles,18 SWG M.S. box with earth terminal, 6 A switch, 3.0 mm thick ISI marked phenolic laminated sheet, zinc plated / brass screws, cup washers, making connections, testing etc. as required.			
i)	1.00	P. point	Short point (up to 3 mtr.)	194.00	P. point	194.00
ii)	1.00		Medium point (up to 6 mtr.)	293.00	P. point	293.00
iii)	1.00		Long point (up to 10 mtr)	415.00	P. point	415.00
2			Wiring of 3 pin 5 amp. Light plug point with 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper conductor 1.1 kV grade and 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper earth conductor 1.1 kV grade(IS:694) of approved make on surface ISI marked (IS:14927 P - II) PVC casing capping & it's accessories, 18 SWG 175 mm x 100 mm x 60 mm M.S. box with earth terminal, 6 A switch, 6 A socket, 3.0 mm thick ISI marked phenolic laminated sheet, zinc plated / brass screws, cup washers, making connections, testing etc. as required.			
i)	1.00	P. point	On board	91.00	P. point	91.00
ii)	1.00		Short point (up to 3 mtr.)	232.00	P. point	232.00
ii)	1.00		Medium point (up to 6 mtr.)	326.00	P. point	326.00
v)	1.00		Long point (up to 10 mtr)	442.00	P. point	442.00
3			S&F following sizes of ISI marked ( IS:14927 P - II ) PVC casing capping along with accessories like coupler, inner, outer, elbow, square box, tee etc. on surface with screws, expansion fasteners as required.			
i)	1.00	R. mtr.	20 mm x 12 mm	24.00	R. mtr.	24.00
ii)	1.00	R. mtr.	25 mm x 12 mm	28.00	R. mtr.	28.00
iii)	1.00	R. mtr.	32 mm x 12 mm	34.00	R. mtr.	34.00
4			Wiring of light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper conductor 1.1 kV grade and 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper earth conductor 1.1 kV grade (IS:694) of approved make in surface / recessed ISI marked MMS ( IS:9537 P - III ) PVC conduit & it's accessories, round tiles,18 SWG M.S. box with earth terminal, 6 A switch, 3.0 mm thick ISI marked phenolic laminated sheet, zinc plated / brass screws, cup washers, making connections, testing etc. as required.			
i)	1.00	D point		215.00	D. point	215.00
i) ii)	1.00	P. point P. point	Short point (up to 3 mtr.) Medium point (up to 6 mtr.)	215.00 338.00	P. point P. point	338.00
11/	1.00	P. point	Long point (up to 10 mtr)	474.00	P. point	474.00



-						
			Wiring of 3 pin 5 amp. Light plug point with 1.5 sq. mm nominal			
-			size FR PVC insulated unsheathed flexible copper conductor 1.1			
			kV grade and 1.5 sq. mm nominal size FR PVC insulated			
**		1	unsheathed flexible copper earth conductor 1.1 kV grade(IS:694)		1 2 2	
_			of approved make in surface / recessed ISI marked MMS (		1 1	
5			IS:9537 P - III ) PVC conduit & it's accessories, 18 SWG 175 mm			
-			x 100 mm x 60 mm M.S. box with earth terminal, 6 A switch, 6			
			A socket, 3.0 mm thick ISI marked phenolic laminated sheet,			
			zinc plated / brass screws, cup washers, making connections,			
#			testing etc. as required.			
i)	1.00	P point	On board	90.00	P. point	90.00
ii)	1.00	P. point	Short point (up to 3 mtr.)	251.00	P. point	251.00
iii)	1.00		Medium point (up to 6 mtr.)	368.00	P. point	368.00
iv)	1.00	P. point	Long point (up to 10 mtr)	498.00	P. point	498.00
	2100	11 50 111		150.00	T. pomic	130.00
. 1			S&F following sizes (dia.) of ISI marked medium duty PVC			
6			conduit along with accessories in surface / recessed using		- a	
			saddles, clamps, fastener as required including cutting the wall,			
			covering conduit and making good the same as required.			
i)	1.00	R. mtr.	20 mm	32.00	R. mtr.	32.00
ii)	1.00	R. mtr.	25 mm	42.00	R. mtr.	42.00
iii)	1.00	R. mtr.	32 mm	65.00	R. mtr.	65.00
			Supplying and drawing FR PVC insulated & unsheathed flexible			
			copper conductor ISI marked (IS:694) of 1.1 kV grade and			2
7			approved make in existing surface or recessed conduit/casing			
			capping including making connections etc. as required.			
:\	1.00	N/I		4400		1100
i) ii)	1.00	Mtr.	1 x 1.5 sq.mm	14.00	Mtr.	14.00
iii)	1.00	Mtr.	2 x 2.5 sq. mm. + 1x1.5sqmm	53.00	Mtr.	53.00
iv)	1.00	Mtr. Mtr.	2 x 4.0 sq. mm. + 1 x 2.5 sq. mm. 4 x 6.0 sq.mm	77.00	Mtr.	77.00 176.00
v)	1.00	Mtr.	1 x 2.5 sq.mm	176.00 21.00	Mtr.	21.00
vi)	1.00	Mtr.	4 x 10.0 sq.mm	305.00	Mtr.	305.00
vii)	1.00	Mtr.	1 x 4.0 sq.mm	30.00	Mtr.	30.00
1	1.00	Tici.	Supplying and drawing PVC jacketed with annealed bare copper	30.00	Mar.	30.00
			inner conductor & tinned copper conductor shielding foam PE			
8	1.00	Mtr.	dielectric coaxial cable of approved make in existing surface or	23.00	Mtr.	23.00
		All Allestys.	recessed conduit/casing capping including making connections as			
			required PG - 6			
			Supplying and drawing PVC/ Polythene insulated and PVC			
			sheathed unarmoured/ armoured telephone cable with 0.5 mm			
9			dia. Tinned / annealed copper conductor taped &confirming to			
			ITD specification S/WS -113C of approved make in existing			
			surface or recessed conduit/casing capping.		1 "	
-			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			
a			Unarmoured Telephone cable in existing surface or recessed			
i)	1.00	Mtr.	conduit/casing capping.	12.00	Men	12.00
ii)	1.00	Mtr.	2 pair 5 pair	13.00 25.00	Mtr.	13.00 25.00
")	1.00	PICE.	Jelly filled armoured (PIJF) Armoured telephone cable including	25.00	MILI.	23.00
			excavation of 30cmx75cm size trench, 25 cm thick under layer			
10			of sand, IInd class bricks covering, refilling earth, compaction of			
-						
			earth, making necessary connection, testing etc. as required of			
i)	1.00	Mtr.	5 pair	136.00	Mtr.	136.00
	2.00	1101		100.00	11011	-30.00
			Supplying and fixing of power plug point accessories on 18 SWG			
11	1.00	Fact	metal box of size 175 x 100 x 60 mm. on surface or in recessed	225.00	CL	225.00
11	1.00	Each	with suitable size phenolic laminated sheet cover including cost	235.00	Each	235.00
			of 6 pin 16 amp. Switch and socket outlet , making connection ,			
			testing , etc. as required.			
		41 -1	P/Laying ISI marked P.V.C. insulated submersible cable			
12			confirming to IS:694 with flexible copper conductor including			
			making connection etc. as required.			1
i)	1.00	Mtr.	2.5 Sq.mm 3 core flat / Round	59.00	Mtr.	59.00
ii)	1.00	Mtr.	4.0 Sq.mm 3 core flat / Round	128.00	Mtr.	128.00
jii)	1.00	Mtr.	6.0 Sq.mm 3 core flat / Round	188.00	Mtr.	188.00



13	1.00	Each	P & F Krone module with base frame in the recess / surface made out of 16 SWG sheet steel box, front openable, having locking arrangements duly powder painted, including dressing, ferruling and punching of telephone cable with krone tool etc.	987.00	Each	987.00
14	1.00	Each	Supplying and fixing of power plug point Modular accessories on hot dipped galvanized modular on surface or in recessed with suitable size of grid plate with cover plate including cost of modular 16 amp. Switch and socket outlet , making connection , testing , etc. as required.	538.00	Each	538.00
15			P&F 240/415 V AC MCB with positive isolation of breaking capacity not less than 10 KA (B/ C/ D tripping characteristic) ISI marked IS 8828(1996)]/ conforming to IEC 60898 in existing board/sheets including making connections, testing etc. as	,		
a			Single pole MCB			151.00
i)	1.00	Each	6 A to 32 A rating	151.00	Each	151.00
b	1.00	Each	Double pole MCB 40 A 63 A rating	689.00	Each	689.00
i) C	1.00	Each	Triple pole MCB	009.00	Lacii	003.00
i)	1.00	Each	6 A to 32 A rating	688.00	Each	688.00
ii)	1.00	Each	40 A 63 A rating	1034.00	Each	1034.00
d			Four pole MCB			
i)	1.00	Each	40 A 63 A rating	1378.00	Each	1378.00
16			P&F Recessed/ Surface mounting heavy duty horizontal type sheet steel Distribution board phophatised/ powder painted complete with suitable rating insulated copper bus bar, shorting link , neutral link, earth link and din bar,masking sheet, conforming to IS13032 & IS8623 including making internal DB terminations with copper lugs , testing etc. as required.			
a			Double door (single phase)			
i)	1.00	Each	8 Way	897.00	Each	897.00
ii)	1.00	Each	12 Way	1065.00	Each	1065.00
b			Double door (Three phase)	1820.00	Foob	1820.00
i)	1.00	Each Each	4 Way 8 Way	2480.00	Each Each	2480.00
ii) 17	1.00	Edeli	P&F metal clad industrial plug top & socket unit with pin and sleeve type contact on porcelain/ bakelite base in sheet steel enclosure (without MCB) including making connections, testing etc. as required.	2100100		
a			Single / Double Pole (Three pin)		- 1	725.00
i)	1.00	Each	20 A	725.00	Each	725.00
18			P&F recessed/ surface mounting heavy duty Vertical type 16 SWG sheet steel Distribution board with provision of incomer suitable for MCCB and SP / TP MCB as outgoing , phophatised ,powder painted complete with insulated suitable rating copper bus bar , neutral link, earth link and din bar, masking sheet & conforming to IS13032 & IS8623 including making internal DB terminations with copper lugs , testing etc. as required.			
			Double door with Provision of Incomer MCCB 100 / 125	1 7		
a			A Rating	F770.00	F . '	F770.00
i)	1.00	Each	8 Way	5770.00	Each	5770.00
19	1.00	Each	P & F ISI marked (IS :3854) 6 amp. flush type switch including cutting hole in tile and making connection testing etc. as required.		Each	19.00
20	1.00	Each	P & F ISI marked (IS:3854) 16 amp. flush type switch including cutting hole in tile and making connection testing etc. as required.		Each	47.00
			P & F of 3 pin 6 amp. flush type socket including cutting hole in		- 1	20.00
21	1.00	Each	tile and making connection testing etc. as required.	20.00	Each	20.00



2 1						
23	1.00	Each	P & F IS:371 marked 6 amp surface type ceiling rose including making connection testing etc. as required.	18.00	Each	18.00
- 24	1.00	Each	P & F ISI marked 6 amp bakelite batten/angle holder including making connection testing etc. as required.	20.00	Each	20.00
25	1.00	Each	P & F ISI marked 6 amp bakelite unbreakable 3 pin plug top including making connection testing etc. as required.	30.00	Each	30.00
26	1.00	Each	P & F ISI marked 16 amp bakelite unbreakable 3 pin plug top including making connection testing etc. as required.	45.00	Each	45.00
27	1.00	Each	P & F socket size flush type 120/280 watt rotary 5 step fan regulator including making connection testing etc. as required.	210.00	Each	210.00
28	1.00	Each	P & F ISI marked single tone electronic call bell including making connection testing etc. as required.	225.00	Each	225.00
29	1.00	Each	P & F of Multiple socket with surge and spikes protection cartridge and minimum four nos. universal 6 A sockets, one 6 A switch and plug top including making connection etc as required.	574.00	Each	574.00
30	1.00	Mtr.	S & F of PVC trunking system for cable management including finishing accessories like corners, tee, adjustable angles, junction etc. as required. The trunking system shall have adaptable system for modular type RJ 45 data socket/ wiring accessories/ power sockets and shall be covered with peal off plastic cover.	675.00	Mtr.	675.00
31	1.00	S.mtr.	SITC of wall/ free standing floor mounted dust and vermin proof compartmentalised cubical panel made out of CRCA sheet , required hardware ,duly treated for derusting in 7 tank process with dephosphating and with powder coating on both side of panel in desired shade. The panel having PU/ Neoprene rubber gasket of not less than 3mm thickness , separate detachable gland plate M.S. base channel ,hinged door with locking arrangement for equipment/switchgear. Thickness of sheet shall not be less than 1.6 mm up to 600 mm length / width of any compartment and be of 2.0 mm above 600 mm. Load bearing structure shall be of 2.0 mm thick sheet supported by base M.S. channel if required. Side walls and cable alley compartments having bolted type doors with / without detachable extension type structure. (only outer area on all sides shall be measured & panel to be fabricated from CPRI approved fabricator)	2752.00	S.mtr.	2752.00
32	1.00	Kg	Supplying and fixing of Aluminium / Copper bus bar by means of SMC / DMC type insulator, high tensile nuts and bolts spring washers in existing panel including bending , cutting in required shape and size and colour coding with heat shrinkable PVC sleeves. Electrolytic grade Aluminium bus bar	420.00	Kg	420.00
33	1.00	Each	SF of (0-500) V range Volt meter on existing panel , making connection by PVC insulated copper conductor with PVC sleeves / channel etc. as required. Analog type ( 96 mm x 96 mm )	570.00	Each	570.00
34			SF of CT operated direct reading type Ampere meter on existing panel , making connection by PVC insulated copper conductor with PVC sleeves / channel etc. as required.	w	×	
a	4.65		Analog type ( 96 mm x 96 mm )			
i) b	1.00	Each	Below 500 A Digital type	375.00	Each	375.00
i)	1.00	Each	Below 500 A	1100.00	Each	1100.00
35	1.00	Each	SF of Current Transformer , with all necessary support in existing panel including connection etc. as required . from 200 / 5 to 400/5 Ratio . 10 VA . class 1 accuracy	323.00	Each	323.00
36	1.00	Each	SF of selector switch of 10 A for voltmeter (4 position ) including making connection etc. as required.	228.00	Each	228.00
	1.00	Each	SF of CT linked selector switch of 10 A for Ampere meter (4)	286.00	Each	286.00

Tind

			II or 1 to 500g 1 1151 Necessed full box, flexaddollar foulto the size 1		- 1	
44	1.00	Each	and making good the same, with cement plaster as required of following size: Un to 457 mm size  P & F 18 swg M.S. Recessed fan box, hexagonal/ round of size	200.00	Each	200.00
ii)	1.00	Mtr.	10 SWG G.I. ( Hot Dipped ) Wire  Making of hole in wall of required size for housing exhaust fan	6.00	Mtr.	6.00
)	1.00	Mtr.	8 SWG copper Wire	79.00	Mtr.	79.00
,	4.00		saddles, making connection etc. as required.			
3			run in ground/surface/recess including riveting, soldering,			
		100.000	S & Laying following size earth wire/strip in horizontal or vertical			2,00,00
)	1.00	Set	GI pipe 2000 mm long, 80 / 40 mm, Terminal 12 mm GI Strip	9750.00	Set	9750.00
a			with Pipe in Pipe Technology (Inner pipe dia. / Outer pipe dia. ) 80 - 100 micron GI Coating			
-			earth resistance as required. of following sizes.  With Pipe in Pipe Technology (Inner pipe dia. / Outer	:		
			long time to create low resistance zone ) and C.C. finished chamber covered with hinged type with locking arrangement C.I. Cover, C.I. Frame of size 300mm x 300mm complete testing of	- ,		
2			& surrounding filled with required mineral filling compound (MFC should have hygroscopic property to retain the moisture for			
			technology filled with anti corrosive conductive compound (CPRI Tested ) below the ground in 150 - 200 mm dia. earth pit			
1	1.00	Set	size of Armoured PVC insulated & PVC sheathed/ XLPE aluminium conductor cable of 1100 volt grade as required of Maintenance free Gel Earthing with Pipe in pipe / Pipe in strip	114.00	Set	114.00
1	1.00		Supplying and making one end termination with heavy duty single compression brass gland SIBG type, heavy duty aluminium lugs duly crimped with crimping tool, PVC tape etc for following	4		
) i)	1.00	Mtr. Mtr.	<b>120.0 Sq.mm 3.5 core</b> 185.0 Sq.mm 3.5 core	636.00 917.00	Mtr. Mtr.	636.00 917.00
)	1.00	Mtr.	50.0 Sq.mm 3.5 core	299.00	Mtr.	299.00
()	1.00	Mtr.	25.0 Sq.mm 3.5 Core	208.00	Mtr.	208.00
i)	1.00	Mtr.	16.0 Sq.mm 4 Core	178.00	Mtr.	178.00
)	1.00	Mtr.	10.0 Sq.mm 4 Core	170.00	Mtr.	170.00
)	1.00	Mtr.	6.0 Sq.mm 4 Core	146.00	Mtr.	146.00
0			KV grade with aluminium conductor of IS:1554 P-I / IS:7098 P-I of Group 1 of approved make in ground as per IS:1255 including excavation of 30cmx75cm size trench, 25 cm thick under layer of sand,IInd class bricks covering, refilling earth,compaction of earth, making necessary connection, testing			
i)	1.00	Each	P/Laying P.V.C. / XLPE insulated & P.V.C. sheathed cable of 1.1	23821.00	Each	23821.00
			% Icu 400 Amp ,35 kA, adjustable O/L & adjustable S/C setting, Ics =	18989.00	Each	18989.00
'') '')	1.00	Each	100 % Icu 250 Amp , 35 kA, adjustable O/L & fixed S/C setting, Ics = 100	16210.00 18989.00	Each	16210.00
ii) ii)	1.00	Each Each	Icu 200 Amp , 25/35kA, adjustable O/L & fixed S/C setting, Ics =	9095.00	Each	9095.00
			100 % Icu 160 Amp, 25 kA, adjustable O/L & fixed S/C setting, Ics = 100 %	6341.00	Each	6341.00
a i)	1.00	Each	With Thermal Magnetic release  up to 100 Amp , 25 kA, adjustable O/L & fixed S/C setting, Ics =	6241.00	Each	6241.00
2			fault trip, push (test) to trip, including making connections with lugs & spreaders, etc. as required.	18		
39			capacity at 440/415 V, 50 Hz; O/L & S/C settings and conforming to IS 60947-2 / IEC 60947-2 with front face and centralised adjustable, line load interchangeability, having positive isolation capability, provision for UVR, shunt trip ,earth			
			SITC of quick make and quick break 4 POLE current limiting MCCB having following current rating, short circuit breaking	× ×		a 2 4
	1	×	integral circuit, terminal block, including connection etc. as required Red/yellow/Green colour	150.00	Each	150.00

Graf

			P&F of Double ball bearing, capacitor start single phase metallic			
16			blade fresh air fan, in existing opening including cost of hardware, flexible copper conductor ,making connections, testing			
i)	1.00	Each	etc. as required 225 mm sweep	1614.00	Each	1614.00
i)	1.00	Each	300 mm sweep	1856.00	Each	1856.00
17	1.00	Each	P&F of Heavy duty capacitor start, Double ball bearing 900/1400 RPM single phase ISI marked Exhaust fan,IS:2312 marked in existing opening including making connections testing etc. as required. 300 mm sweep(900/1400 RPM)	3002.00	Each	3002.00
18	1.00	Each	P & F of capacitor start, metal body, metal blade three speed wall mounting fan of following sweep with the help of anchor bolts including making connection testing etc. as required. 400 mm sweep(Oscillating type)	2649.00	Each	2649.00
19	1.00	Mtr.	P & F extra down rod of 15 mm dia . ERW (Electrical resistance welded ) of 1.6mm nominal thick medium duty steel pipe including cutting, threading, drilling, fixing quarter pin etc as read	89.00	Mtr.	89.00
50	1.00	Each	P & F of Gravity Louver shutter of superior quality made out of frame of 18 swg M.S. sheet & Louvers made from 24 swg MS Sheet with enamel paint including cost of nuts, bolts, etc as read. Up to 380 mm size	169.00	Each	169.00
51			P & F box type fluorescent tube fitting fabricated from CRCA sheet and finished with powder coating / stove enamelled paint complete with accessories (Low Loss Copper Choke, starter, starter seat) / Electronic Choke with terminal block duly prewired with copper conductor including making connection, testing etc. as required( without tube).			
)	1.00	Each	1 X 36 Watts with EB	855.00	Each	855.00
i)	1.00	Each	1 X 28 Watts with EB	911.00	Each	911.00
52			P & F Mirror optics type fluorescent tube fitting fabricated from CRCA sheet and finished with powder coating,having aluminium mirror reflector,low glare V shape double parabolic cross louvers,complete with accessories like (Low Loss Copper Choke, starter, starter seat) / Electronic Choke with terminal block duly prewired with copper conductor including making connection, testing etc. as equired. ( without tube)			
a			Surface mounting			
)	1.00	Each	2 X 36 Watts with OCCB	3769.00	Each	3769.00
53			P & F of IP20 LED batten type light fixture made from CRCA sheet steel housing suitable for moutning LED tube system (integral driver), Power Consumption of 18W / 36W 1500-3000 lumens, system lumen efficiency 80 lm/Watt output, life time of 50,000 burning hours with 70% initial lumen maintained. CCT 3000°K, 4000°K & 6000°K.			
		Fl	4' LED Tube shape fixture 18W	4500.00	Each	4500.00
	1.00	Fach	, and disappe interest to the	1000.00	Lucii	1300.00
i)	1.00	Each	P & F Fluorscent tube rod in existing fixtures as required			
i) 54	1.00	Each	P & F Fluorscent tube rod in existing fixtures as required, Flourscent powder coated (minimum 3 star rating)			
i) 54 a			Flourscent powder coated (minimum 3 star rating)	59.00	Each	59.00
i) 54 a i)	1.00 1.00 1.00	Each Each		59.00 63.00	Each Each	59.00 63.00



55			P & F of IP20 LED ceiling / recessed / suspended mounting light fixture made from CRCA sheet steel housing, high purity / transmisivity diffuser for uniform light distribution. High efficiency driver electronics having efficiency > 85% and in compliance to IEC standards (Integral with light fixture). Power Consumption of 40W / 50W / 60W ~ 3000/3300/4200 lumens, System lumen efficacy of 70 - 80 lm/Watt output suitable for 2x36WFTL / 2x36W CFL / 3x36W CFL light fixtures, life time of 50,000 burning hours with 70% initial lumens maintained. CCT 3000°K, 4000°K & 6000°K. Fixtures shall be CE compliance. Recessed Mounting			
i)	1.00	Each	36W LED light fixture 1'x4' with acrylic / prismatic front cover.	13500.00	Each	13500.00
ii)	1.00	Each	36W LED light fixture 2'x2' with acrylic / prismatic front cover.	12500.00	Each	12500.00
56	1.00	Each	Vacuum pressure impregnated open construction(VPIT) copper ballast 18/36 Watts for FTL	293.00	Each	293.00
57	1.00	Each	High frequency electronic ballast 18/36 watts for FTL	575.00	Each	575.00
58	1.00	Each	High frequency electronic ballast 9/11/13/18 watts for CFL.	350.00	Each	350.00
59	1.00	Each	High frequency electronic ballast 28 watts for T5 Lamps	563.00	Each	563.00
60	1.00	Each	P & F starter for existing fluorscent lamp fixture as required. FSU	11.00	Each	11.00
61	1.00	Each	P & F of recess mounting CFL luminaire made from powder coated CRCA sheet with perforations on the body with metalised polystrene louvers, complete with accessories extra low watt loss copper ballast, starter, holder, condensor, terminal block duly prewired with copper conductor including making connections, testing etc. as required (without lamp). 3 X PL-36 Watt CFL	5015.00	Each	5015.00
62			P & F of surface/ recess mounting CFL luminaire made from powder coated CRCA sheet with aluminium reflector assembly electrochemically brightened and anodized cross louvers, complete with accessories copper ballast, starter, holder, terminal block duly prewired with copper conductor including making connections, testing etc. as required (without lamp)			
а			Surface mounting			
i)	1.00	Each	2 X PL-9/11 Watt Note :- Add extra @10% for fixture with EB	1294.00	Each	1294.00
60			P & F of IP20 LED Recessed / Surface Mounted Round / Sqaure Dimmable Downlight with diecast aluminum housing & Heat Sink for heat dissipation, high purity reflector with external driver having efficiency > 85% and in compliance to IEC standards. Power Consumption of ≤ 15W / 20Wwith ~1100 / 1400 lumens, System Lumen efficacy of 70 lm/Watt output Downlights, life time of 50000 Burning Hours with 70% of intial Lumen maintaned. CCT 3000°K , 4000°K & 6000°K. Fixture shall be CE compliance.			
i)	1.00	Each	LED Downlight 18/20W	4000.00	Each	4000.00
63	1.00	Each	P & F energy efficient / energy saving direct fit (Retrofit) composite self ballasted compact fluorscent lamp (CFL) with PF >0.85 in existing holder / fixture as required. 14/15 Watt	180.00	Each	180.00
			D C E tue sin anargu officient compact fluoresent lama in	1		
64			P & F two pin energy efficient compact fluorscent lamp in			
64	1.00	Each	existing holder/fixture as required.		Each	113.00
	1.00	Each Each		113.00 242.00	Each Each	113.00 242.00

Jul

	1.00	Each	1 X 400 Watt	8170.00	Each	8170.00
ii)	1.00	Each	1 X 250 Watt	7150.00	Each	7150.00
i)	1.00	Each	1 X 150 Watt	5350.00	Each	5350.00
			block including making connection testing etc. as required. (with out lamp)	5		-
			gear box having copper ballast, capacitor, electronic ignitor prewired with pvc insulated copper conductor up to terminal			
70			resistant and toughened glass, porcelain holder, integral control			
			aluminium housing, electrochemically brightened and anodized stippled aluminium reflector, covered with suitably gasketed heat			
			P & F IP -65 protected integral flood light luminaire suitable for HPSV/ Metal halide lamp comprising of powder coated die cast			
11)	1.00	Each	1 X 250 Watt	6330.00	Each	0330.00
i) i)	1.00	Each	1 X 150 Watt	6045.00	Each	6330.00
a i\	1.00	Each	Fixture suitable for HPSV Lamp	604F 00	Each	6045.00
-					,	
			testing etc. as required (without lamp)			
2			terminal block etc. as required including making connection			
			ballast, electronic ignitor, capacitor, holder prewired up to			
59			resistant and toughened glass cover and accessories like copper			
			brightened and anodized POT optics aluminium reflector, heat			
			single piece die cast aluminium housing, electrochemically			
			suitable for HPSV/ MH LAMP, made out from powder coated		-	
			P & F IP-66 protected street light luminaire on existing bracket			
i)	1.00	Each	400 Watt	2800.00	Each	2800.00
i)	1.00	Each	250 Watt	1850.00	Each	1850.00
)	1.00	Each	150 Watt	1530.00	Each	1530.00
a			For HPSV/Metal halide lamp			
			The state of the s	-		
8			HPMV / HPSV / Metal halide lamp luminaire as required.			
			P & F vacuum pressure impregnated copper ballast suitable for			
57	1.00	Each	P & F Electronic ignitor suitable for HPSV/ Metal halide lamp up to 30.0 Mtr. distance as required.	270.00	Each	270.00
ii)	1.00	Each	43 mfd	470.00	Each	470.00
i)	1.00	Each	33 mfd	450.00	Each	450.00
i)	1.00	Each	20 mfd	285.00	Each	285.00
56			HPSV/ HPMV/ Metal halide lamp fixture as required.			
			P & F Capacitors for power factor improvement in existing			
i)	1.00	Each	400 Watt	1140.00	Each	1140.00
)	1.00	Each	250 Watt	1060.00	Each	1060.00
)	1.00	Each	150 Watt	950.00	Each	950.00
c			Metal halide lamp single ended tubular	000.00		
i)	1.00	Each	400 Watt 56500 Lumens	830.00	Each	830.00
b	1.00	Lacii	HPSV Tubular lamp High Output	030.00	Lacii	050.00
i)	1.00	Each	400 Watt 48000 Lumens	650.00	Each	650.00
1	1.00	Each Each	150 Watt 15000 Lumens 250 Watt 28000 Lumens	465.00 550.00	Each Each	465.00 550.00



71			P&F.of Ip65 prolect@ Luminaire on existing bracket. pressure die cast aluminum with-heat dissipation fins on housing with UV stabilized pClToughened ClIss cover (from 45W onwa.ds ) and ,t oufa be secondary lens on each LED The System level Luminaire efficacy >=100 yjt!_ High power Le Ds of cree/N rcH rAlo sRA M / pHrLti i /sEo uL make is to be used .ihe LEo nriver shall be BIS cerrified and Inpui Vottrg. AC 110 to 270 V AC with Input Frequency S0Hz!30/o power Factor >0.95 Driver Efficiency >BSo/0, THDII) <'1.00/o Humidity LOo/o to gOVo RH Working Temp _zOC ro 50C . Life Expectancy Equal or more than 50000 burning hrs with Minimum iO;), inirial lumens maintained,Renderinf Ina., :-7!%.Surge protection shall Ue"min > S KV internal and min 10 KV external. Manufactures Word t tr.t /ruu Engraved/Embossed on die' cast housing to allow traceabiliry/authenticity till life of 50}re. Fixtures shall be CE cornpiirn.A.			
i)	1.00	Each	LED Street Light fixture 30 W	2385.00	Each	2385.00
ii)	1.00	Each	LED Street Light fixture 70 W	5063.00	Each	5063.00
iii)	1.00	Each	LED Street Light fixture 120 W	9275.00	Each	9275.00
72	1.00	Mtr.	S & F of Street light bracket made out from following size of 'B' class GI pipe with heavy duty pole clamp, Saddles suitable fastners etc. as required, 40 mm Dia.		Mtr.	500.00
73	1.00	Each	P & F of IP-65 Protected high Power ,ED flood light sYstem with Pressure liecast aluminium housing , toughened 3lass diffuser with suitable lenses on LED to achieve various beam angles, Z4O volt, 50H2, of high Power LED [ixture supplied with pre wired cable of 1 mtr. Integrated driver shall be high efficiency having efficiency more than 85 o/o and in comPliance to IEC standards/BIS certified. The System level Luminaire efficacy >=100 with High Power LEDs of CRE E/N I CH IAIO S RAM / PH I LI PS/SE OUL make is to be used . LED Driver InPut Voltage AC L10 to 270 V AC with Auto resetting Safery Cut-off. InPut Frequency 50Hzt 3o/o Power Factor >0.95 Driver Efficiency >850/o ,Control Gear Integral Design, THD[I) =5KV internal and 10KV external in BOW onwards,Humidiry t\o/o to 900/o RH Working TemP -ZTC to 50C LED Luminaire Specifications: Life Expectancy Equal or more than 50000 burning hrs with Minimum 700/o lumen maintenance.Manufactures Word Mark/Name Engraved/Embossed on die cast housing to allow traceability/authenticity till life of fixture. Fixtures shall be CE complianed		Each	7830.00
i)	1.00	Each	High Porver LED Flood Light 100W	7830.00	Each	7830.00
ii)	1.00	Each	High Power LED Flood Light 150W	11655.00	Each	11655.00
iii) 74	1.00	Each	High Power LED Flood Light 240W  Rewinding of ceiling fan motor (starting and running winding) including all necessary material. The motor is to be wound taking no. of coils, turns and pitch as it was originally wound with required size super enamelled wire with 'E' class insulation material and making connections etc. as required. (New model		Each	27682.00
i)	1.00	Each	900/1200 mm sweep (New model ceiling fan)	270.00	Each	270.00
ii)	1.00	Each	All sizes (Old model ceiling fan)	786.00	Each	786.00
75	1.00	Each	Labour charges for removing and refixing of Ceiling fan/ Exaust fan from site		Each	36.00



С	1.00	I D noint	II ong point (up to 10 mtr.)	508.00	P. point	508.00
U		P. point	Medium point (up to 6 mtr.) Long point (up to 10 mtr)	377.00	P. point	377.00
b	1.00			260.00	P. point	260.00
a	1.00	P. point	Modular switch, Modular plate with grid plate, screws, making connections, testing etc. as required.  Short point (up to 3 mtr.)	260.00	D. noint	260.00
85			1.1 kV grade (IS:694) of approved make in surface / recessed ISI marked medium duty PVC conduit & it's accessories, round tiles, Hot Dipped Galvanized Modular Box with earth terminal, 6 A			
			Wiring of light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper conductor 1.1 kV grade and 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper earth conductor			
ii)	1.00	Each	4.0 micro farad	51.00	Each	51.00
i)	1.00	Each	2.5/3.15 micro farad	39.00	Each	39.00
a			Running capacitor			- 3: 7 - 3
			Punsumi/ Priva/ Capital/ JEC/ AMCAP/ CONCAP make			
84	2.00	Lucii	S & F of capacitor of 230V/ 275V, 50Hz rating of Usha/	32304.00	Each	32964.00
i)	1.00	Each	respectively. 5.0 HP, 3-Ø, (120-220)Mtr, (100-38)LPM	32964.00	Each	32064.00
a			following HP Rating, phase, Head, minimum Discharge			
			100 mm diameter Submersible pump shall have			-
			water to water mains, complete in all respect.			
			All labour for testing of submersible pumps set and supply of			
			and accessories, jointing of electrical cables up to switch board.			
83			D.C.B./ Open well. The job includes lowering of riser pipe, G.I./ H.D.P.E. pipe with rope, cables, installation of complete fitting			
			accessories including making connection suitable for T.W./			
			marked (IS:8034-1989) of approved make with required			
			SITC of radial / mixed flow submersible motor pump sets ISI			
b	1.00	Each	Delowering and Lowering	3555.00	Each	3555.00
a	1.00	Each	Lowering only	2592.00	Each	2592.00
			tripod, chain pulley block & any other material required for this			
82			including lowering/ delowering of pipes, cables, accessories etc. in tube-well/ open well complete including T&P, transportation of		5 5	
			Labour charges for installation of submersible motor pump set			
81	1.00	Each	necessary material and of the same characteristics as original with required size of super enamelled wire 'E' class insulation material and testing etc. as required. 0.75 H.P. To 1.0 H.P.	658.00	Each	658.00
			Rewinding of single phase motor of 1400 RPM including all		Each	2337.00
iii)	1.00	Each	10.0 H.P.	1649.00 2357.00	Each	1649.00 2357.00
i) ii)	1.00	Each Each	3.0 H.P. 5.0 H.P.	1255.00	Each	1255.00
:)	1.00	-	wire 'E' class insulation material and testing etc. as required.			
80			Rewinding of three phase squirrel cage induction motor of 1400 to 2800 RPM including all necessary material and of the same characteristics as original with required size of super enamelled	1 8		
79	1.00	Each	coils,turns and pitch as it was originally wound with required size super enamelled wire with 'E' class insulation material and making connections etc. as required. 457 mm sweep	491.00	Each	491.00
		AL.	Rewinding of Heavy duty Exhaust fan motor including all necessary material, The motor is to be wound taking no. of	4		
78	1.00	Each	submercible pump (Millborn/ Wonder make)	252.00	Each	252.00
77	1.00	Each	fan as required. (NBC/ SKF)	133.00	Each	133.00
-		+1	removing, refixing of fan from site and testing etc. as required.  Providing and Replacement of ball bearing of ceiling/ exhaust		20011	
76	1.00	Each	Charges for oiling, greasing, overhauling of ceiling fan, table fan, pedestal fan irrespect to the size of fan including		Each	60.00



			Wiring of 3 pin 5 amp. Light plug point with 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper conductor 1.1 kV grade and 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper earth conductor 1.1 kV grade(IS:694)			
86			of approved make in surface / recessed ISI marked medium duty PVC conduit & it's accessories, Hot Dipped Galvanized M.S Modular box of 20 SWG with earth terminal, 6 A modular switch, 6 A modular socket, Modular plate with grid plate, screws, making connections, testing etc. as required.		a 11	
a	1.00	P. point	On board	244.00	P. point	244.00
b	1.00		Short point (up to 3 mtr.)	339.00	P. point	339.00
С	1.00	P. point	Medium point (up to 6 mtr.)	445.00	P. point	445.00
87			P&F flush/surface type enclosure for housing MCB/Isolator with Din rail including making connections with lugs, repairs etc. as required.			E V
i			With sheet steel enclosure		-	
а	1.00	Each	Four way	315.00	Each	315.00
88			Supplying and making one end termination with heavy duty single compression brass gland SIBG type, heavy duty aluminium lugs duly crimped with crimping tool, PVC tape etc for following size of Armoured PVC insulated & PVC sheathed/ XLPE aluminium conductor cable of 1100 volt grade as required of			
a	1.00	Set	3.5 x 120.0 sq.mm	310.00	Set	310.00
b	1.00	Set	3.5 x 185.0 sq.mm	395.00	Set	395.00
С	1.00	Set	3.5 x 95.0 sq.mm	286.00	Set	286.00
d	1.00	Set	3.5 x 50.0 sq.mm	132.00	Set	132.00
89			P & F following modular accessories made out of unbreakable and fire retardant poly carbonate with silver contacts including making connections testing etc. as required			
а	1.00	Each	6 A one way switch	92.00	Each	92.00
b	1.00	Each	16 A one way switch	138.00	Each	138.00
С	1.00	Each	6 A 3 pin shuttered socket	120.00	Each	120.00
d	1.00	Each	16 A 6 pin shuttered socket	189.00	Each	189.00
е	1.00	Each	5 step fan regulator 2 Module	460.00	Each	460.00
f	1.00	Each	Blanking plate	19.00	Each	19.00
90			P & F in position frame made out of M.S. angle (riveted or welded) finished with two coats of red oxide and enamel paint including cutting, welding, holes etc.of following sizes as required			
a	1.00	Mtr.	40mm x 40mm x 5mm	209.00	Mtr.	209.00
91			P & F following size hot dip galvanized M.S. box of 20 SWG with earthing terminal in recess/ surface suitable for modular accessories as required.			
а	1.00	Each	1-2 Module	40.00	Each	40.00
J.	1.00	Lucii	SITC of Managed Layer-2 Intelligent Ethernet Switch providing	7 3 3		
92	1.00	Each	24 x 10/100 Fast Ethernet ports and with min 2 SFP Giga Ports (provision for Fiber Giga connectivity) with related LAN Base Software	41000.00	Each	41000.00
93	1.00	Each	Supply and Installation of Information outlets made of high impact plastic body ABS FR Grade with spring loaded collapsible shutters in jack Recess, suitable for Cat 6 application complying to latest ammendments EIA/ TIA 568 B.2-1 Specifications in existing modular /MS Boxes along with necessory connections as	380.00	Each	380.00
94			Supply & fixing of Faceplate for Flush / Surface Mount Information Outlets Single Aperture with screw hole covers & Icon Tree Size 86mmX86mm			
а	1.00	Each	Single Aperture	98.40	Each	98.40
b	1.00	Each	Dual Aperture	107.20	Each	107.20
С	1.00	Each	Quad Aperture	116.80	Each	116.80



95	1.00	Mtr.	Supply , Drawing and Testing of 4 pair, 24 AWG UTP Cat 6 Cable as per latest ammendments of TIA /EIA 568 B.2-1 Specifications in existing MS/PVC Conduits including making connections to Information outlets and Patch Panels with ferruling at both ends for identification with necessary tools for punching, stripping, crimping and testing required		Mtr.	36.00
96		- - 	Supply , Installation, Testing and Comissioning of Rack mounted 19", Cat 6 UTP,1.5-1.6 MM CRS chasis , powder coated Modular Patch Panels with collapsible shutters on jacks to support latest ammendments of TIA / EIA Cat 6 Specifications in Existing Communication Rack along with necessary connections of Cat 6 UTP Cables, With Rear Cable management trays and clamps.	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		7 S
а	1.00	Each	6 Ports	4400.00	Each	4400.00
b	1.00	Each	12 Ports	5400.00	Each	5400.00
С	1.00	Each	18 Ports	6400.00	Each	6400.00
d	1.00	Each	24 Ports	7400.00	Each	7400.00
97			Supply , Installation and Testing of 4 pair , 100 Ohm, 24 AWG , Cat 6 UTP, flexible , Double ended Patch Cords along with 2 No of RJ 45 connectors with strain relief transparent boots as per TIA /EIA 568 B.2-1 Specifications.			10.7
а	1.00	Each	1 Mtr/3 ft	250.00	Each	250.00
b	1.00	Each	2 Mtr / 7 ft	290.00	Each	290.00
C	1.00	Each	3 Mtr / 10 ft.	330.00	Each	330.00
98			P & F ISI marked (IS:2082) Horizontal storage water heater with outer casing made of M.S.sheet finished with anti-corrosive powder coating,inner tank made of pure electrolytic copper/stainless steel , Tubular copper sheathed and Nickel plated heating element/ twin ceremic cartridge heating element, stem type thermostat and thermal cut out,Dual indicating lamps for power supply and thermostat,PUF insulation, Pressure relase valve,fusible plug etc. as required held in position with 4 no. rack bolts,duly wired with 3 core 2.5/4.0 Sqmm PVC insulated & sheathed copper conductor and 16 A/25A three pin plug top,including making inlet,outlet heavy gauge C.P.	2		
			connection, testing etc. as required.			
99	1.00	Each	Supply , Installation, Testing and Comissioning of Wall mounted Communication rack with glass doors, handles ,lock , Top and Bottom Cable entries, Supports for mounting rack on wall , Cable managers, one Fan, Equipment mounting hardware, power supply box for supplying power to switches, fans etc along with earth continuity kit, Mcb, indicator, moulded power supply cable	-	Each	6486.00
а	1.00	Each	9 U(44 mm ) wall mounted	10500.00	Each	10500.00
100			Supply, Fixing and testing of following capacity wall mounted stablisers having output voltage variation from 200 V to 250 V(+/-5%) with input voltage variation from 170 V to 260 V, time delay facility from 2 to 4 minute and high cutoff at 270 V with providing of 16 Amp plug top making connection etc complete in			
а	1.00	Each	5 kVA	3100.00	Each	3100.00
101	2.00	and self	SITC of Air Cooled split type Air conditioners complete with Indoor unit(IDU), Out door unit (ODU), surface / concealed copper Refrigerant piping with insulation (EP foam pipe section) upto 3 Mtr (IDU to ODU), copper power cable upto 4 Mtr (IDU to ODU), R-22/R-410 Refrigerant, Remote, suitable for 400/230V +10% of 50 Hz ,1 /3 phase AC supply capable of performing cooling, dehumidification, air circulation of following capacity with Scroll / reciprocating / rotary compressor as specified.	2200,00	2001	
i -			Hi Wall/Ceiling Wall Split			
а	1.00	Each	1.5 TR with 5 star rating of BEE	58795.00	Each	58795.00
u						



10	1.00	Mtr.	per IS:1255 including excavation of 30cmx75cm size trench, 25 cm thick under layer of sand,IInd class bricks covering, refilling earth,compaction of earth, making necessary connection, testing etc. as required of size.50.0 Sq.mm 3.5 core	55.00	Mtr.	55.00
			P/Laying P.V.C. / XLPE insulated & P.V.C. sheathed cable of 1.1 KV grade with aluminium conductor of IS:1554 P-I / IS:7098 P - I of Group 1 of approved make in ground as			
109	1.00	Mtr.	Supply & fixing of GI pipes with flanges duly screwed & welded including rubber washer, nuts & bolts of 8mm dia complete in all respect ISI make.B class 80mm dia	404.00	Mtr.	404.00
	1.00	EdCII	3.0 HP to 10.0 HP	4560.00	Each	4560.00
a i	1.00	Each	Fully Automatic Star/ Delta Starter			-
.08			Supply and fixing of oil / Air break DOL / Star Delta Starter made out of sheet steel powder coated enclosure with single phasing protection, ON / OFF push buttons, etc. complete in all respect suitable for following rating motors.			
107	1.00	Each	P & F of M.S. J- hook of standard design made out of 16 mm dia. M.S. round bar and fixed with cement concrete mortar with required support as required.	135.00	Each	135.00
u	1.00	Each	7.5 Mtr. (410 SP - 5)	6408.00	Each	6408.00
a	1.00	Facility	terminals , cable entry, GI cable sleeve complete as required. The pole shall be fabricated by using ISI mark tube for structural purpose of following height & designation. (See Table E - 09 for specs.)			
106			C.C. of M-20 grade (1:1.5:3) from base plate to 50 cm above ground level, with the help of steel frame not less than 40 cm dia up to 114.3mm outer dia and 50 cm beyond 114.3mm outer dia			
			Tr outdoor type of Split AC.  Supply and erection of M S swaged tubular pole conforming to IS: 2713-1980 (part I to II) with galvanised base plate in	1030.00	Each	1050.00
105	1.00	Each	Supply & fixing MS powder coated stand suitable for 1 0/1 5/ 2 0	1250.00	Each	1250.00
а	1.00	Each	50mm to 150mm	1250.00		
104			Making hole in stone masonary/ RCC with core cutter for accomodating refrigerant pipe/ drain pipe for split/ cassattee/		7 161.	273.00
103	1.00	Mtr.	S & F of rigid CPVC (20mm) drain piping of 6 kg/cm2 with 6mm thick nitrile rubber insulation.	275.00	Mtr.	900.00
a	1.00	Mtr.	19.05 mm	900.00	Mtr.	000.00
102			SITC of Interconnecting refrigerant pipe work with closed cel elastomeric nitrile rubber tubular insulation between each set of indoor & outdoor units as per specifications including chase cutting, supports etc. as required.	F		* 15



111	1.00	Mtr.	SITC of wall/ free standing floor mounted dust and vermin proof compartmentalised cubical panel made out of CRCA sheet , required hardware ,duly treated for derusting in 7 tank process with dephosphating and with powder coating on both side of panel in desired shade The panel having PU/ Neoprene rubber gasket of not less than 3mm thickness , separate detachable gland plate M.S. base channel ,hinged door with locking arrangement for equipment/switchgear . Thickness of sheet shall not be less than 1.6 mm up to 600 mm length / width of any compartment and be of 2.0 mm above 600 mm. Load bearing structure shall be of 2.0 mm thick sheet supported by base M.S. channel if required . Side walls and cable alley compartments having bolted type doors with / without detachable extension type structure. (only outer area on all sides shall be measured & panel to be fabricated from CPRI approved fabricator)	400.00	Mtr.	400.00
112 (i)	1.00	Set	S & Making Heat shrinkable type outdoor straight through joint for following size of PVC/ XLPE insulated aluminium conductor cable of 1.1 KV grade including cost of compound, sleeves etc. as required. 4 x 6.0 sq.mm	556.00	Set	556.00
(ii)	1.00	Set	3.5 x 120.0 sq.mm	1263.00	Set	1263.00
113	1.00	Mtr.	Add @ 350/- p.m. if Cable laid through Vernier Machine	350.00	Mtr.	350.00
114			Providing and fixing of IP 65 protectd Polycarbonate / Polysterene fuse box moulded with inside knock outs of following size with hinged cover, transparent window, PU gasket, locking arrangement, duly holded with 2 nos. pole clamps of 20 mm x 3 mm flat with nut and bolts, complete with The box shall be provided with Din rail, 4 / 8 way 10.0 / 16.0 sq.mm heavy duty connector, earth terminal,			
(i)	1.00	Each	125 mm X 200 mm X 122 mm	1200.00	Each	1200.00
115			S & F of PVC trunking system for cable management including finishing accessories like corners, tee, adjustable angles, junction etc. as required. The trunking system shall have adaptable system for modular type RJ 45 data socket/ wiring accessories/ power sockets and shall be covered with peal off plastic cover.			
(i)	1.00	Mtr.	150/160mm x 50mm	1150.00	Mtr.	1150.00
116			P&F of IP51 direct or CT operated, 1x240 / 3x240 volts , 50 Hz static watt-hour meter (kwh) having resolution 0.1 / 0.01 kwh , 1/ 0.5 accuracy class , LED indicators for tamper operation ( Reverse &/or earth connection) , pulsating LED indicator for meterology , electromechanical counter , LCD Display, cover plate for body and terminal sealing , including making connection			
1			tecting etc. as required			



117	1.00	Each	Supply, Installation, Testing & Commissioning of HT metering cubical panel as approved By DISCOMs fabricated out of 14 SWG CRCA sheet steel in two compartment & MS angle of size 60mmX6mm having provision for Following: (i)Provision for fixing Trivector Meter (To be supplied by DISCOMs) (ii)Provision for fixing of combined CT PT Set (To be supplied by DISCOMs), (iii)TT Block, (iv) 6mm Bakelite sheet on all sides, (V) 3/6 core copper cable for interconnections etc. as required.	20813.00	Each	20813.00
118			Providing of synthetic rope for submersible pump ISI			
	1.00	1.0	marked (IS:5175) of following sizes.			
(i)	1.00	Mtr.	12mm (suitable up to 50 mm OD pipe)	15.00	Mtr.	15.00
(iii)	1.00	Mtr.	16mm (suitable above 50mm & up to 75mm OD pipe) 20mm (suitable for 90 mm OD pipe)	25.00 38.00	Mtr.	25.00 38.00
119	1.00	MC.	SITC of self contained drinking water cooler with energy efficient hermetic sealed type compressor, non cFC refrigerant suitable for operation on230v/LpH/50H2 ac supply, Full stainless steel [S30a)body and tank, stainless steel water tray, minimum two nos faucets and suitable drainage system complete in all respect with 300mm height MS fabricated and painted plateform. complete in all respect of the following capacify		Mtr.	36.00
(i)	1.00	Each	cooling capacity 150 Ltr./Hr. and storage capaciw 150 Ltrs	59700.00	Each	59700.00
120			SITC of ISI mark( IS:8472) self priming monoblock pump set of approved make, TEFC, permanent split capacitor type (PSC), fitted with thermal overload protection, mechanical seal, 1440/1500 RPM, single phase(180 to 240 V). Including cost of hardware etc on existing platform complete. Pump shall have following HP Rating, phase, Head, minimum Discharge respectively.	1		
a			Self priming pumps			
(i)	1.00	Each	0.5 HP, 1-Ø, (6-28)Mtr, (52-12)LPM	3538.00	Each	3538.00
(ii)	1.00	Each	1.0/ 1.1 HP, 1-Ø, (10-50)Mtr, (53-6.5)LPM	5011,00	Each	5011.00
121			SITC of radial / mixed flow submersible motor pump sets ISI marked (IS:8034-1989) of approved make with required accessories including making connection suitable for T.W./ D.C.B./ Open well. The job includes lowering of riser pipe, G.I./ H.D.P.E. pipe with rope, cables, installation of complete fitting and accessories, jointing of electrical cables up to switch board. All labour for testing of submersible pumps set and supply of water to water			
a			100 mm diameter Submersible pump shall have following HP Rating, phase, Head, minimum Discharge respectively.			
(i)	1.00	Each	1.0 HP, 1-Ø, (30-78)Mtr, (46-18)LPM	17425.00	Each	17425.00
(ii)	1.00	Each	5.0 HP, 3-Ø, (120-220)Mtr, (100-38)LPM	32964.00	Each	32964.00
h			150 mm diameter Submersible pump shall have following HP Rating, phase, Head, minimum Discharge respectively.			
b						
(i)	1.00	Each	7.5 HP, 3-Ø, (45-73)Mtr. (400-280)LPM	27289.00	Each	27289.00
	1.00	Each Each	7.5 HP, 3-Ø, (45-73)Mtr, (400-280)LPM 10.0 HP, 3-Ø, (64-104)Mtr, (400-167)LPM	27289.00 33630.00	Each Each	27289.00 33630.00



			Providing and laying in position cement concrete including			
122	1.00	Cum	curing, compaction etc. complete in specified grade excluding the cost of centering and shuttering - All work up to plinth level. M15 grade Nominal Mix  1: 2: 4 (1 cement : 2 coarse sand : 4 graded stone aggregate 40mm nominal size)	5240.00	Cum	5240.00
123	1.00	Each	SITC of 1 KVA Line interactive,1.60-260 V,50 Hz ON-Line UPS with Isolation transformer suitable for single phase AC input and single phase AC output having enclosure degree of protection as per IS13947 Part-I/1993/2004 complete with all protection with SMF VRLA [12V, 7AH - 2nosl Batteries, Charser, Switchine Device etc.	\$ (A. 10.10.10.10.10.10.10.10.10.10.10.10.10.1	Each	7550.00
124			Supply and fixing of Oil / Air break Starter panel made out of sheet steel powder coated enclosure comprising of over load protection relay, short circuit & single phasing protection, ON / OFF push buttons, ammeter, voltmeter, indicating lamps etc. complete in all respect suitable for following rating motors.			
a			For single phase Submersible / Monoblock pump			
(i)	1.00	Each	0.5 HP to 3.0 HP	3150.00	Each	3150.00
b			For Three phase Submersible / Mono block pump			
(i)	1.00	Each	3.0 HP to 10.0 HP ( DOL )	4450.00	Each	4450.00
(ii)	1.00	Each	3.0 HP to 10.0 HP ( Star / Delta )	7850.00	Each	7850.00
(iii)	1.00	Each	12.5 HP to 17.5 HP ( Star / Delta )	10500.00	Each	10500.00
125 a			P & F G.I. pipes (Internal Work) with G.I. Fittings excluding union (IS:1239 Mark) & MS clamps including cutting and making good the walls and floors:  40mm dia nominal bore		,	<i>E</i>
(i)	1.00	Mtr.	B' Class	483.00	Mtr.	483.00
b	1.00	1-101.	65mm dia nominal bore	103.00	PICE.	703.00
D I						

Secretary Rajasthan State Sports Council Jaipur

I/We agree to execute the above work as per rate filled in related item. (Rate in words \$%\$ above/below)

Signature of Contractor With full Address





### RAJASTHAN STATE SPORTS COUNCIL

## **TENDER DOCUMENT**

#### FOR

Annual maintenance work (Painting) in S.M.S.Stadium, Jaipur.

NIT NO.

: NIT No. 33/2021-22

**ESTIMATED COST** 

Rs. 20.00 Lacs

**EARNEST MONEY** 

Rs. 40,000/-

DATE OF SALE / DOWNLOADING :

From Wednesday March 17, 2021, 17:00 Hours to

Wednesday March 30, 2021, 13:00 Hours

DATE OF RECEIPT (D.D. &

From Wednesday March 17, 2021, 17:00 Hours to

DOCUMENTS)

Wednesday March 30, 2021, 15:00 Hours

DATE OF OPENING OF TENDER

Wednesday March 30, 2021 AT 16:00 Hours

**COMPLETION PERIOD** 

01 (One) Year

**COST OF TENDER** 

Rs. 500/- in favour of Secretary, RSSC, Jaipur

PROCESSING FEES

Rs 500/- in favour of MD, RISL, Jaipur



## IMPORTANT DATES AND OTHER INFORMATION

## Secretary, Rajasthan State Sports Council. Jaipur

Important Dates of Bids for Annual maintenance work (Painting) in S.M.S.Stadium, Jaipur

1. Completion Period	01 Year
2. Date of Issue of Notice Inviting Tender	Monday March 15, 2021
Period and Places of Sale/ Download of Bidding Documents -	From Wednesday March 17, 2021, 17:00 Hours to Wednesday March 30, 2021, 13:00 Hours
V V	http://sppp.rajasthan.gov.in, http://eproc.rajasthan.gov.in & www.rssc.in
4. Deadline for uploading	From Wednesday March 17, 2021, 17:00 Hours to Wednesday March 30, 2021, 13:00 Hours
5. Time and Date for Opening of Bids	Wednesday March 30, 2021, AT 16:00 Hours
6. Place of Opening of Bids	Rajasthan State Sports Council, SMS Stadium, Jaipur-302005
7. Officer Inviting Bids	Designation: Secretary, Rajasthan State Sports Council. Jaipur.
# j	Address: SMS Stadium, Jaipur-302005
8. Rate are based on BSR	Based on PWD City Circle , Jaipur BSR 2019 and its all Corrigendums
9 Earnest money to be deposited	As per NIT



### Instructions and information to bidder regarding Fee, EMD etc.

District	Name of Work Package No.	Estimated Cost (Rs.)	Earnest Money	Time Allowed for completion	End date and time for downloading Tender	Time and date of opening of tender	Place of Sale of documents	Class of contractor
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
Jaipur	Annual maintenance work (Painting) in S.M.S.Stadium, Jaipur	20.00 Lacs	Rs. 40,000/-	01 Year	Wednesday March 30, 2021, 13:00 Hours	Wednesday March 30, 2021, AT 16:00 Hours	http://sppp.rajasthan.gov.in, http://eproc.rajasthan.gov.in & www.rssc.in	"A" & above for Painting work

- 1. The Tender Fee and earnest money as mentioned above should be deposited in the appropriate form as per the tender documents in favour of Secretary, Rajasthan State Sports Council. Jaipur payable at Jaipur and Processing Fees Rs 500/- in favour of MD, RISL, Jaipur payable at Jaipur and must be uploaded scan copy of Registration of Firm, Demand Draft of Tender Cost, Processing Fee & Earnest Money and GST Number on the site
- 2. The tender can be viewed and downloaded from web site http://sppp.rajasthan.gov.in, http://eproc.rajasthan.gov.in & www.rssc.in
- The authorized tender documents are available for inspection in the office of Rajasthan State Sports Council, SMS Stadium, Jaipur from all working days.



# Annexure A: Compliance with the Code of Integrity and No Conflict of Interest

Any person participating in a procurement process shall-

- (a) Not offer any bribe, reward or gift or any material benefit either directly or indirectly in exchange for an unfair advantage in procurement process or to otherwise influence the procurement process;
- (b) Not misrepresent or omit that misleads or attempts to mislead so as to obtain a financial or other benefit or avoid an obligation;
- (c) Not indulge in any collusion, Bid rigging or anticompetitive behavior to impair the transparency, fairness and progress of the procurement process;
- (d) Not misuse any information shared between the procuring entity and the bidders with an intent to gain unfair advantage in the procurement process;
- (e) Not indulge in any coercion including impairing or harming or threatening to do the same, directly or indirectly, to any party or to its property to influence the procurement process;
- (f) Not obstruct any investigation or audit of a procurement process;
- (g) Disclose conflict of interest, if any; and
- (h) Disclose any previous transgressions with any entity in India or any other country during the last three years or any debarment by any other procuring entity.

#### Conflict of interest.-

The Bidder participating in a bidding process must not have a Conflict of Interest.

A Conflict of interest is considered to be a situation in which a party has interests that could improperly influence that party's performance of official duties or responsibilities, contractual obligations, or compliance with applicable laws and regulations.

- (i) A bidder may be considered to be in conflict of interest with one or more parties in the bidding process if, including but not limited to:
- (a) Have controlling partners/shareholders in common; or
- (b) Receive or have received any direct or indirect subsidy from any of them; or
- (c) Have the same legal representative for purposes of the bid; or
- (d) have a relationship with each other, directly or through common third parties, that puts them in a position to have access to information about or influence on the bid of another bidder, or influence the decisions of the procuring Entity regarding the bidding process; or
- (e) The bidder participates in more than one bid in a bidding process. Participation by a bidder in more than one bid will result in the disqualification of all bids in which the bidder is involved. However, this does not limit the inclusion of the same subcontractor, not otherwise participating as a bidder, in more than one bid; or
- (f) the bidder or any of its affiliates participated as a consultant in the preparation of the design or technical specifications of the goods, Works or services that are the subject of the Bid; or
- (g) Bidder or any of its affiliates has been hired (or proposed to be hired) by the procuring entity as engineer-in-charge/consultant for the contract.



# Annexure B: Declaration by the Bidder regarding Qualifications Declaration by the Bidder

In relation to my/our	Bid submitted t	0		•••••	for p	rocurem	ent	of
in	response	to	their	Notice	invi	ting	В	ids
NoDated	I/we		hereb	y declare	under	Section	7	of
Rajasthan Transparer	ncy in Public Pro	cureme	nt Act, 2012	that:				

- 1. I/we possess the necessary professional, technical, financial and managerial resources and competence required by the Bidding Document issued by the Procuring Entry;
- I/we have fulfilled my/our obligation to pay such of the taxes payble to the union and the state government or any local authority as specified in the Bidding Document.
- I/we are not insolvent, in receivership, bankrupt or being wound up, not have my/our affairs administered by a court or a judicial officer, not have my/our business activities suspended and not the subject of legal proceedings for any of the foregoing reasons;
- 4. I/we do not have, and our directors and officers not have, been convicted of any criminal offence related to my/our professional conduct or the making of false statements or misrepresentations as to my/our qualifications to enter into a procurement contract within a period of three years preceding the commencement of this procurement process, or not have been otherwise disqualified pursuant to debarment proceedings;
- 5. I/we do not have a conflict of interest as specified in the Act, Rules and the Bidding Document, which materially affects fair competition;

Date:	Signature of bidder
Place:	Name:
	Designation:
	Address:



## Annexure C: Grievance Redressed during Procurement Process

The designation and address of the First Appellate Authority is Dy. Secretary Youth Affairs & Sports Department Govt. of Rajasthan. The designation and address of the Second Appellate Authority is **Principal Secretary** Youth Affairs & Sports Department Govt. of Rajasthan, Jaipur.

### (1) Filing an appeal:-

if any bidder or prospective bidder is aggrieved that any decision, action or omission of the procuring entity is in contravention to the provisions of the Act or the rules or the guidelines issued thereunder, he may file an appeal to First Appellate authority, as specified in the Bidding document within a period of ten days from the date of such decision or action, omission, as the case may be, clearly giving the specific ground or grounds on which he feels aggrieved:

Provided that after the declaration of a bidder as successful the appeal may be filed only by a bidder who has participated in procurement proceedings:

Provided further that in case a procuring entity evaluates the technical bids before the opening of the financial bids, an appeal related to the matter of financial bids may be filed only by a bidder whose technical bid is found to be acceptable.

- (2) The officer to whom an appeal is filed under Para (1) shall deal with the appeal as expeditiously as possible and shall endeavour to dispose it of within thirty days from the date of the appeal.
- (3) If the officer designated under Para (1) fails to dispose of the appeal filed within the period specified in Para (2), or if the bidder or prospective bidder or the procuring entity is aggrieved by the order passed by the first appellate authority, the bidder or prospective bidder or the procuring entity, as the case may be, may file a second appeal to second appellate authority specified in the bidding document in this behalf within fifteen days from the expiry of the period specified in Para (2) or of the date of receipt of the order passed by the first appellate authority, as the case may be.

### (4) Appeals not to lie in certain cases:-

No appeal shall lie against any decision of the procuring entity relating to the following matters, namely:-

- (a) Determination of need of procurement
- (b) Provisions limiting participation of bidders in the bid process
- (c) The decision of whether or not to enter into negotiations
- (d) Cancellation of a procurement process
- (e) Applicability of the provisions of confidentiality

#### (5) Form of Appeals:-

(a) An appeal under Para (1) or (3) above shall be in the annexed form along with as many copies as there are respondents in the appeal.



- (b) Every appeal shall be accompanied by an order appealed against, if any, affidavit verifying the facts stated in the appeal and proof of payment of fee,
- (c) Every appeal may be presented to first appellate authority or second appellate authority, as the case may be, in person or though registered post or authorized representative.

## (6) Fee for filing Appeal:-

- (a) Fee for first appeal shall be rupees two thousand five hundred and for second appeal shall be rupees ten thousand, which shall be non-refundable.
- (b) The fee shall be paid in the form of bank demand draft or banker's cheque of a scheduled bank in India payable in the name of appellate authority concerned.

## (7) Procedure for disposal of Appeal:-

- (a) The first appellate authority or second appellate authority as the case may be, upon filing of appeal, shall issue notice accompanied by copy of appeal, affidavit and documents, if any, to the respondents and fix date of hearing
- (b) On the date fixed for hearing, the first appellate authority of second appellate authority, as the case may be shall-
  - (i) Hear all the parties to appeal present before him; and
  - (ii) Peruse or inspect documents, relevant records or copies thereof relating to the matter.
- (c) After hearing the parties, perusal or inspection of documents and relevant records or copies thereof relating to the matter, the appellate authority concerned shall pass an order in writing and provide the copy of order to the parties to appeal free of cost.
- (d) The order passed under sub-clause (c) above shall also be placed on the state public procurement portal.



#### Annexure D: Additional Conditions of Contract

#### 1. Correction of arithmetical errors

Provided that a Financial Bid is substantially responsive, the Procuring Entity will correct arithmetical errors during evaluation of Financial Bids on the following basis:

- i. If there is a discrepancy between the unit price and the total price that is obtained by multiplying the unit price and quantity, the unit price shall prevail and the total price shall be corrected, unless in the opinion of the Procuring Entity there is an obvious misplacement of the decimal point in the unit price, in which case the total price as quoted shall govern and the unit price shall be corrected;
- ii. It there is an error in a total corresponding to the addition or subtraction of subtotals, the subtotals shall prevail and the total shall be corrected; and
- iii. If there is a discrepancy between words and figures, the amount in words shall prevail, unless the amount expressed in words is related to an arithmetic error, in which case the amount in figures shall prevail subject to (i) and (ii) above.

If the Bidder that submitted the lowest evaluated Bid does not accept the correction of errors, its Bid shall be disqualified and its Bid Security shall be forfeited or its Bid Securing Declaration shall be executed.

#### 2. Procuring Entity's Right to Vary Quantities

- (i) At the time of award of contract, the quantity of Goods, Works or services originally specified in the Bidding Document may be increased or decreased by a specified percentage, but such increase or decrease shall not exceed Five percent, of the quantity specified in the Bidding Document. It shall be without any change in the unit prices or other terms and conditions of the Bid and the conditions of contract.
- (ii) If the Procuring Entity does not procure any subject matter of procurement or procures less than the quantity specified in the Bidding Document due to change in circumstances, the Bidder shall not be entitled for any claim or compensation except otherwise provided in the Conditions of Contract.
- (i) In case of procurement of Goods or services, additional quantity may be procured by placing a repeat order on the rates and conditions of the original order. However, the additional quantity shall not be more than 50% of the value of Goods of the original contract and shall be within one month from the date of expiry of last supply. If the supplier fails to do so, the Procuring Entity shall be free to arrange for the balance supply by limited Bidding or otherwise and the extra cost incurred shall be recovered from the supplier.

# 3. Dividing quantities among more than one Bidder at the time of award (In case of procurement of Goods)

As a general rule all the quantities of the subject matter of procurement shall be procured from the Bidder, whose Bid is accepted. However, when it is considered that the quantity of the subject matter of procurement to be procured is very large and it may not be in the capacity of the Bidder, whose Bid is accepted, to deliver the entire quantity or when it is considered that the subject matter of procurement to be procured is of critical and vital nature, in such cases, the quantity may be divided between the Bidder, whose Bid is accepted and the second lowest Bidder or even more Bidders in that order, in a fair, transparent and equitable manner at the rates of the Bidder, whose Bid is accepted.



Jims

# राजस्थान राज्य क्रीडा परिषद



15 P


सवाई मानसिंह स्टेडियम, जनपथ, जयपुर

कार्यालय दूरभाष नं0 0141-2744283, फैक्स नं0 0141-2740568, ईमेल आईडी-rsscjaipur@gmail.com

बोली की शर्तें

विशेष टिप्पणी :- बोलीदाताओं को इन शर्तों को सावधानी पूर्वक पढ़ना चाहिए तथा अपनी ई-बोलियां भेजते समय इनकी पूर्ण रूपेण पालना करनी चाहिए।

- 1. तकनीकी प्रस्तावों में सफल बोलीदाताओं के ही वित्तीय प्रस्ताव खोले जावेगें जो निविदादाता तकनीकी बिड में सफल नहीं पाये गये उनकी वित्तीय बोली नहीं खोली जायेगी।
- 2. कोई भी फर्म/संवेदक यदि जी.एस.टी. अधिनियम के अन्तर्गत पंजीकृत नहीं है तो वह बोली नहीं देगा। इनके अभाव में बोलियों पर विचार नहीं किया जायेगा। जी. एस. टी. देयता प्रमाण पत्र दिसम्बर, 2020 तक का संलग्न करना आवश्यक है।
- 3. दरें जी. एस. टी. तथा केन्द्र व राज्य सरकार द्वारा देय समस्त करों सहित देनी होगी।
- 4. बोली ऑन-लाईन प्रस्तुत की जावेगी एवं निर्दिष्ट कॉलमों में प्रविष्टी की जावेगी।
- 5. दरें गन्तव्य स्थान तक एफ.ओ.आर. सवाई मानिसंह स्टेडियम जयपुर के आधार पर होगीं अर्थात परिवहन संबंधी कोई राशि परिषद द्वारा पृथक से देय नहीं होगी।
- 6. बोलियां उपापन अधिनियम / पारदर्शिता अधिनियम के तत्संबंधी प्रावधानों (धारा—28 आदि) के अध्यधीन रहते हुये उनके खोले जाने की दिनांक से एक वर्ष की अवधि के लिए विधि मान्य होंगी।
- 7. बोलीदाता अपनी संविदा या उसके किसी भाग को किसी अन्य एजेन्सी के लिए नहीं सौंपेगा या उपभाडे पर नहीं देगा।
- 8. बोलीदाता का उसके प्रतिनिधि की ओर से प्रत्यक्ष अथवा अप्रत्यक्ष रूप से अपना पक्ष समर्थन करना एक प्रकार की अनर्हता होगी। हित विरोधी धारा 80 होगी।
- 9. विहित समय एवं तारीख के पश्चात् जो भी बोलियां प्राप्त होंगी उन्हें किसी स्थिति में स्वीकार नहीं किया जावेगा।
- 10. यदि बोलीदाता ऐसी कोई शर्त आरोपित करता है जो उसमें वर्णित शर्तों के अतिरिक्त है या उनके विरोध में है तो उसकी बोली को संक्षिप्त रूप में कार्यवाही कर रदद कर दिया जावेगा।
- 11. तकनीकी बोली के साथ बोलीदाता को निम्न दस्तावेज संलग्न करने अनिवार्य होगे (जिसके आधार पर तकनीकी बिड का मूल्याकंन किया जायेगा) :-
  - i. बोली में अंकित पते के प्रमाण हेतु पानी/बिजली/टेलीफोन/मोबाईल के बिल, पेन कार्ड, पासपोर्ट, आधार कार्ड अथवा ड्राईविंग लाईसेन्स में से कोई एक की प्रमाणित छाया प्रतियां।



बोलीदाता / फर्म का विगत 1 वित्तीय वर्ष में टर्न ओवर 20.00 लाख से कम नहीं होना चाहिये। इस हेतु बोलीदाता को उक्त वर्ष के लेखा विवरण एवं आयकर विवरणी की प्रति संलग्न करनी होगी।

गत 2 वर्षों में किये गये राजकीय विभागों में किये गये पैन्टिंग कार्य का एकल कार्य राशि रूपये 10.00 लाख न्यूनतम का अनुभव होना आवश्यक होगा। इसके प्रमाणीकरण हेतु कार्यादेश एवं कार्य के सन्तोषजनक होने का प्रमाण पत्र आदि आवश्यक दस्तावेज संलग्न करने होगे।

बोलीदाता को माल एवं सेवाकर (GST) के रजिस्ट्रेशन की प्रति संलग्न करनी

अमानत राशि एवं बोली प्रपत्र शुल्क का डी.डी. संलग्न करना होगा।

## 12. बयाना राशि:-

(क) बोली से पूर्व (2% बोली सूचना के अनुसार) नियमानुसार बयाना राशि ऑन-लाईन प्रस्तुत की जायेगी। इसके बिना बोलीओं पर विचार नहीं किया जायेगा। यह राशि सचिव, राजस्थान राज्य क्रीड़ा परिषद, जयपुर के पक्ष में बैंक ड्राफ्ट / बैंकर्स चैक में से किसी रूप में जमा करायी जा सकती है।

(ख) असफल बोलीदाता की बयाना राशि बोली को अंतिम रूप से स्वीकार करने के

बाद यथा संभव शीघ्र लौटा दी जावेगी।

- (ग) अनुमोदन की प्रतीक्षा करने वाली या रद्द की गई या संविदाओं के पूर्ण हो जाने के कारण परिषद कार्यालय के पास जमा बयानाराशि / प्रतिभूति निक्षेप को नवीन निविदा के लिए बायाना राशि / प्रतिभूति राशि के प्रति समायोजित नहीं किया जायेगा।
- 13. बयाना राशि का समपहरण:- बयाना राशि को निम्नलिखित मामलों में समपहरत कर लिया जायेगा:-
  - जब बोलीदाता बोली खोलने के बाद किन्तु बोली को स्वीकार करने के पूर्व प्रस्ताव को वापस लेता है या उसमें उपान्तरण करता है।
  - जब बोलीदाता विर्निष्ट समय के भीतर विहित करार को निष्पादित नहीं (ख)
  - जब बोलीदाता प्रदायगी के लिए आदेश देने के बाद प्रतिभूति राशि जमा (ग) नहीं कराता हो।
  - जब वह निर्धारित समय के अन्तर्गत आदेशों के अनुसार कार्य करने में (घ) असफल रहता है अथवा संतोषजनक सेवाएं देने में असमर्थ रहता है।

## 14. करार एवं प्रतिभृति निक्षेप :--

- सफल बोलीदाता को आदेश दिनांक से 7 दिन की अवधि के भीतर (क) नियमानुसार मूल्य के नॉन ज्यूडिशियन स्टॉम्प पेपर पर (जिसका व्यय स्वयं बोलीदाता द्वारा वहन किया जावेगा) एक करार-पत्र निष्पादित करना होगा तथा प्रावधित मूल्य जिसके लिए बोली स्वीकार की गई है।
- बोली के समय जमा कराई गई बयाना राशि को प्रतिभूति की राशि के लिए समायोजित किया जायेगा।
- बयाना / प्रतिभूति राशि पर परिषद द्वारा कोई ब्याज का भुगतान नहीं किया (ग) जायेगा।

प्रतिभृति राशि के रूप में नकद रसीद पत्र/शिड्यूल बैंक का ड्राफ्ट/ बैंकर्स चैक मान्य होंगे।

15. प्रतिभूति राशि का समपहरण :- प्रतिभूति की राशि को पूर्ण अथवा आंशिक रूप से निम्नलिखित मामलों में समपहरत किया जायेगा:-

- जब संविदा की किसी शर्त / अथवा शर्तों का उल्लंघन किया गया हो।
- जब बोलीदाता सम्पूर्ण कार्य संतोषजनक ढंग से करने में असफल रहा हो। (ख)
- प्रतिभूति निक्षेप को समपहरत करने के मामले में युक्तियुक्त नोटिस दिया जावेगा इस सम्बन्ध में परिषद के अधिकारी का निर्णय अन्तिम होगा।
- कार्य में असफल रहने पर परिषद द्वारा वैकल्पिक व्यवस्था किये जाने पर उसमें जो भी व्यय होगा बोलीदाता से उसकी प्रतिभृति राशि में से अथवा उसको देय बिल की राशि के भुगतान में से की जायेगी। यदि वसूली करना सम्भव न हो तो राजस्थान पी.डी.आर.एक्ट या प्रवृत्त अन्य किसी कानून के अन्तर्गत कार्यवाही की जावेगी।

16. करार पत्र को पूर्ण करने एवं उस पर स्टाम्प लगाने का व्यय बोलीदाता द्वारा वहन किया जायेगा तथा परिषद को उस करार पत्र की निष्पादित स्टाम्प श्रदा प्रति पडत निःशुल्क प्रस्तुत की जायेगी।

17. परिषद के प्राधिकृत अधिकारी या उसका विधिवत् प्राधिकृत प्रतिनिधि सभी युक्तियुक्त उचित समयों पर ठेकेदार के परिसर में जायेगा तथा वह विनिर्माण की प्रक्रिया के दौरान या उसके बाद जैसे भी हो किसी भी समय सामग्री का निरीक्षण एवं जांच करने की शक्ति रखेगा।

18. परीक्षण प्रभार परिषद द्वारा वहन किये जायेंगे। यदि बोलीदाता अत्यावश्यक तत्काल परीक्षण कराना चाहता है या यदि परिणामों से यह ज्ञात होता है कि प्रदाय किया गया सामान विहित स्तरों या विनिर्देशों के अनुसार नहीं है तो

परीक्षण प्रभार बोलीदाता द्वारा वहन किये जायेंगे।

19. अनुमोदित कार्य के लिए यह समझा जाएगा कि उसने कार्य किये जाने वाले विनिर्देशों की सावधानीपूर्वक जांच कर ली है यदि उसे इन शर्तों, विनिर्देशों, रेखाचित्रों आदि के किसी भाग के आशय के बारे में कोई सन्देह हो तो वह संविदा पर हस्ताक्षर करने से पूर्व परिषद से स्पष्टीकरण प्राप्त करेगा।

20. सफल बोलीदाता को कार्य आदेश जारी तिथि के 10 दिवस के अन्दर कार्य

प्रारम्भ करना होगा।

21. यदि निविदा सूचना में दर्शित मात्रा से अधिक के लिए आदेश दिया जाता है, तो निविदादाता अपेक्षित कार्य करने के लिए बाध्य होगा। पुनः आदेश भी निविदा में दी गयी शर्तों पर दिए जा सकेंगें परन्तु शर्त यह है, कि ऐसे पुनआदेश मूल रूप से खरीदी गयी मात्रा की 50 प्रतिशत तक के अतिरिक्त प्रदाय के लिए ही होगें।

22. गारन्टी :-गारन्टी नियमानुसार होगी।

23. परिसमापित नुकसानी :-

(1) परिसमापित नुकसानी के साथ कार्य अवधि में वृद्धि करने के मामले में, वसूली राजस्थान लोक उपापन पारदर्शिता अधिनियम, 2012 एवं राजस्थान लोक उपापन पारदर्शिता नियम 2013 के प्रावधान अनुसार होगी।

(2) यदि प्रदायकर्ता किन्ही बाधाओं के कारण संविदान्तर्गत कार्य का प्रदाय पूरा करने के लिए समय में वृद्धि कराना चाहता है, तो वह लिखित में परिषद को आवेदन करेगा। किन्तु वह उसके लिए निवेदन बाधा के घटित होने



पर तुरन्त उसी समय करेगा न कि प्रदाय पूर्ण होने की निर्धारित तारीख के बाद करेगा।

(3) यदि कार्य प्रदाय करने में उत्पन्न हुई बाधा बोलीदाता के नियन्त्रण से परे कारणों से हुई हो तो कार्य की अवधि में वृद्धि परिसमापित नुकसानी सहित या रहित की जा सकेगी।

24. वसूली :-परिसमापित नुकसानी, कम प्रदाय, टूट-फूट, रद्द की गई वस्तुओं के लिए वसूली साधारण रूप से बिल में से की जाएगी। संवेदक कम प्रदाय, टूट-फूट, रद्द किए गए कार्यों की सीमा तक राशि को भी रोका जा सकेगा तथा यदि सेवा सन्तोषजनक ढंग से उनको कार्य करता है तो परिसमापित नुकसानी के साथ वसूली उसे देय राशि एवं विभाग के पास उपलब्ध प्रतिभूति निक्षेप से की जाएगी। यदि वसूली करना सम्भव न हो तो राजस्थान पी डी आर एक्ट या प्रवृत्त अन्य कानून के अन्तर्गत कार्रवाई की जाएगी।

25. भुगतान :-

(क) बोलीदाता द्वारा क्रेता अधिकारी को उचित प्रारूप में लोक उपापन नियमों के अनुसार बिल प्रस्तुत करने पर भुगतान किया जायेगा। सभी प्रेषण प्रभार बोलीदाता द्वारा वहन किये जायेंगे। किसी भी सूरत में अग्रिम भुगतान नहीं किया जायेगा।

(ख) विवादास्पद मदों में राशि का 10 प्रतिशत से 25 प्रतिशत तक को रोका जायेगा तथा उस विवाद का निपटारा हो जाने पर उसका भुगतान कर

देया जायेगा।

(ग) उन मामलों में, जिनमें परीक्षण करने की जरूरत है, भुगतान तभी किया जायेगा जब उनका परीक्षण कर लिया जाये तथा प्राप्त हुए परीक्षण परिणाम विहित निर्देशों के अनुरूप हों।

26. यदि कार्य की तात्कालिक आवश्यकता के कारण पूर्ण या आंशिक रूप में उन कार्यों को बदलना साध्य नहीं समझा जाए तो राजस्थान राज्य क्रीडा परिषद द्वारा बोलीदाता को सुनवाई किये जाने का एक उचित अवसर देकर, ऐसे कारणों से जो अभिलिखित किये जायेंगे, अनुमोदित दरों में से उपयुक्त राशि की कटौती करेगा। इस प्रकार की गई कटौती अन्तिम होगी।

27. निविदादाता करार को निष्पादित करते समय निम्नलिखित दस्तावेज प्रस्तुत

करेगा :-

(i) यदि भागीदारी फर्म हो तो "पार्टनरशिप डीड" की अनुप्रमाणित प्रति।

(ii) यदि भागीदारी फर्म रजिस्ट्रार ऑन फर्म्स के पास पंजीकृत हो तो पंजीयन संख्या एवं उसका वर्ष।

(iii) एक मात्र स्वामित्तव के मामले में आवास एवं कार्यालय का पता, टेलीफोन

(iv) कम्पनी के मामले में कम्पनी के रजिस्ट्रार के द्वारा जारी किया गया प्रमाण–पत्र।

28. संविदा के निर्वचन, आशय या संविदा की शर्तों के उल्लंघन के सम्बन्ध में या अन्य किसी भी प्रकार का विवाद होने पर परिषद का निर्णय अन्तिम होगा।

29. समस्त विधिक कार्यवाहियां यदि संस्थित किया जाना आवश्यक हो तो जयपुर स्थित न्यायालय में ही की जाएगी। अन्यत्र नहीं की जाएगी।



30. बोलीदाता द्वारा अपलोड किये जाने वालो दस्तावेजों पर नम्बरिंग होनी चाही एवं चैक लिस्ट भर कर प्रस्तुत करनी होगी। 31. सचिव, राजस्थान राज्य क्रीडा परिषद, जयपुर को बिना कारण बताये किसी भी

बोली को स्वीकार / अस्वीकार करने का अधिकार होगा।

32. जी.एफ. एण्ड ए.आर.,राजस्थान लोक उपापन पारदर्शिता अधिनियम, 2012 एवं राजस्थान लोक उपापन पारदर्शिता नियम 2013 के प्रावधान लागू होगें।

> बोलीदाता के हस्ताक्षर (मय नाम पता एवं मोहर)



## घोषणा

मैने/हमने सवाई मानसिंह स्टेडियम, जयपुर में पैन्टिंग हेतु (मय सामग्री) की बोली के नियम एवं शर्तों को भली—भॉित पढ व समझ लिया है। मुझे/हमारी फर्म को किसी भी विभाग द्वारा ब्लेक—लिस्ट नहीं किया गया है। इन शर्तो एवं नियमों के अधीन मैं/हम सवाई मानसिंह स्टेडियम, जयपुर में पैन्टिंग कार्य करने हेतु सहमत एवं वचनबद्व हूँ/है। यदि मेरे/हमारे द्वारा की किसी बोली की शर्तों, नियमों अथवा आदेशों का उल्लंघन किया जावेगा तो सक्षम अधिकारी द्वारा मेरे/हमारे विरुद्व बोली के नियम/शर्तों के उल्लंधन की कार्यवाही करने के लिए अधिकृत होगा। इस सम्बन्ध में मुझे/हमें सक्षम/अधिकृत अधिकारी द्वारा लिया गया निर्णय मान्य होगा तथा इसमें मुझे/हमको कोई आपित्त/हस्तक्षेप नहीं है।

हस्ताक्षर ब	ोलीदाता
नाम / पता	
टेलीफोन	<del>-</del> i
दिनांक	



### General Instructions for Filling of Bid

The complete bidding document has been published on the website www.rssc.in, http://sppp.raj.nic.in, http://eproc.raj.gov.in, for the purpose of downloading.

- 1. Bidders who wish to participate in this bidding process must register on www.rssc.in & http://sppp.raj.nic.in,
- 2. To participate in online bidding process, Bidders must procure a Digital Signature Certificate (Type III) as per Information Technology Act-2000 using which they can digitally sign their electronic bids. Bidders can procure the same from any CCA approved certifying agency, i.e. TCS, safe crypt, Node etc. Bidders who already have a valid Digital Signature Certificate (DSC) need not procure a new DSC.
- 3. Bidder (authorized signatory) shall submit their offer on-line in Electronic formats both for Technical and financial proposal. However, DD for Tender Fees, EMD payable in favor of SECRETARY RAJASTHAN STATE SPORTS COUNCIL, JAIPUR, payable at Jaipur and Processing Fees payable in favor of Managing Director, RAJCOMP Info Services Limited, payable at JAIPUR. Tender fee, EMD and processing fee DD Should be submitted physically at the office of RAJASTHAN STATE SPORTS COUNCIL, JAIPUR, and Scanned copy of same should also be uploaded along with the technical bid.
- 4. RAJASTHAN STATE SPORTS COUNCIL, JAIPUR will not be responsible for delay in online submission due to any reason. For this, bidders are requested to upload the complete bid well advance in time so as to avoid Last hours issues like slow speed; choking of web site due to heavy load or any other unforeseen problems.
- 5. Bidders are also advised to refer "Bidders Manual Kit" available at e-Proc website for further details about the e-tendering process.
- 6. No contractual obligation, whatsoever shall arise from the bidding process unless and until a formal contract is signed and executed between the tendering authority and the successful Bidder.

**SECRETARY** 



# UNDERTAKING BY THE BIDDER

This is to certify that I/we before signing this tender have read and fully understood all the terms and conditions contained herein and undertake myself/ourselves to abide by them. I/We have signed all the pages in acceptance of the terms and conditions.

I/We also undertake that I/We will not adopt any malpractices at any stage of bidding/execution.

Signature of the Bidder with Seal Name: Designation: Address:



# BIDDER'S AUTHORIZATION CERTIFICATE (to be filled by the bidder)

To,
{Tendering Authority},
I/ We{Name/Designation} hereby
declare/ certify that
documents on behalf of the company/ firm in dealing with Tender with RAJASTHAN
STATE SPORTS COUNCIL, JAIPUR.
He/ She is also authorized to attend meetings & submit technical & commercial
information/ clarifications as may be required by you in the course of processing the Bid.
For the purpose of validation, his/ her verified signatures are as under.
Thanking you,
Name of the Bidder: - Verified Signature:
Authorized Signatory: -
Seal of the Organization: -
Date:
Place:



## CHECKLIST OF DOCUMENTS SUBMITTED

S. No.	Documents to be submitted	Submitted	Not Submitted	Page No.
1.	Scanned Copies of tender document fee, EMD and processing fees			
2.	Copy of Registration of firms (A & Above Class Certificate by Work Department of Govt.)			<
3.	Copy of GST Registration		V	
4.	Copy of PAN Card		ü	
5.	Proof of Work Order and Work Satisfactory of Painting work (Minimum work order Rs. 50% of Tender cost) in financial Year 2018-19, 2019-20.		-	
6.	Financial Year 2019-20 audited statement and Turn Over must be at least equal to this tender cost from Chartered Accountant in proof of Painting work.			
7.	Annexure A to D duly signed in context to RTPP Rules – 2013.			
8.	Authorization certificate If the tender is signed other than owners			
9.	Copy of GST paid certificate for the month of November, 2020 in gstr-3b Performa			
10.	Tender document and Technical Bid and undertaking all three duly signed			
11.	Any other Document			

Signature of Bidder Seal of Establishment Full Name of Bidder with address and date

Shap

## **G** Schedule

Name of work :-- Annual maintenance work (Painting) in S.M.S.Stadium, Jaipur.

As per PWD BSR, 2019 City Circle, Jaipur S. Quantity **Particulars** Rate Amount No. Providing and applying plaster of paris putty of 2 1 1.00 63.00 63.00 mm thickness over plastered surface to prepare the P.Sam surface even and smooth complete Providing & Laying POP moulding & beading in 2 1.00 65.00 Rm Rm 65.00 ceiling including nailing & scafollding etc. complete of size: 25mm x 25 mm Providing & Laying POP Cornice of required design & pattern in ceiling including nailing & 3 1.00 Rm 133.00 133.00 Rm scafollding etc. complete with fine finishing of size: 75mm x 75mm Finishing wall with water proofing cement paint of approved brand and manufacture and or required 4 shade to give an even shade including all scaffolding: New work (Two or more coats applied @ 3.84 1.00 Sqm 48.00 P.Sqm 48.00 a ka/10 sam). 1.00 Old work (One or more coats). 18.00 b Sqm P.Sqm 18.00 Painting with synthetic enamel paint of approved 5 brand and manufacture to give an even shade: 1.00 63.00 63.00 Sqm Two or more coats on new work P.Sqm a 1.00 31.00 b One or more coats on old work. 31.00 P.Sam Painting (two or more coats) on rain water soil, waste and vent pipes and fitting with black anticorrosive bitumastic paint of approved brand 6 1.00 Mtr. 24.00 P.Mtr 24.00 and manufacture over and including a priming coat of ready mixed zinc chromate yellow primer on new work · 100mm dia Pines Colour washing of all shades to give an even shade including all scaffolding: Old work (one or more 7 1.00 Sam 6.50 6.50 P.Sqm coats) with whiting with a base coat of white washing including scrapping old surface. White washing with lime to give an even shade 8 including all scaffolding: 1.00 Sqm New work (three or more coats). 10.00 P.Sqm 10.00 a Old work (one or more coats) including scrapping old surface and repairing with putty where ever b 1.00 Sqm 2.75 P.Sqm 2.75 necessary. Removing dry or oil bound distemper by scrapping sand papering and preparing surface smooth 9 1.00 Sqm 3.90 P.Sam 3.90 including necessary repairs to scratches by sandla/loi and all scaffolding (for colour changing Distempering with oil bound washable distemper of 10 approved brand and manufacture to give an even shade including all scaffolding: New work (two or more coats) over and 1.00 68.00 P.Sam 68.00 Sqm with including scrapping and priming coat a cement primer.



S. No.	Quantity		Particulars	Rate		Amount	
b	1.00	Sqm	Old work (one or more coats) including scrapping surface and necessary repairs. Colour change.	14.00	P.Sqm	14.00	
11	Wall painting with plastic emulsion paint of approved brand and manufacture to give an even shade including all scaffolding:						
а	1.00	Sqm	Two or more coats on new work including prepartion of base with primer, putty, lippy etc complete in all respect.	73.00	P.Sqm	73.00	
b	1.00	Sqm	Old work (One or more coats )	36.00	P.Sqm	36.00	
12			Applying priming coat :				
a	1.00	Sqm	With ready mix pink or gray primer of approved brand and manufacture on wood work hard and soft wood.	26.00	P.Sqm	26.00	
b	1.00	Sqm	With ready mixed red oxide zinc chromate primer of approved brand and manufacture on steel work (second coat)	11.00	P.Sqm	11.00	
13			French sprit polishing :				
а	1.00	Sqm	Two or more coats on new work including a coat of wood filler.	152.00	P.Sqm	152.00	
b	1.00	Sqm	One or more coats on old work.	52.00	P.Sqm	52.00	
14			Providing and applying white cement based putty over plastered surface to prepare the surface even and smooth complete				
а	1.00	Sqm	New Plastered Surface (three or more coats)	76.00	P.Sqm	76.00	
а	1.00	Sqm	Old Plastered Surface (two or more coats)	42.00	P.Sqm	42.00	
15	1.00	P. Letter Per cm. height	Lettering with black Japan paint of approved brand and manufacture.	2.00	P. Letter Per cm. height	2.00	
16	1.00	Sqm	Finishing walls with Acrylic Smooth exterior paint of required shade including all scaffolding. New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including base coat of water proofing cement paint applied @ 2.20 kg/ 10 sqm).	78.00	P.Sqm	78.00	
17			Finishing walls with textured exterior paint of required shade as per approved colour complete as per manufacturers specifications including primer coat and protecting coat				
а	1.00	Sqm	Roller Finish av. thickness 400 to 500 microns.	155.00	P.Sqm	155.00	
b	1.00	Sqm	Trowel Finish av. thickness 1500 to 2000 microns.	367.00	P.Sqm	367.00	



S. No.	Quantity		Particulars		Rate	
18			Painting exterior surface of Wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade with two or more coats including prepartion of base with sand papering, primer, putty, etc complete in all respect including scaffolding and safety provision		,	
а	1.00	Sqm	New Work	112.00	P.Sqm	112.00
b	1.00	Sqm	Old Work	45.00	P.Sqm	45.00

Secretary Rajasthan State Sports Council Jaipur

I/We agree to execute the above work as per rate filled in related item. (Rate in words % above/below)

Signature of Contractor
With full Address

