



राजस्थान राज्य क्रीडा परिषद

सवाई मानसिंह स्टेडियम, जनपथ, जयपुर

कार्यालय दूरभाष नं० 0141-2744283, फ़ैक्स नं० 0141-2740568, ईमेल आईडी-rsscjaipur@gmail.com

No. : एफ-8 / स.अ. / ब.घो. 24 / 2024-25 / एथ0अ0भ0मरम्मत, अजमेर / 1921 Dated : 16/12/2022

निविदा सूचना संख्या 82 / 2024-25

राजस्थान राज्य क्रीडा परिषद, जयपुर की ओर से पटेल स्टेडियम, अजमेर पर एथलेटिक्स खेल अकादमी भवन की मरम्मत कार्य हेतु केन्द्र/राज्य सरकार के अधिकृत संगठनों/विभागों में पंजीकृत संवेदकों से ऑनलाइन निविदाएं आमंत्रित की जाती है।

निविदा से संबंधित अन्य आवश्यक विवरण वेबसाइट <http://sppp.rajasthan.gov.in>, <http://eproc.rajasthan.gov.in> & www.rssc.in पर देखा जा सकता है।

(राजेन्द्र सिंह)

आर.ए.एस

सचिव

RajKaj Ref
12437816



Signature valid

Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.14 00:02:34 IST
Reason: Approved



RAJASTHAN STATE SPORTS COUNCIL

TENDER DOCUMENT FOR

Maintenance work of Academy building, Patel Stadium, Ajmer.

NIT NO. : NIT No. 82/2024-25

ESTIMATED COST : Rs. 30.00 Lacs

EARNEST MONEY : Rs. 60,000/-

DATE OF SALE / DOWNLOADING : From Monday December 16, 2024 to Thursday
December 26, 2024, 13:00 Hours

**DATE OF RECEIPT (D.D. &
DOCUMENTS)** : From Monday December 16, 2024 to Thursday
December 26, 2024, 15:00 Hours

DATE OF OPENING OF TENDER : Friday December 27, 2024 AT 12:00 Hours

PERIOD OF WORK : 03 Months

COST OF TENDER : Rs. 500/- in favour of Secretary, RSSC, Jaipur

PROCESSING FEES : Rs 500/- in favour of MD, RISL, Jaipur

RajKaj Ref
12437816

Signature valid

Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.14 09:02:34 IST
Reason: Approved

Rajasthan State Sports Council. Jaipur

Important Dates of Bids

1. Period of Work	03 Months
2. Date of Issue of Notice Inviting Tender	Monday December 16, 2024
3. Period and Places of Sale/ Download of Bidding Documents -	From Monday December 16, 2024, to Thursday December 26, 2024 , 13:00 Hours http://sppp.rajasthan.gov.in , www.rssc.in & http://eproc.rajasthan.gov.in
4. Deadline for uploading	From Monday December 16, 2024 to Thursday December 26, 2024 , 13:00 Hours
5. Time and Date for Opening of Bids	Friday December 27, 2024 AT 12:00 Hours
6. Place of Opening of Bids	Rajasthan State Sports Council, SMS Stadium, Jaipur-302005
7. Officer Inviting Bids	Secretary, Rajasthan State Sports Council. Jaipur. Address: SMS Stadium, Jaipur-302005
8. Earnest money to be deposited	As per NIT

RajKaj Ref
12437816

Signature valid

Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.14 09:02:34 IST
Reason: Approved

Instructions and information to bidder regarding Fee, EMD etc.

District	Name of Work Package No.	Estimated Cost (Rs.)	Earnest Money	Time Allowed for Work	End date and time for downloading Tender	Time and date of opening of tender	Place of Sale of documents	Registration of Firm/Contractor
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
Jaipur	Maintenance work of Academy building, Patel Stadium, Ajmer.	30.00 Lacs	Rs. 60,000/-	03 Months	Thursday December 26, 2024, 13:00 Hours	Friday December 27, 2024 AT 12:00 Hours	http://sppp.rajasthan.gov.in , http://eproc.rajasthan.gov.in & www.rssc.in	C and Above category for Civil works

- The Tender Fee and earnest money as mentioned above should be deposited in the appropriate form as per the tender documents in favour of **Secretary, Rajasthan State Sports Council, Jaipur** payable at **Jaipur** and **Processing Fees Rs 500/-** in favour of **MD, RISL, Jaipur** payable at Jaipur and must be uploaded scan copy of Registration of Firm, Demand Draft of Tender Cost, Processing Fee & Earnest Money and GST Number on the site
- The tender can be viewed and downloaded from web site <http://sppp.rajasthan.gov.in>, <http://eproc.rajasthan.gov.in> & www.rssc.in
- The authorized tender documents are available for inspection in the office of **Rajasthan State Sports Council, SMS Stadium, Jaipur** from all working days.

RajKaj Ref
12437816

Signature valid

Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.14 09:02:34 IST
Reason: Approved

Annexure A: Compliance with the Code of Integrity and No Conflict of Interest

Any person participating in a procurement process shall-

- (a) Not offer any bribe, reward or gift or any material benefit either directly or indirectly in exchange for an unfair advantage in procurement process or to otherwise influence the procurement process;
- (b) Not misrepresent or omit that misleads or attempts to mislead so as to obtain a financial or other benefit or avoid an obligation;
- (c) Not indulge in any collusion, Bid rigging or anticompetitive behavior to impair the transparency, fairness and progress of the procurement process;
- (d) Not misuse any information shared between the procuring entity and the bidders with an intent to gain unfair advantage in the procurement process;
- (e) Not indulge in any coercion including impairing or harming or threatening to do the same, directly or indirectly, to any party or to its property to influence the procurement process;
- (f) Not obstruct any investigation or audit of a procurement process;
- (g) Disclose conflict of interest, if any; and
- (h) Disclose any previous transgressions with any entity in India or any other country during the last three years or any debarment by any other procuring entity.

Conflict of interest.-

The Bidder participating in a bidding process must not have a Conflict of Interest.

A Conflict of interest is considered to be a situation in which a party has interests that could improperly influence that party's performance of official duties or responsibilities, contractual obligations, or compliance with applicable laws and regulations.

(i) A bidder may be considered to be in conflict of interest with one or more parties in the bidding process if, including but not limited to:

- (a) Have controlling partners/shareholders in common; or
- (b) Receive or have received any direct or indirect subsidy from any of them; or
- (c) Have the same legal representative for purposes of the bid; or
- (d) have a relationship with each other, directly or through common third parties, that puts them in a position to have access to information about or influence on the bid of another bidder, or influence the decisions of the procuring Entity regarding the bidding process; or
- (e) The bidder participates in more than one bid in a bidding process. Participation by a bidder in more than one bid will result in the disqualification of all bids in which the bidder is involved. However, this does not limit the inclusion of the same subcontractor, not otherwise participating as a bidder, in more than one bid; or
- (f) the bidder or any of its affiliates participated as a consultant in the preparation of the design or technical specifications of the goods, Works or services that are the subject of the Bid; or
- (g) Bidder or any of its affiliates has been hired (or proposed to be hired) by the procuring entity as engineer-in-charge/consultant for the contract.

RajKaj Ref
12437816

Signature valid

Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.14 07:02:34 IST
Reason: Approved

Annexure B: Declaration by the Bidder regarding Qualifications
Declaration by the Bidder

In relation to my/our Bid submitted tofor procurement
ofin response to their Notice inviting Bids
No.....Dated.....I/wehereby declare under Section 7 of
Rajasthan Transparency in Public Procurement Act, 2012 that :

1. I/we possess the necessary professional, technical, financial and managerial resources and competence required by the Bidding Document issued by the Procuring Entry;
2. I/we have fulfilled my/our obligation to pay such of the taxes payable to the union and the state government or any local authority as specified in the Bidding Document.
3. I/we are not insolvent, in receivership, bankrupt or being wound up, not have my/our affairs administered by a court or a judicial officer, not have my/our business activities suspended and not the subject of legal proceedings for any of the foregoing reasons;
4. I/we do not have, and our directors and officers not have, been convicted of any criminal offence related to my/our professional conduct or the making of false statements or misrepresentations as to my/our qualifications to enter into a procurement contract within a period of three years preceding the commencement of this procurement process, or not have been otherwise disqualified pursuant to debarment proceedings;
5. I/we do not have a conflict of interest as specified in the Act, Rules and the Bidding Document, which materially affects fair competition;

Date:
Place:

Signature of bidder
Name:
Designation:
Address:

RajKaj Ref
12437816

Signature valid

Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.14 09:02:34 IST
Reason: Approved

Annexure C: Grievance Redressed during Procurement Process

The designation and address of the First Appellate Authority is Deputy Secretary, Youth Affairs & Sports Department Govt. of Rajasthan. The designation and address of the Second Appellate Authority is Secretary, Youth Affairs & Sports Department Govt. of Rajasthan, Jaipur.

(1) Filing an appeal:-

if any bidder or prospective bidder is aggrieved that any decision, action or omission of the procuring entity is in contravention to the provisions of the Act or the rules or the guidelines issued there under, he may file an appeal to First Appellate authority, as specified in the Bidding document within a period of ten days from the date of such decision or action, omission, as the case may be, clearly giving the specific ground or grounds on which he feels aggrieved:

Provided that after the declaration of a bidder as successful the appeal may be filed only by a bidder who has participated in procurement proceedings:

Provided further that in case a procuring entity evaluates the technical bids before the opening of the financial bids, an appeal related to the matter of financial bids may be filed only by a bidder whose technical bid is found to be acceptable.

(2) The officer to whom an appeal is filed under Para (1) shall deal with the appeal as expeditiously as possible and shall endeavor to dispose it of within thirty days from the date of the appeal.

(3) If the officer designated under Para (1) fails to dispose of the appeal filed within the period specified in Para (2), or if the bidder or prospective bidder or the procuring entity is aggrieved by the order passed by the first appellate authority, the bidder or prospective bidder or the procuring entity, as the case may be, may file a second appeal to second appellate authority specified in the bidding document in this behalf within fifteen days from the expiry of the period specified in Para (2) or of the date of receipt of the order passed by the first appellate authority, as the case may be.

(4) Appeals not to lie in certain cases:-

No appeal shall lie against any decision of the procuring entity relating to the following matters, namely:-

- Determination of need of procurement
- Provisions limiting participation of bidders in the bid process
- The decision of whether or not to enter into negotiations
- Cancellation of a procurement process
- Applicability of the provisions of confidentiality

(5) Form of Appeals:-

- An appeal under Para (1) or (3) above shall be in the annexed form along with as many copies as there are respondents in the appeal.
- Every appeal shall be accompanied by an order appealed against, if any, Affidavit verifying the facts stated in the appeal and proof of payment of fee,
- Every appeal may be presented to first appellate authority or second Appellate authority, as the case may be, in person or through registered post Or authorized representative.

(6) Fee for filing Appeal:-

- Fee for first appeal shall be rupees two thousand five hundred and for second appeal shall be rupees ten thousand, which shall be non-refundable
- The fee shall be paid in the form of bank demand draft or banker's cheque of a scheduled bank in India payable in the name of appellate authority concerned.

(7) Procedure for disposal of Appeal:-

- The first appellate authority or second appellate authority as the case may be upon filing of appeal, shall issue notice accompanied by a copy of the appeal, affidavit and documents, if any, to the respondent.

Signature valid


Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.14 09:02:34 IST
Reason: Approved

- (b) On the date fixed for hearing, the first appellate authority of second appellate authority, as the case may be shall-
- (i) Hear all the parties to appeal present before him; and
 - (ii) Peruse or inspect documents, relevant records or copies thereof relating to the matter.
- (c) After hearing the parties, perusal or inspection of documents and relevant records or copies thereof relating to the matter, the appellate authority concerned shall pass an order in writing and provide the copy of order to the parties to appeal free of cost.
- (d) The order passed under sub-clause (c) above shall also be placed on the state public procurement portal.

RajKaj Ref
12437816

Signature valid

Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.14 07:02:34 IST
Reason: Approved



Annexure D: Additional Conditions of Contract

1. Correction of arithmetical errors

Provided that a Financial Bid is substantially responsive, the Procuring Entity will correct arithmetical errors during evaluation of Financial Bids on the following basis:

- i. If there is a discrepancy between the unit price and the total price that is obtained by multiplying the unit price and quantity, the unit price shall prevail and the total price shall be corrected, unless in the opinion of the Procuring Entity there is an obvious misplacement of the decimal point in the unit price, in which case the total price as quoted shall govern and the unit price shall be corrected;
- ii. If there is an error in a total corresponding to the addition or subtraction of subtotals, the subtotals shall prevail and the total shall be corrected; and
- iii. If there is a discrepancy between words and figures, the amount in words shall prevail, unless the amount expressed in words is related to an arithmetic error, in which case the amount in figures shall prevail subject to (i) and (ii) above.

If the Bidder that submitted the lowest evaluated Bid does not accept the correction of errors, its Bid shall be disqualified and its Bid Security shall be forfeited or its Bid Securing Declaration shall be executed.

2. Procuring Entity's Right to Vary Quantities

- (i) At the time of award of contract, the quantity of Goods, Works or services originally specified in the Bidding Document may be increased or decreased by a specified percentage, but such increase or decrease shall not exceed Five percent, of the quantity specified in the Bidding Document. It shall be without any change in the unit prices or other terms and conditions of the Bid and the conditions of contract.
- (ii) If the Procuring Entity does not procure any subject matter of procurement or procures less than the quantity specified in the Bidding Document due to change in circumstances, the Bidder shall not be entitled for any claim or compensation except otherwise provided in the Conditions of Contract.
- (i) In case of procurement of Goods or services, additional quantity may be procured by placing a repeat order on the rates and conditions of the original order. However, the additional quantity shall not be more than 50% of the value of Goods of the original contract and shall be within one month from the date of expiry of last supply. If the supplier fails to do so, the Procuring Entity shall be free to arrange for the balance supply by limited Bidding or otherwise and the extra cost incurred shall be recovered from the supplier.

3. Dividing quantities among more than one Bidder at the time of award (In case of procurement of Goods)

As a general rule all the quantities of the subject matter of procurement shall be procured from the Bidder, whose Bid is accepted. However, when it is considered that the quantity of the subject matter of procurement to be procured is very large and it may not be in the capacity of the Bidder, whose Bid is accepted, to deliver the entire quantity or when it is considered that the subject matter of procurement to be procured is of critical and vital nature, in such cases, the quantity may be divided between the Bidder, whose Bid is accepted and the second lowest Bidder or even more Bidders in that order, in a fair, transparent and equitable manner at the rates of the Bidder, whose Bid is accepted.

RajKaj Ref
12437816

Signature valid

Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.14 09:02:34 IST
Reason: Approved

राजस्थान राज्य क्रीडा परिषद

सवाई मानसिंह स्टेडियम, जनपथ, जयपुर

कार्यालय दूरभाष नं० 0141-2744283, फ़ैक्स नं० 0141-2740568, ईमेल आईडी-rsscjaipur@gmail.com

बोली की शर्तें

- विशेष टिप्पणी** :- बोलीदाताओं को इन शर्तों को सावधानी पूर्वक पढ़ना चाहिए तथा अपनी ई-बोलियां भेजते समय इनकी पूर्ण रूपेण पालना करनी चाहिए।
1. तकनीकी प्रस्तावों में सफल बोलीदाताओं के ही वित्तीय प्रस्ताव खोले जावेंगे जो निविदादाता तकनीकी बिड में सफल नहीं पाये गये उनकी वित्तीय बोली नहीं खोली जायेगी।
 2. कोई भी फर्म/संवेदक यदि जी.एस.टी. अधिनियम के अन्तर्गत पंजीकृत नहीं है तो वह बोली नहीं देगा। इनके अभाव में बोलियों पर विचार नहीं किया जायेगा।
 3. जी. एस. टी. देयता प्रमाण पत्र सितम्बर, 2024 का संलग्न करना आवश्यक है।
 4. दरे जी.एस.टी. तथा केन्द्र व राज्य सरकार द्वारा देय समस्त करों सहित देनी होगी।
 5. बोली ऑन-लाईन प्रस्तुत की जावेगी एवं निर्दिष्ट कॉलमों में प्रविष्टी की जावेगी।
 6. दरे गन्तव्य स्थान तक एफ.ओ.आर. सवाई मानसिंह स्टेडियम जयपुर के आधार पर होंगी अर्थात् परिवहन संबंधी कोई राशि परिषद द्वारा पृथक से देय नहीं होगी।
 7. बोलियां उपापन अधिनियम/पारदर्शिता अधिनियम के तत्संबंधी प्रावधानों (धारा-28 आदि) के अधीन रहते हुये उनके खोले जाने की दिनांक से एक वर्ष की अवधि के लिए विधि मान्य होंगी।
 8. बोलीदाता अपनी संविदा या उसके किसी भाग को किसी अन्य एजेन्सी के लिए नहीं सौंपेगा या उपभाडे पर नहीं देगा।
 9. बोलीदाता का उसके प्रतिनिधि की ओर से प्रत्यक्ष अथवा अप्रत्यक्ष रूप से अपना पक्ष समर्थन करना एक प्रकार की अनर्हता होगी। हित विरोधी धारा 80 होगी।
 10. विहित समय एवं तारीख के पश्चात् जो भी बोलियां प्राप्त होंगी उन्हें किसी स्थिति में स्वीकार नहीं किया जावेगा।
 11. यदि बोलीदाता ऐसी कोई शर्त आरोपित करता है जो उसमें वर्णित शर्तों के अतिरिक्त है या उनके विरोध में है तो उसकी बोली को संक्षिप्त रूप में कार्यवाही कर रद्द कर दिया जावेगा।
 12. तकनीकी बोली के साथ बोलीदाता को निम्न दस्तावेज संलग्न करने अनिवार्य होंगे (जिसके आधार पर तकनीकी बिड का मूल्यांकन किया जायेगा) :-
 - i. बोली में अंकित पते के प्रमाण हेतु पानी/बिजली/टेलीफोन/मोबाईल के बिल, पेन कार्ड, पासपोर्ट, आधार कार्ड अथवा ड्राईविंग लाईसेन्स में से कोई एक की प्रमाणित छाया प्रतियां।
 - i. बोलीदाता/फर्म का विगत 3 वर्षों (2021-22, 2022-23 एवं 2023-24) में औसत वार्षिक टर्न ओवर 30.00 लाख से कम नहीं होना चाहिये। इस हेतु बोलीदाता को उक्त वर्षों का सीए से प्रमाणित प्रमाण पत्र की प्रति मय यूडीआई नम्बर सहित संलग्न करनी होगी।
 - ii. गत 3 वर्षों (2021-22, 2022-23 एवं 2023-24) में राजकीय विभागों में किये गये सिविल कार्य (भवन निर्माण कार्य) का एकल कार्य आदेश 18.00 लाख या उससे अधिक या दो कार्य आदेश 12.00 लाख का होना आवश्यक है। इसके प्रमाणीकरण हेतु कार्यादेश एवं कार्य के प्रमाणित प्रमाण पत्र आदि आवश्यक दस्तावेज संलग्न करने होंगे।

Signature valid

Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.14 07:02:34 IST
Reason: Approved

iii. बोलीदाता को माल एवं सेवाकर (GST) के रजिस्ट्रेशन की प्रति संलग्न करनी होगी।

iv. अमानत राशि एवं बोली प्रपत्र शुल्क का डी.डी. संलग्न करना होगा।

12. **बयाना राशि :-**

- (क) बोली से पूर्व (2%) नियमानुसार बयाना राशि ऑफ-लाईन प्रस्तुत की जायेगी। इसके बिना बोलीओं पर विचार नहीं किया जायेगा। यह राशि सचिव, राजस्थान राज्य क्रीड़ा परिषद, जयपुर के पक्ष में बैंक ड्राफ्ट/बैंकर्स चैक में से किसी रूप में जमा करायी जा सकती है।
- (ख) असफल बोलीदाता की बयाना राशि बोली को अंतिम रूप से स्वीकार करने के बाद यथा संभव शीघ्र लौटा दी जावेगी।
- (ग) अनुमोदन की प्रतीक्षा करने वाली या रद्द की गई या संविदाओं के पूर्ण हो जाने के कारण परिषद कार्यालय के पास जमा बयानाराशि/प्रतिभूति निक्षेप को नवीन निविदा के लिए बायाना राशि/प्रतिभूति राशि के प्रति समायोजित नहीं किया जायेगा।

13. **बयाना राशि का समपहरण:-** बयाना राशि को निम्नलिखित मामलों में समपहरत कर लिया जायेगा:-

- (क) जब बोलीदाता बोली खोलने के बाद किन्तु बोली को स्वीकार करने के पूर्व प्रस्ताव को वापस लेता है या उसमें उपान्तरण करता है।
- (ख) जब बोलीदाता विनिर्दिष्ट समय के भीतर विहित करार को निष्पादित नहीं करता है।
- (ग) जब बोलीदाता प्रदायगी के लिए आदेश देने के बाद प्रतिभूति राशि जमा नहीं कराता हो।
- (घ) जब वह निर्धारित समय के अन्तर्गत आदेशों के अनुसार कार्य करने में असफल रहता है अथवा संतोषजनक सेवाएं देने में असमर्थ रहता है।

14. **करार एवं प्रतिभूति निक्षेप :-**

- (क) सफल बोलीदाता को आदेश दिनांक से 7 दिन की अवधि के भीतर नियमानुसार मूल्य के नॉन ज्यूडिशियन स्टॉम्प पेपर पर (जिसका व्यय स्वयं बोलीदाता द्वारा वहन किया जावेगा) एक करार-पत्र निष्पादित करना होगा तथा प्रावधित मूल्य जिसके लिए बोली स्वीकार की गई है।
- (ख) बोली के समय जमा कराई गई बयाना राशि को प्रतिभूति की राशि के लिए समायोजित किया जायेगा।
- (ग) बयाना/प्रतिभूति राशि पर परिषद द्वारा कोई ब्याज का भुगतान नहीं किया जायेगा।
- (घ) प्रतिभूति राशि के रूप में नकद रसीद पत्र/शिड्यूल बैंक का ड्राफ्ट/बैंकर्स चैक मान्य होंगे।

15. **प्रतिभूति राशि का समपहरण :-** प्रतिभूति की राशि को पूर्ण अथवा आंशिक रूप से निम्नलिखित मामलों में समपहरत किया जायेगा:-

- (क) जब संविदा की किसी शर्त/अथवा शर्तों का उल्लंघन किया गया हो।
- (ख) जब बोलीदाता सम्पूर्ण कार्य संतोषजनक ढंग से करने में असफल रहा हो।
- (ग) प्रतिभूति निक्षेप को समपहरत करने के मामले में युक्तियुक्त नोटिस दिया जावेगा इस सम्बन्ध में परिषद के अधिकारी का निर्णय अन्तिम होगा।
- (घ) कार्य में असफल रहने पर परिषद द्वारा वैकल्पिक व्यवस्था करने पर उसमें जो भी व्यय होगा बोलीदाता को देना होगा।
- उसको देय बिल की राशि के भुगतान में से

Signature valid

Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.14 09:02:34 IST
Reason: Approved

- करना सम्भव न हो तो राजस्थान पी.डी.आर.एक्ट या प्रवृत्त अन्य किसी कानून के अन्तर्गत कार्यवाही की जावेगी।
16. करार पत्र को पूर्ण करने एवं उस पर स्टाम्प लगाने का व्यय बोलीदाता द्वारा वहन किया जायेगा तथा परिषद को उस करार पत्र की निष्पादित स्टाम्प शुदा प्रति पडत निःशुल्क प्रस्तुत की जायेगी।
 17. परिषद के प्राधिकृत अधिकारी या उसका विधिवत् प्राधिकृत प्रतिनिधि सभी युक्तियुक्त उचित समयों पर ठेकेदार के परिसर में जायेगा तथा वह विनिर्माण की प्रक्रिया के दौरान या उसके बाद जैसे भी हो किसी भी समय सामग्री का निरीक्षण एवं जांच करने की शक्ति रखेगा।
 18. परीक्षण प्रभार परिषद द्वारा वहन किये जायेंगे। यदि बोलीदाता अत्यावश्यक तत्काल परीक्षण कराना चाहता है या यदि परिणामों से यह ज्ञात होता है कि प्रदाय किया गया सामान विहित स्तरों या विनिर्देशों के अनुसार नहीं है तो परीक्षण प्रभार बोलीदाता द्वारा वहन किये जायेंगे।
 19. अनुमोदित कार्य के लिए यह समझा जाएगा कि उसने कार्य किये जाने वाले विनिर्देशों की सावधानीपूर्वक जांच कर ली है यदि उसे इन शर्तों, विनिर्देशों, रेखाचित्रों आदि के किसी भाग के आशय के बारे में कोई सन्देह हो तो वह संविदा पर हस्ताक्षर करने से पूर्व परिषद से स्पष्टीकरण प्राप्त करेगा।
 20. सफल बोलीदाता को कार्य आदेश जारी तिथि के 10 दिवस के अन्दर कार्य प्रारम्भ करना होगा।
 21. यदि निविदा सूचना में दर्शित मात्रा से अधिक के लिए आदेश दिया जाता है, तो निविदादाता अपेक्षित कार्य करने के लिए बाध्य होगा। पुनः आदेश भी निविदा में दी गयी शर्तों पर दिए जा सकेंगे परन्तु शर्त यह है, कि ऐसे पुनःआदेश मूल रूप से खरीदी गयी मात्रा की 50 प्रतिशत तक के अतिरिक्त प्रदाय के लिए ही होंगे।
 22. **गारन्टी** :- गारन्टी नियमानुसार होगी।
 23. **परिसमापित नुकसानी** :-
 - (1) परिसमापित नुकसानी के साथ कार्य अवधि में वृद्धि करने के मामले में, वसूली राजस्थान लोक उपापन पारदर्शिता अधिनियम, 2012 एवं राजस्थान लोक उपापन पारदर्शिता नियम 2013 के प्रावधान अनुसार होगी।
 - (2) यदि प्रदायकर्ता किन्ही बाधाओं के कारण संविदान्तर्गत कार्य का प्रदाय पूरा करने के लिए समय में वृद्धि कराना चाहता है, तो वह लिखित में परिषद को आवेदन करेगा। किन्तु वह उसके लिए निवेदन बाधा के घटित होने पर तुरन्त उसी समय करेगा न कि प्रदाय पूर्ण होने की निर्धारित तारीख के बाद करेगा।
 - (3) यदि कार्य प्रदाय करने में उत्पन्न हुई बाधा बोलीदाता के नियन्त्रण से परे कारणों से हुई हो तो कार्य की अवधि में वृद्धि परिसमापित नुकसानी सहित या रहित की जा सकेगी।
 24. **वसूली** :- परिसमापित नुकसानी, कम प्रदाय, टूट-फूट, रद्द की गई वस्तुओं के लिए वसूली साधारण रूप से बिल में से की जाएगी। संवेदक कम प्रदाय, टूट-फूट, रद्द किए गए कार्यों की सीमा तक राशि को भी रोका जा सकेगा तथा यदि सेवा सन्तोषजनक ढंग से उनको कार्य करता है तो परिसमापित नुकसानी के साथ वसूली उसे देय राशि एवं विभाग के पास उपलब्ध प्रतिभूति निक्षेप से की जाएगी। यदि वसूली करना सम्भव न हो तो राजस्थान पी.डी.आर.एक्ट या प्रवृत्त अन्य कानून के अन्तर्गत कार्यवाही की जाएगी।

Signature valid

Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.14 09:02:34 IST
Reason: Approved

25. भुगतान :-

- (क) बोलीदाता द्वारा क्रेता अधिकारी को उचित प्रारूप में लोक उपापन नियमों के अनुसार बिल प्रस्तुत करने पर भुगतान किया जायेगा। सभी प्रेषण प्रभार बोलीदाता द्वारा वहन किये जायेंगे। किसी भी सूरत में अग्रिम भुगतान नहीं किया जायेगा।
- (ख) विवादास्पद मदों में राशि का 10 प्रतिशत से 25 प्रतिशत तक को रोका जायेगा तथा उस विवाद का निपटारा हो जाने पर उसका भुगतान कर दिया जायेगा।
- (ग) उन मामलों में, जिनमें परीक्षण करने की जरूरत है, भुगतान तभी किया जायेगा जब उनका परीक्षण कर लिया जाये तथा प्राप्त हुए परीक्षण परिणाम विहित निर्देशों के अनुरूप हों।
26. यदि कार्य की तात्कालिक आवश्यकता के कारण पूर्ण या आंशिक रूप में उन कार्यों को बदलना साध्य नहीं समझा जाए तो राजस्थान राज्य क्रीडा परिषद द्वारा बोलीदाता को सुनवाई किये जाने का एक उचित अवसर देकर, ऐसे कारणों से जो अभिलिखित किये जायेंगे, अनुमोदित दरों में से उपयुक्त राशि की कटौती करेगा। इस प्रकार की गई कटौती अन्तिम होगी।
27. निविदादाता करार को निष्पादित करते समय निम्नलिखित दस्तावेज प्रस्तुत करेगा :-
- (i) यदि भागीदारी फर्म हो तो "पार्टनरशिप डीड" की अनुप्रमाणित प्रति।
- (ii) यदि भागीदारी फर्म रजिस्ट्रार ऑन फर्म्स के पास पंजीकृत हो तो पंजीयन संख्या एवं उसका वर्ष।
- (iii) एक मात्र स्वामित्व के मामले में आवास एवं कार्यालय का पता, टेलीफोन नम्बर।
- (iv) कम्पनी के मामले में कम्पनी के रजिस्ट्रार के द्वारा जारी किया गया प्रमाण-पत्र।
28. संविदा के निर्वचन, आशय या संविदा की शर्तों के उल्लंघन के सम्बन्ध में या अन्य किसी भी प्रकार का विवाद होने पर परिषद का निर्णय अन्तिम होगा।
29. समस्त विधिक कार्यवाहियां यदि संस्थित किया जाना आवश्यक हो तो जयपुर स्थित न्यायालय में ही की जाएगी। अन्यत्र नहीं की जाएगी।
30. बोलीदाता द्वारा अपलोड किये जाने वाले दस्तावेजों पर नम्बरिंग होनी चाही एवं चैक लिस्ट भर कर प्रस्तुत करनी होगी।
31. सचिव, राजस्थान राज्य क्रीडा परिषद, जयपुर को बिना कारण बताये किसी भी बोली को स्वीकार/अस्वीकार करने का अधिकार होगा।
32. जी.एफ. एण्ड ए.आर., राजस्थान लोक उपापन पारदर्शिता अधिनियम, 2012 एवं राजस्थान लोक उपापन पारदर्शिता नियम 2013 के प्रावधान लागू होंगे।

बोलीदाता के हस्ताक्षर
(मय नाम पता एवं मोहर)

Signature valid

RajKaj Ref
12437816

Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.04 09:02:34 IST
Reason: Approved

घोषणा

मैने/हमने पटेल स्टेडियम, अजमेर पर एथलेटिक्स खेल अकादमी भवन की मरम्मत कार्य हेतु की बोली के नियम एवं शर्तों को भली-भाँति पढ व समझ लिया है। मुझे/हमारी फर्म को किसी भी विभाग द्वारा ब्लेक-लिस्ट नहीं किया गया है। इन शर्तों एवं नियमों के अधीन मैं/हम पटेल स्टेडियम, अजमेर में कार्य करने हेतु सहमत एवं वचनबद्ध हूँ/है। यदि मेरे/हमारे द्वारा की किसी बोली की शर्तों, नियमों अथवा आदेशों का उल्लंघन किया जावेगा तो सक्षम अधिकारी द्वारा मेरे/हमारे विरुद्ध बोली के नियम/शर्तों के उल्लंघन की कार्यवाही करने के लिए अधिकृत होगा। इस सम्बन्ध में मुझे/हमें सक्षम/अधिकृत अधिकारी द्वारा लिया गया निर्णय मान्य होगा तथा इसमें मुझे/हमको कोई आपत्ति/हस्तक्षेप नहीं है।

हस्ताक्षर बोलीदाता.....

नाम/पता

टेलीफोन नं.

दिनांक

RajKaj Ref
12437816

Signature valid

Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.14 09:02:34 IST
Reason: Approved

General Instructions for Filling of Bid

The complete bidding document has been published on the website www.rssc.in, <http://sppp.raj.nic.in>, <http://eproc.raj.gov.in>, for the purpose of downloading.

1. Bidders who wish to participate in this bidding process must register on www.rssc.in & <http://sppp.raj.nic.in>,
2. To participate in online bidding process, Bidders must procure a Digital Signature Certificate (Type III) as per Information Technology Act-2000 using which they can digitally sign their electronic bids. Bidders can procure the same from any CCA approved certifying agency, i.e. TCS, safe crypt, Node etc. Bidders who already have a valid Digital Signature Certificate (DSC) need not procure a new DSC.
3. Bidder (authorized signatory) shall submit their offer on-line in electronic formats both for Technical and financial proposal. However, DD for Tender Fees, EMD payable in favor of SECRETARY RAJASTHAN STATE SPORTS COUNCIL, JAIPUR, payable at Jaipur and Processing Fees payable in favor of Managing Director, RAJCOMP Info Services Limited, payable at JAIPUR. **Tender fee, EMD and processing fee DD should be submitted physically at the office of RAJASTHAN STATE SPORTS COUNCIL, JAIPUR, and Scanned copy of same should also be uploaded along with the technical bid.**
4. RAJASTHAN STATE SPORTS COUNCIL, JAIPUR will not be responsible for delay in online submission due to any reason. For this, bidders are requested to upload the complete bid well advance in time so as to avoid Last hours issues like slow speed; choking of web site due to heavy load or any other unforeseen problems.
5. Bidders are also advised to refer "Bidders Manual Kit" available at e-Proc website for further details about the e-tendering process.
6. No contractual obligation, whatsoever shall arise from the bidding process unless and until a formal contract is signed and executed between the tendering authority and the successful Bidder.

SECRETARY

RajKaj Ref
12437816

Signature valid

Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.14 09:02:34 IST
Reason: Approved

UNDERTAKING BY THE BIDDER

This is to certify that I/we before signing this tender have read and fully understood all the terms and conditions contained herein and undertake myself/ourselves to abide by them. I/We have signed all the pages in acceptance of the terms and conditions.

I/We also undertake that I/We will not adopt any malpractices at any stage of bidding/execution.

Signature of the Bidder with Seal
Name:
Designation:
Address:

RajKaj Ref
12437816

Signature valid

Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.14 09:02:34 IST
Reason: Approved

BIDDER'S AUTHORIZATION CERTIFICATE {to be filled by the bidder}

To,
{Tendering Authority},

I/
We.....{Name/Designatio
n} hereby declare/ certify that

..... {Name/ Designation} is hereby authorized to sign relevant documents on behalf of the company/ firm in dealing with Tender with RAJASTHAN STATE SPORTS COUNCIL, JAIPUR.
He/ She is also authorized to attend meetings & submit technical & commercial information/ clarifications as may be required by you in the course of processing the Bid.
For the purpose of validation, his/ her verified signatures are as under.

Thanking you,

Verified Signature:

Name of the Bidder: -
Authorized Signatory: -
Seal of the Organization: -
Date:
Place:

RajKaj Ref
12437816

Signature valid

Digitally signed by Palendra Singh
Designation: Secretary
Date: 2024.12.14.09:02:34 IST
Reason: Approved

CHECKLIST OF DOCUMENTS SUBMITTED

S. No.	Documents to be submitted	Submitted	Not Submitted	Page No.
1.	Scanned Copies of tender document fee, EMD and processing fees			
2.	Copy of Registration of firms (C & Above category for Civil works, Registration under Govt. Department's of Rajasthan/GoI).			
3.	Copy of GST Registration			
4.	Copy of PAN Card			
5.	Proof of Work order and Satisfactory Completion of Civil work (Building work) should be as per tender document condition no. 11 (iii) in financial Year 2021-22, 2022-23 & 2023-24.			
6.	Certificate from Chartered Accountant having UDIN for the proof of average annual Turnover that must be equal/more than the cost of work (bid cost) in the last three Financial Years from 2021-22, 2022-23 & 2023-24.			
7.	Annexure A to D duly signed in context to RTPP Rules-2013.			
8.	Authorization certificate If the tender is signed other than owners			
9.	Copy of GST paid certificate filed by September, 2024 Financial Year 2024-25 in GSTR-3B Performa			
10.	Tender document and Technical Bid and undertaking all three duly signed			
11.	Any other Document			

- Note: -1. The work executed under Govt. /Semi-Govt. / Autonomous Departments shall be considered for experience purposes.
 2. Similar nature shall mean works related to Plantation works.
 3. Last Three FY for works means 2021-22, 2022-23 & 2023-24.
 4. Last three FY for average annual turnover means 2021-22, 2022-23 & 2023-24.
 5. The contractor should ensure that the Registration should be latest or updated.

Signature of Bidder Seal of Establishment
 Full Name of Bidder with address and date

RajKaj Ref
 12437816

Signature valid
 Digitally signed by Rajendra Sin
 Designation: Secretary
 Date: 2024.12.04 09:02:34 IST
 Reason: Approved

Schedule "G"

Name of work :- Maintenance work of Academy building, Patel Stadium, Ajmer.

S. No.	Quantity		Particular	Rate		Amount
Civil Work						
1	1.00	Sqm	Clearing grass and removal of the rubbish upto a distance of 50 m outside the periphery of the area cleared.	2.00	Sqm	2.00
2	1.00	Cum	Earth work in excavation by mechanical means (Hydraulic Excavator)/ manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sum on plan) including dressing of sides and ramming of bottoms, lift upto 1.5 m, including taking out the excavated soil and depositing and refilling of jhiri with watering & ramming and disposal of surplus excavated soil as directed with in a lead of 50 meter. All kinds of soils	178.00	Cum	178.00
3	1.00	Cum	Providing and laying in position cement concrete including curing, compaction etc. complete in specified grade excluding the cost of centering and shuttering - All work up to plinth level. M10 grade Nominal Mix 1: 3: 6 (1 cement : 3 coarse sand : 6 graded stone aggregate 20mm nominal size).	3847.00	Cum	3847.00
4	1.00	Cum	Brick work with F.P.S. bricks of class designation 75 in superstructure above plinth level upto floor V level in all shapes and sizes in : Cement mortar 1 : 6 (1 cement : 6 coarse sand)	4990.00	Cum	4990.00
5	1.00	Sqm	Providing and fixing 50mm thick cement concrete flooring with Metallic concrete hardener topping, under layer of 38mm thick cement concrete 1:2:4 (1-cement : 2-coarse sand : 4-graded stone aggregate 20mm thick nominal size) and top layer of 12mm thick metallic concrete hardener consisting of mix 1:2 (1 cement : 2 stone aggregate, 6mm nominal size) by volume & mixed with metallic hardening compound of approved quality @ 2Kg./Sqm including cement slurry, rounding off edges etc. but excluding the cost of nosing of step etc. complete.	453.00	Sqm	453.00
6	1.00	Sqm	Cement plaster in skirting and/dado 18 mm thick with cement mortar 1:3 (1 cement : 3 coarse sand) finished with a floating coat of neat cement including rounding of junctions with floor	284.00	Sqm	284.00
7	1.00	Sqm	Kota stone slab flooring 25 mm thick over 20 mm (average) thick base laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab including rubbing and polishing complete with base of cement mortar 1 : 4 (1 cement : 4 coarse sand) For area of each slab from 2001 to 5000 Sq.Cm	1023.00	Sqm	1023.00
8	1.00	Cum	Demolishing stone rubble masonry manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge: In cement mortar.	641.00	Cum	641.00
9	1.00	Cum	Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar.	538.00	Cum	538.00
10	1.00	Sqm	Repairs to plaster of thickness 12mm to 20mm in patches of area 2.5 sq. metres and under including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete including disposal of rubbish to the dumping ground within 50 m lead : With cement mortar 1 : 4 (1 cement : 4 coarse sand)	235.00	Sqm	235.00
11	1.00	Sqm	Add extra for mirror polishing on existing marble work/ Kota stone flooring work where ever required to give high gloss finish complete.	121.00	Sqm	121.00
12	1.00	Mtr.	Providing gola 75x75 mm in concrete 1:2:4 (1 cement : 2 coarse sand : 4 stone aggregate 10mm and down gauge) including finishing with cement mortar 1:1:1 cement : 3 fine sand) as per standard detail			

Signature valid

Digitally signed by Rajendra Singh
 Designation: Secretary
 Date: 2024.12.06 10:52:32 IST
 Reason: Approved



13	1.00	Kg	Providing and fixing steel gate, grating, and grills made of angles, tees, square bars, flats, or black pipe with holdfast and fittings complete as per design and drawing including cutting welding and fabrication with priming coat of red oxide	96.00	Kg	96.00
a	1.00	Kg	Extra if square, rectangular hollow tubular sections are used or grill made by flats only (Rs. 96 of 10% Rate)	9.60	Kg	9.60
14	1.00	Sqm	Supplying and fixing fixed wire gauge of 14 mesh x 24 gauge to the metal frame of rolled section by metal beading 20x3mm with suitable screw at not exceeding 150mm distance.	617.00	Sqm	617.00
15	1.00	Sqm	Plaster on new surface on walls in cement sand mortar 1:6 including racking of joints etc. complete fine finish : 20 mm thick.	190.00	Sqm	190.00
16	1.00	Sqm	Finishing with neat cement (punning).	36.00	Sqm	36.00
17	1.00	Cum	Carriage of building rubbish, Stone metal (Earth, Sand, Lime, Morrum manure or sludge) including loading, unloading & stacking with all leads 1 Km	80.00	Cum	80.00
18	1.00	Sqm	Supplying and fixing rolling shutters of approved make, made of 80 x 1.25mm. M.S. laths interlocked together through their entire length and jointed together at the end by end locks mounted on specially designed pipe shaft with brackets, side guides and arrangements for inside and outside locking with push and pull operation complete including cost of spring hooks, providing and fixing necessary 25.3cm. long wire springs grade No. 2 and M.S. top cover 1.25mm thick for rolling shutters as per design & IS 6248-1979.	2074.00	Sqm	2074.00
19	1.00	Sqm	Fine grinded Gangsaw cut 30-35 mm thick stone flooring over 20 mm (average) thick base of cement mortar 1:4 (1 cement : 4 coarse sand) jointed grey cement slurry mixed with pigment to match the shade of stone complete as per design drawing and instruction of EI. Pink sand stone (Bansi Paharpur stone)	937.00	Sqm	937.00
20	1.00	Sqm	Providing and fixing steel glazed doors windows and ventilator shutters of standard rolled steel section (IS 1038-1983) joints mitred and welded with steel lugs 13x3mm, 10cm. long embedded in cement concrete block 15x10x10cm. of 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 20mm nominal size) or with wooden plugs and screws or rawl plugs and screws with fixing clips or with bolts and nuts as required including providing and fixing of plain glass panes 4mm thick with cooper glazing clips and special metal sash putty of approved make or metal beading with screws complete including priming coat of approval steel primer, excluding the cost of metal beading and other fitting except necessary hinges of pivots steel handles peg stay etc. as required : Partly fixed and partly openable [fixed area not to exceed 33%]	3090.00	Sqm	3090.00
21	1.00	Sqm	Extra for double leaf shutters. (Rs. 2869 of 20% Rate)	573.80	Sqm	573.80
22	1.00	Sqm	Providing and fixing double scaffolding system on the exterior side, upto five story made with 4" wooden member 1.5 m c/c horizontal and vertical direction joining with rassi, clamps, challies. The scaffolding system shall be stiffened with bracing, runner, connection of building if necessary with all essential safety features for the workmen etc complete as per direction of EI. The lavation area of the scaffolding shall be measured for payment. The payment will be made once irrespective of duration of scaffolding. Note : This item to be used for maintenance work judically	162.00	Sqm	162.00
23			Grading roof for water proofing treatment with water proffing compound			
i	1.00	Cum	Cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size)	4483.00	Cum	4483.00
24	1.00	Sqm	Supplying and fixing in walls machine cut and polished stone shelves, tands and in CM 1:3 with machine cut stone : Kota stone minimum 30mm thick			
25			Diluting and injecting by hand operated pressure pump chemical Emulsion timber ground treatment [TCCL] ratio 1: 2 as per manufacturers specification for			

Signature valid

digitally signed by Rajendra Singh
 Designation: Secretary
 Date: 2024.12.16 19:52:32 IST
 Reason: Approved

RajKaj Ref
12457806

			CONSTRUCTIONAL Anti-termite treatment (as per IS 6313) part - III 1971 as amended from time to time) (excluding the cost of chemical emulsion) :			
a	1.00	Mtr.	Along the external wall below concrete or masonry apron using chemical emulsion @ 2.25 litres per linear metre including drilling and plugging holes etc. With Chlorpyrifos/Lindane E.C. 20% with 1% concentration	17.00	Mtr.	17.00
b	1.00	Mtr.	Treatment of existing masonry using chemical emulsion@ one litre per hole at 300mm interval including drilling holes at 45 degree and plugging them with cement mortar 1:2(1 cement : 2 coarse sand) to the full depth of the hole. With Chlorpyrifos/Lindane E.C. 20% with 1% concentration	13.00	Mtr.	13.00
c	1.00	Mtr.	Treatment at points of contact of wood work by chemical emulsion Chlorpyrifos/Lindane (in oil or kerosene based solution) @ 0.5 litres per hole by drilling 6 mm dia holes at downward angle of 45 degree at 150mm centre to centre and sealing the same. With Chlorpyrifos/Lindane E.C. 20% with 1% concentration	124.00	Mtr.	124.00
26	1.00	Mtr.	Supplying and providing of two components poly sulphide sealant containing solid contents, conforming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Engineer-in-charge.	865.00	Mtr.	865.00
27	1.00	Kg	Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting (height upto 10 m) , fixing in position and applying a priming coat of approved steel primer all complete:	81.00	Kg	81.00
28	1.00	Sqm	Providing corrugated G.S. sheet roofing including vertical / curved surface fixed with polymer coated J or L hooks, bolts and nuts 8 mm diameter with bitumen and G.I. limpet washers or with G.I. limpet washers filled with white lead and including a coat of approved steel primer and two coats of approved paint on overlapping of sheets complete (upto any pitch in horizontal/ vertical or curved surfaces) excluding the cost of purlins, rafters and trusses and including cutting to size and shape whenever required. 0.80 mm thick with zinc coating not less than 275 gm/m ²	765.00	Sqm	765.00
29	1.00	Sqm	Providing and fixing stone slabs table rubbed, 15-18 mm thick in Walls, Steps, Pillars, Counters, Jambs, Shelves, Sills etc. laid on 12mm (Av.) thick base of CM 1:3 (1 cement : 3 coarse sand) jointing with white cement mortar 1:2 (1white cement : 2 marble dust) with pigment to match the shade of the marble slab including grinding, rubbing and polishing complete. Rajnagar 1st quality/Ageria with light spots. 1501 Cm2 to 3600 Cm2 Tiles	1157.00	Sqm	1157.00
30	1.00	mtr.	Extra for providing edge moulding to 15-18mm thick marble/ Granite stone counters, Vanities etc. including machine polishing to edge to give high gloss finish etc. complete as per design approved by Engineer-in-Charge	146.00	mtr.	146.00
31	1.00	Sqm	Earth work in surface excavation not exceeding 300 mm depth but exceeding 1.5 meter in width as well as 1000 mm	35.00	Sqm	35.00

Signature valid

Digitally signed by Rajendra Singh
Designation: Secretary

Date: 2024.12.16 19:52:32 IST
Reason: Approved

			on plan including disposal of excavated earth up to 50 Mtr. and lift up to 1.5 Mtr. disposed soil to be levelled and neatly dressed: All kinds of soil			
32	1.00	Sqm	Providing and fixing 1st quality standard white, grey, ivory, fume red brown, light green, light blue and other light shades glazed tiles confirming to IS : 13753 & IS :15622 of size 200mm x 300mm in walls, floors, steps, pillars etc. laid on a bed of neat cement slurry finished with flush pointing in the white cement mixed with pigment to match the shade of the tile complete (excluding the cost of cement plaster on walls and pillar).	674.00	Sqm	674.00
33	1.00	Sqm	Providing and fixing 1st quality MAT finished ceramic tile size 300x300mm confirming to IS : 13755 and IS : 15622 colour such as white, grey, ivory, fume red brown, light green, light blue and other light shades in floors, steps, pillars etc. laid on a bed of neat cement slurry finished with flush pointing in the white cement mixed with pigment to match the shade of the tile complete (including the cost of cement mortar bed 1:4).	748.00	Sqm	748.00
34	1.00	Sqm	Extra for using Marble printed / Granite shade or dark shade tiles instead of white, grey, ivory, fume red brown, light green, light blue and other light shades in glazed tiles and MAT finished tiles.	6.74	Sqm	6.74

Electrical Work

35			Wiring of light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper conductor 1.1 kV grade and 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper earth conductor 1.1 kV grade (IS:694) in recessed ISI marked MMS (IS:9537 P - III) virgin material PVC conduit & it's ISI marked (IS:3419-1988) accessories, round tiles, 1.2 mm thick Hot Dipped Galvanized Modular Box with earth terminal, 10A Modular switch, Modular face plate with grid plate, 3 pin ceiling rose / Holder /3 way connector, screws, making connections, testing etc. as required. For specification of copper Conductor, Phenolic Laminated sheet's & Electrical/ Wiring accessories refer Chapter E - 04, E - 05 & E - 07 For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a	1	P. point	Short point (up to 3 mtr.)	359.00	P. point	359.00
b	1	P. point	Medium point (up to 6 mtr.)	578.00	P. point	578.00
c	1	P. point	Long point (up to 10 mtr.)	772.00	P. point	772.00
36			Wiring of 3/5 pin 6 amp. Light plug point with 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper conductor 1.1 kV grade and 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper earth conductor 1.1 kV grade (IS:694) in recessed ISI marked MMS (IS:9537 P - III) PVC conduit & it's ISI marked (IS:3419-1988)accessories, Hot Dipped Galvanized Modular box of 1.2 mm thick with earth terminal, 10 A modular switch, 3/5 pin 6 A modular socket, Modular face plate with grid plate, screws, making connections, testing etc. as required. For specification of copper Conductor, Phenolic Laminated sheet's & Electrical/ Wiring accessories refer Chapter E - 04, E - 05 & E - 07 For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a	1	P. point	On board	357.00	P. point	357.00
b	1	P. point	Short point (up to 3 mtr.)	507.00	P. point	507.00
c	1	P. point	Medium point (up to 6 mtr.)	726.00	P. point	726.00
d	1	P. point	Long point (up to 10 mtr..)	820.00	P. point	820.00

RajKaj Ref
12457806

Signature valid

Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.16 15:52:32 IST
Reason: Approved

		point			point	
37			S&F following sizes (dia.) of ISI marked virgin material MMS (IS:9537 P - III) PVC conduit along with ISI marked (IS:3419-1988) accessories as required in recess including cutting the wall, covering conduit and making good the same as required. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a	1	R. mtr.	20 mm	40.00	R. mtr.	40.00
b	1	R. mtr.	25 mm	56.00	R. mtr.	56.00
c	1	R. mtr.	32 mm	84.00	R. mtr.	84.00
d	1	R. mtr.	40 mm	115.00	R. mtr.	115.00
e	1	R. mtr.	50 mm	170.00	R. mtr.	170.00
38			Rewiring of light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper conductor 1.1 kV grade and 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper earth conductor 1.1 kV grade (IS:694) in recessed ISI marked MMS (IS:9537 P - III) virgin material PVC conduit & it's ISI marked (IS:3419-1988) accessories, round tiles, 1.2 mm thick MS box with earth terminal, 6 A switch, 3 pin ceiling rose/holder / 3 way connector , 3.0 mm thick ISI marked (IS:2036-1995) phenolic laminated sheet, Al.alloy / Cadmium plated iron/ brass screws, cup washers, making connections, testing etc. as required. For specification of copper Conductor, Phenolic Laminated sheet's & Electrical/ Wiring accessories refer Chapter E - 04, E - 05 & E - 07 For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a	1	P. point	Short point (up to 3 mtr.)	256.00	P. point	256.00
b	1	P. point	Medium point (up to 6 mtr.)	472.00	P. point	472.00
c	1	P. point	Long point (up to 10 mtr.)	662.00	P. point	662.00
39			Rewiring of 3/5 pin 6 amp. Light plug point with 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper conductor 1.1 kV grade and 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper earth conductor 1.1 kV grade (IS:694) in recessed ISI marked MMS (IS:9537 P - III) virgin material PVC conduit & it's ISI marked (IS:3419-1988) accessories, 1.2 mm thick MS box with earth terminal of required size, 6 A switch, 3/5 pin 6 A socket, 3.0 mm thick ISI marked (IS:2036-1995) phenolic laminated sheet, Al.alloy / Cadmium plated iron/ brass screws, cup washers, making connections, testing etc. as required. For specification of copper Conductor, Phenolic Laminated sheet's & Electrical/ Wiring accessories refer Chapter E - 04, E - 05 & E - 07 For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a	1	P. point	On board	136.00	P. point	136.00
b	1	P. point	Short point (up to 3 mtr.)	283.00	P. point	283.00
c	1	P. point	Medium point (up to 6 mtr.)	499.00	P. point	499.00
d	1	P. point	Long point (up to 10 mtr.)	689.00	P. point	689.00
40			Wiring of light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper conductor 1.1 kV grade and 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper earth conductor 1.1 kV grade (IS:694) on			

Signature valid

Digitally signed by Rajendra Singh
 Designation: Secretary
 Date: 2024.12.06 19:52:32 IST
 Reason: Approved

Rajkaj Ref
12457886

			ISI marked (IS:14927 P - II) virgin material UPVC trunking & it's accessories, Hot Dipped Galvanized Modular box of 1.2 mm thick with earth terminal/ Surface Moulded virgin material UPVC Modular Box , 10 A Modular switch, Modular face plate with grid plate, 3 pin ceiling rose/holder /3 way Connector, screws, making connections, testing etc. as required. For specification of copper Conductor, Phenolic Laminated sheet's & Electrical/ Wiring accessories refer Chapter E - 04, E - 05 & E - 07 For additional technical parameters of product / work refer Annexure 'A' attached with this BSR				
a	1	P. point	Short point (up to 3 mtr.)	361.00	P. point	361.00	
b	1	P. point	Medium point (up to 6 mtr.)	584.00	P. point	584.00	
c	1	P. point	Long point (up to 10 mtr.)	814.00	P. point	814.00	
41			Wiring of 3/5 pin 6 amp. Light plug point with 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper conductor 1.1 kV grade and 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper earth conductor 1.1 kV grade (IS:694) on surface ISI marked (IS:14927 P - II) virgin material UPVC Trunking & it's accessories, Hot Dipped Galvanized Modular box of 1.2 mm thick with earth terminal/ Surface Moulded virgin material UPVC Modular Box, modular 10A switch, 3/5 pin 6 A modular socket, Modular face plate with grid plate, screws, making connections, testing etc. as required. For specification of copper Conductor, Phenolic Laminated sheet's & Electrical/ Wiring accessories refer Chapter E - 04, E - 05 & E - 07 For additional technical parameters of product / work refer Annexure 'A' attached with this BSR				
a	1	P. point	On board	389.00	P. point	389.00	
b	1	P. point	Short point (up to 3 mtr.)	509.00	P. point	509.00	
c	1	P. point	Medium point (up to 6 mtr.)	732.00	P. point	732.00	
d	1	P. point	Long point (up to 10 mtr..)	929.00	P. point	929.00	
42			S&F following sizes of ISI marked (IS:14927 P - II) virgin material UPVC trunking along with accessories like coupler, inner, outer, elbow, square box, tee, end cap etc. on surface with screws, expansion fasteners as required. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR				
a	1	R. mtr.	20 mm x 12 mm	41.00	R. mtr.	41.00	
b	1	R. mtr.	25 mm x 12 mm	50.00	R. mtr.	50.00	
43			Supplying and drawing FR PVC insulated & unsheathed flexible copper conductor as per PWD specification for electrical Works with ISI marked (IS:694) and as per IS 8130 : 2013 of 1.1 kV grade . Wire should be made from 99.90 % purity copper, class 5 stranding in acc. to IS:8130/IEC 60228 for lower watt loss , oxygen free for less chances of oxidization, insulation PVC type A/C/D , flame retardant as per IS 10810-53, better amperage rating as per IS:3961 part 5, in existing surface or recessed PVC/ MS conduit/casing making connections with Copper Lugs of suitable size, Ferrules, testing etc. as required. OEM Must have its own in house NABL lab setup for all testing facilities for wires. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR				
a	1	Mtr.	1 x 1.5 sq.mm	22.00	Mtr.	22.00	
b	1	Mtr.	2 x 2.5 sq. mm. + 1x1.5sqmm	81.00	Mtr.	81.00	
c	1	Mtr.	2 x 4.0 sq. mm. + 1 x 2.5 sq. mm.	122.00	Mtr.	122.00	
d	1	Mtr.	2 x 2.5 sq.mm	61.00	Mtr.	61.00	
e	1	Mtr.	4 x 10.0 sq.mm	331.00	Mtr.	331.00	

RajKaj Ref
12457806

Signature valid
Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.06 10:52:32 IST
Reason: Approved

				857.00	Mtr.	857.00
f	1	Mtr.	4 x 16.0 sq.mm			
44			P & F paper phenolic resin bonded laminates conforming to IS : 2036 - 1995 for boxes/ frames including making holes for switches etc, with brass screws, washers/ zinc plated nut and bolts as required. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR	1002.0	Sq.m	1002.00
a	1	Sq.m	3.0 mm thick	1291.0	Sq.m	1291.00
b	1	Sq.m	6.4 mm thick			
45			Providing & Fixing of 240/415 V AC MCB with positive isolation of 10 kA breaking capacity (B/ C/D tripping characteristic as per type of load and site requirement) 4 KV impulse withstand voltage, ISI marked IS 8828(1996) / conforming to IEC 60898-1 2002, IEC 60947-2, low watt losses, trip free mechanism , energy limiting of class 3 as per IEC, minimum phase termination capacity of 35sq.mm. , conductor line load reversibility , IP 20 contact protection and fitted in existing distribution board/sheets, minimum electrical operation 20,000 upto 20 A rating and 10,000 upto 63 A, 5000 for 80 A & above rating including making connections, testing etc. as required. OEM shall have submit NABL / CPRI / ERDA accredited lab type test reports & All as per pre approved by Engineer in charge. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a			Single pole MCB (With B/C curve tripping Characteristics)	187.0	Each	187.00
	1	Each	6 A to 32 A rating			
b			Double pole MCB(With B/C curve tripping Characteristics)	566.0	Each	566.00
	1	Each	6 A to 32 A rating	900.0	Each	900.00
	1	Each	40 A rating			
c			Triple pole MCB (With B/C curve tripping Characteristics)	910.0	Each	910.00
	1	Each	6 A to 32 A rating	1384.0	Each	1384.00
	1	Each	40 A rating			
d			Four pole MCB (With B/C curve tripping Characteristics)	1738.4	Each	1738.36
	1	Each	40 A rating	7262.0	Each	7262.00
	1	Each	100 A rating			
46			Providing & Fixing of Recessed/surface mounting heavy duty horizontal type Double Door (Metal / Glazed)Distribution board with Metal end box made out from Galvanized steel / CRCA sheet not less than 1.2 mm thick conforming to IS-8623-1 & 3 / IEC 61439- 1 & 3, powder painted complete with reversible door (for double door DB only)100 amp. insulated copper bus bar/shorting link , copper neutral link, copper earth link , color coded interconnecting wire set of suitable rating and din bar,masking sheet, making internal DB terminations with copper lugs, Ferrules, detachable gland plate, including making connections, testing etc. as required. OEM shall have submit NABL / CPRI / ERDA accredited lab type test reports & All as per pre approved by Engineer in charge. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
I			Metal door (single phase) IK-09 and IP-43 with Metal end box	1795.0	Each	1795.00
a	1	Each	4 Way (4+2)	2018.0	Each	2018.00
b	1	Each	6 Way (6+2)	2184.0	Each	2184.00
c	1	Each	8 Way (8+2)			
ii			Metal door (Three phase) IK-09 and IP-43 with Metal end box	3838.0	Each	3838.00
a	1	Each	4 Way	4811.0	Each	4811.00
b	1	Each	6 Way	5980.0	Each	5980.00
c	1	Each	8 Way			
47			Providing & Fixing of Recessed/surface mounting heavy duty Vertical TPN Distribution board with Metal end box with provision of incomer suitable for MCB and SP / TP MCB as outgoing ,made out from Galvanized steel / CRCA sheet not less than 1.2 mm thick conforming to IS-8623-1 & 3 / IEC 61439- 1 & 3, powder painted complete with reversible door (for double door DB only)100 amp. insulated copper bus bar/shorting link , copper neutral link, copper earth link , color coded interconnecting wire set of suitable rating and din bar,masking sheet, making internal DB terminations with copper lugs, Ferrules, detachable gland plate, including making connections, testing etc. as required. OEM shall have submit NABL / CPRI / ERDA accredited lab type test reports & All as per pre approved by Engineer in charge. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			

Signature valid
 Digitally signed by Rajendra Singh
 Designation: Secretary
 Date: 2024.12.06 19:52:32 IST
 Reason: Approved

Rajkaj Ref
 32497806

			to IS-8623-1 & 3 / IEC 61439- 1 & 3. powder painted with reversible door (for double door DB only) complete with insulated 160 (upto 160 A Incomer) / 250 Amp. copper bus bar, neutral bars with shrouds, earth bar , color coded interconnecting wire set of suitable rating and din bar,masking sheet, making internal DB terminations with copper lugs, ferrules, detachable gland plate, including making connections, testing etc. as required. OEM shall have submit NABL / CPRI / ERDA accredited lab type test reports & All as per pre approved by Engineer in charge.For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
			Double door IP-43 & IK-09 with Provision of Incomer MCCB 100/ 125 A Rating with Metal end box			
a	1	Each	4 Way	11538.0	Each	11538.00
b	1	Each	6 Way	12751.0	Each	12751.00
c	1	Each	8 Way	13775.0	Each	13775.00
48	1	Each	P & F ISI marked (IS:3854) 6 amp. flush type non modular switch with CM/L no. printed and made out from industrial grade Polycarbonate or fire resistant ABS material including cutting hole in tile and making connection testing etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .	23.0	Each	23.00
49	1	Each	P & F ISI marked (IS :3854) 16 amp. flush type non modular switch CM/L no. printed and made out from industrial grade Polycarbonate or fire resistant ABS material including cutting hole in tile and making connection testing etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .	50.0	Each	50.00
50	1	Each	Providing & Fixing of of 3/5 pin 6 amp. flush type non modular socket made out from industrial grade Polycarbonate or fire resistant ABS material, brass terminal with Porcelain based back cover & captive screws including cutting hole in tile and making connection testing etc. as required.All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .	33.0	Each	33.00
51	1	Each	Providing & Fixing of 3/6 pin 16 amp flush type non modular socket made out from Industrial grade Polycarbonate or fire resistant ABS material, brass terminal with Porcelain based back cover & captive screws including cutting hole in tile and making connection testing etc. as required.All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .	78.0	Each	78.00
52	1	Each	Providing & Fixing of ISI marked (IS:371) 6 amp surface type 3 pin ceiling rose with CM/L no. printed and made out from industrial grade Polycarbonate or fire resistant ABS material, brass terminal & captive screws including making connection testing etc. as required.All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .	30.0	Each	30.00
53	1	Each	Providing & Fixing of ISI marked (IS:1258) batten/angle lamp holder with CM/L no. printed and made out from industrial grade Polycarbonate or fire resistant ABS material, brass terminal & captive screws including making connection testing etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .	30.0	Each	30.00
54	1	Each	Providing & Fixing of ISI marked (IS:1583) 16 amp unbreakable 3 pin plug top having 4 amp indicator CM/L no. printed and made out from industrial	68.0	Each	68.00

Signature valid

Digitally signed by Rajendra Singh
 Designation: Secretary
 Date: 2024.12.16 15:52:32 IST
 Reason: Approved

			Polycarbonate or fire resistant ABS material, brass terminal including making connection testing etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
55	1	Each	Providing & Fixing of IS 11037:1984 marked non modular socket size flush type 180 watt rotary minimum 5 step fan regulator with CM/L no. printed and made out from industrial grade Polycarbonate or fire resistant ABS material including making connection testing etc. as required.All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .	219.0	Each	219.00
56			SITC of IP-42 and general construction confirming to IS:8623 : 1993, wall/ free standing floor mounted dust and vermin proof compartmentalised cubical panel as specifications and Other parameters required as per point (a) ,(b), (c),(d), (e), (f), (g), (h) as below:-			
			(a)Thickness of CRCA sheet shall be 2.0 mm, cable alley compartments having concealed hinged type doors with key type lock with / without detachable extension type structure. Removable 3 mm. thick sheet steel gland plates with appropriate size of knockouts for cables shall be provided			
			(b)complete panel shall undergo a process of degreasing, Water rinsing, Activation, derusting, pickling in acid bath, phosphatising & shall be subjected to nine tank process and then Powder coated with approved shade of minimum 70 microns on both side of panel. The panel having PE foam/ Neoprene rubber gasket of not less than 3mm thickness ,required hardware , concealed hinged door with key type locking arrangement for equipment/switchgear earthed with 2.5 sq.mm braided copper wire.			
			(c) Interconnection between bus bar and switchgears /cable shall be rigidly supported and made out by flexible copper wires (up to 63 amp) and by solid bus bar (>63 amp) . control wiring will be carried out with 1.5 Sq.mm, Earth wire with 2.5 Sq.mm and CT with 2.5 sq.mm flexible copper wire only. All joints / interconnections of copper bus bar shall be dully tinned . Clearance between main bus bar and risers / metal parts shall be at least 10 mm additional to width of bus bar Bus bar is insulated by Heat Shrinkable sleeves . Earth and Neutral bus bar shall be half of the size of phase bus bar. (Cost of Bus bar / Flexible wire for Interconnection between Main busbar and Switchgear is to be Paid Extra)			
			(d)Wiring between components within switchgear and Incoming / outgoing cable shall be done through the terminal block only. Direct connection shall not be permitted. Each terminal block shall be one piece moulded, barrier type, 650 volt grade, complete with washers, heads, studs with two nuts and identification strips and shall have adequate continuous current rating. For tap-offs, adjacent terminals with shorting strips shall be used. 10% Spare terminal blocks shall be provided. Wire identification on marking strip shall correspond to the designation of the wiring diagrams. All wire terminals on the equipment shall also be marked with designation corresponding to those of the wiring diagram.			
			(e)All wiring shall be enclosed in plastic channels and neatly bunched and closed in metering chamber. Wiring between terminals of various devices shall be 'point to point' (no wire splitting or tee connections) with wires neatly trucked along the back of the panels, adequately supported to prevent sagging.			
			(f)Floor mounted panel shall be mounted in use frame of ISMC channel size 100 x 50 x 5 mm (to be paid Extra)			

Signature valid

Digitally signed by Rajendra Singh
 Designation: Secretary
 Date: 2024.12.16 10:52:32 IST
 Reason: Approved

RajKaj Ref

12457806

			(g) Tests: The insulation resistance (with 1000 V Megger) and High voltage Power frequency test (by applying a voltage of 2.5KV for one minute) shall be measured between phases, between phase and neutral and between phase and earth. both before and after high voltage power frequency test. The insulation resistance shall not be less than three megaohm. CT Secondary current injection test shall also be carried out.			
	1	Sq. Mtr	(h) only outer surface area on all sides shall be measured & panel to be fabricated only from CPRI approved fabricator only (CPRI Test certificates to be submitted)All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .	5975.0	Sq. Mtr	5975.00
57			Supplying and fixing of Aluminium (IEC 60105 ISO 209-1.2) / Copper (IEC 60028) bus bar by means of SMC / DMC type insulator with standard short circuit withstand capacity , high tensile nuts and bolts spring washers in existing panel including bending , cutting in required shape and size and colour coding with heat shrinkable PVC sleeves. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
	1	Kg.	Electrolytic grade Aluminium bus bar 6010 grade	542.0	Kg.	542.00
58			Providing & Fixing of IS: 13875 & IEC :61326 confirming LED Digital type (up to 500) V range Volt meter / Direct-Ammeter / CT oertated ammeter/ Frequency meter / KWH meter / Multi Function Meter / Power analyzer of class 1 accuracy as per IS : 1248 of size 96mm x 96 mm including making connection by PVC insulated copper conductor with PVC sleeves / channel etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
a	1	Each	Three phase Ammeter with Inbuilt Selector Switch	1689.0	Each	1689.00
b	1	Each	Three phase Voltmeter with Inbuilt Selector Switch	1689.0	Each	1689.00
59			Providing & Fixing of 110/220 V, unibody LED Indicating lamp IEC 60947 with integral circuit, IP 65 above panel & IP 20 terminal block, Approx. body dia for panel not less than 20 mm, length min. 50mm, front LED cover dia min. 29 mm, contact material phospher bronze for Led, PCB contacts shall be of brass (tin plated), impulse dielectric tested for 2.5 KV, Rated insulation resistance shall be 100 M ohm at 500VDC including connection etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
a	1	Each	Red/yellow/Green colour	170.0	Each	170.00
b	1	Each	Blue / white Colour	260.0	Each	260.00
60			SITC of 3 /4 pole current limiting Moulded case circuit breaker (MCCB) made of flame retardent & heat resistant material having following current rating, short circuit breaking capacity at 440/415 V, 50 Hz; O/L & S/C settings , conforming to IS/IEC 60947 P -2 :2003 with front face and centralised adjustable, trip free mechanism, true contact position indicator, line load interchangeability, designed for both horizontal & vertical mounting without any adverse effect on electrical performance, suitable for operation upto 55 degree and without derating upto 40 degree, pollution degree 3, having positive isolation capability, push (test) to trip, trip time less than 10 ms under s/c condition, Breaking capacity Ics = 100% Icu. U imp =8 KV, rated insulation voltage 690 V. provision for UVR , shunt trip , earth fault trip, door interlock, pad lock & rotary handle , including making connections etc as required.OEM shall have submit NABL / CPRI / ISI accredited lab type test certificate for execution All as per pre approved by Engineer in charge. For additional technical parameters of product / work refer Annexure "A" attached with this BSR			

Signature valid

Digitally signed by Rajendra Singh
 Designation: Secretary
 Date: 2024.12.16 11:52:32 IST
 Reason: Approved

			4 pole MCCB With Thermal Magnetic release	7112.00	Each	7112.00
a	1	Each	up to 100 Amp , 25 kA, adjustable O/L & adjustable S/C setting,	11835.00	Each	11835.00
b	1	Each	160 Amp , 25 kA, adjustable O/L & adjustable S/C setting,	15348.00	Each	15348.00
c	1	Each	200 Amp , 25 kA, adjustable O/L & adjustable S/C setting,	19792.00	Each	19792.00
d	1	Each	250 Amp , 35 kA, adjustable O/L & adjustable S/C setting,	23846.00	Each	23846.00
e	1	Each	400 Amp , 35 kA, adjustable O/L & adjustable S/C setting,	34513.00	Each	34513.00
f	1	Each	630 Amp , 50 kA, adjustable O/L & adjustable S/C setting,			
61			Providing & Laying P.V.C. / XLPE insulated & P.V.C. sheathed Armoured Aluminium cable confirming to IS:1554 P-I / IS :7098 P - I of 1.1 KV with H4- Grade electrolytic aluminium conductor confirming to IS 8130 of purity >99.6 %, round / flat strip armouring of cables, Inner / outer sheath confirming to IS:5831 in existing RCC / Hume / Stoneware / PVC pipe/ open duct/cable trench / Cable tray(with cable tie) including testing etc. as required of following size. OEM must have it's own in house NABL accredited Laboratory for testing procedure as per IS:10810.For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a			6.0 Sq. mm	128.00	Mtr	128.00
	1	Mtr	2 core	166.00	Mtr	166.00
	1	Mtr	4 core			
b			10.0 Sq. mm	192.00	Mtr	192.00
	1	Mtr	4 core			
c			16.0 Sq. mm	232.00	Mtr	232.00
	1	Mtr	4 core			
d			25.0 Sq. mm	285.00	Mtr	285.00
	1	Mtr	3.5 core			
e			50.0 Sq. mm	457.00	Mtr	457.00
	1	Mtr	3.5 core			
f			120.0 Sq. mm	945.00	Mtr	945.00
	1	Mtr	3.5 core			
g			185.0 Sq. mm	1415.00	Mtr	1415.00
	1	Mtr	3.5 core			
h			240.0 Sq. mm	1733.00	Mtr	1733.00
	1	Mtr	3.5 core			
62			Supply and installation of high tensile low carbon steel rod molecularly bonded with 99.9 % Copper thickness (250 microns) and confirming to UL 467, IS/IEC 62561-2 of following size and length and as per point mentioned (a), (b), (c), (d), (e) below :-			
			(a) Bore a hole of dia. 100 mm of required length, Place the rod in the centre of Hole			
			(b) filled with anti corrosive conductive compounds with the permanent sealings at both the ends, CPRI/ ERDA tested with RMS capacity of minimum 30 KA for withstanding 1 second .To ensure the moisture content and electrical conductivity, 25 kg for 2000 mm & 50 Kgs for 3000mm of resistance lowering earth enhancement material shall be used as a backfill compound. The compound shall be tested form NABL acredeated lab for low resistivity (less than 0.12 Ohm - meter) & high conductivity in nature with carbon as a major content as per reference of IS 3043-1987,IEEE 80-2013 (clause 14.5d) , IEEE 837 & IER 1956 with latest amendemnts			
			© Connect the rod with copper Strip/Conductor/Wire with suitable clamp made from tinned copper and SS 304 Bolt			
			(d) Place Heavy duty weather proof poly-propylene earth pit chamber with lockable Jam free lid suitable for safe working load 5000 Kg or more of size Top Dia. 225 to 250 mm, Bottom Dia 300 to 350 mm. and Height 250 to 300 mm.			

RajKaj Ref
12457806

Signature valid
Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.16 10:52:32 IST
Reason: Approved

			(d) Testing of earth resistance for value of 5 ohms or less as required & must record by engineer in charge during site visit and ensure to enter in measurement book.				
			(e) Test certificates for confirming above standards from OEM is mandatory. All as per pre approved by Engineer in charge. For additional technical parameters of products/work, refer Annexure "A" attached with this BSR.				
	1	Set	25 mm thick and 3 Mtr. Long			7955.00	Set 7955.00
63			Supply & Laying following size earth strip in horizontal or vertical run in surface by means of Earth strip DMC Insulator including riveting/ soldering/ welding, Jointing shall be done by overlapping and with 2 set of Brass (for Cu strip) / GI (for GI Strip) nut bolt & spring washer spaced at 50cm making connection etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/work, refer Annexure "A" attached with this BSR.				
	a	1	Mtr.	25mm x 3mm copper strip		1037.0	Mtr. 1037.00
	b	1	Mtr.	25mm x 3mm G.I. (Hot Dipped) Strip		105.0	Mtr. 105.00
64				Supply & Laying following size earth wire in horizontal or vertical run in ground/surface/recess including riveting, soldering, saddles, making connection with GI/Cu purity purity >95% thimble etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/work, refer Annexure "A" attached with this BSR.			
	a	1	Mtr.	8 SWG tinned copper Wire		163.0	Mtr. 163.00
	b	1	Mtr.	8 SWG G.I. (Hot Dipped) Wire		20.0	Mtr. 20.00
65				Providing & Fixing of BEE Star rated copper wounded double ball bearing capacitor start, aluminium body & Metallic blade ceiling fan Conforming to all the performance requirements laid down in IS 374:2019 including all amendments, as applicable; & Carry BIS licensing (i.e. ISI marking) with down rod up to 80 cm with secondary support safety cable (steel rope), cotter pin with 3 x 1.5 sq.mm pvc insulated flexible copper conductor making connection testing etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/work, refer Annexure "A" attached with this BSR.			
	a	1	Each	1200 mm Sweep BEE 1 Star rated (service value ≥ 4.0 to < 4.5)		1890.00	Each 1890.00
66				Providing & Fixing of Double ball bearing, copper wounded capacitor start single phase metallic blade fresh air fan, in existing opening including cost of hardware, flexible 3 core copper conductor, making connections, testing etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/work, refer Annexure "A" attached with this BSR.			
	a	1	Each	225 mm sweep		1687.00	Each 1687.00
	b	1	Each	300 mm sweep		1822.00	Each 1822.00
67				Providing & Fixing of Heavy duty capacitor start, copper wound Double ball bearing 900/1400 RPM single phase Exhaust fan conforming to IS:2312 ISI marked in existing opening including making connections testing etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/work, refer Annexure "A" attached with this BSR.			
	a	1	Each	300 mm sweep(900/1400 RPM)		3175.00	Each 3175.00
	b	1	Each	380 mm sweep(900/1400 RPM)		4255.00	Each 4255.00
68				Providing & Fixing of energy efficient direct fit (Retrofit) Polycarbonate/ Glass housing SMD Mid Power LED tube rod (with integral driver & alum. heat sink), on existing fixture. system lumen efficacy ≥ 100 lm/Watt output internal surge protection of RajKaj Ref, THD $\leq 20\%$, p.f. ≥ 0.95 , CRI > 80 , life time ≥ 24578 hours, Burning Hours with 70% of initial Lumen maintained, life ends, CCT 3000°K / 4000°K / 5700°K			

Signature valid
 Digitally signed by Rajendra Singh
 Designation: Secretary
 Date: 2024.12.16 10:52:32 IST
 Reason: Approved

			/6000°K/6500°K (As per ANSI Bin) , maximum power consumption should not more than the specified rating and Fixture shall be of BIS standard and trade mark certificate (T.C.). Manufactures Word Mark/ Name Engraved/ Embossing/ Screen printing on housing. OEM must have its own in house NABL lab setup for all testing facilities for LED fixtures. (LM79 & LM80)certificate / Report from OEM shall be submitted. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
	1	Each	1200mm , Min. Lumens output 2000 lm LED Tube rod with Polycarbonate Housing	270.0	Each	270.00
69			Providing & Fixing of IK08 IP-66 protected high power LED flood light system with single piece Pressure diecast aluminium housing, toughened glass diffuser with suitable lenses on LED to achieve various beam angles, of high power LED of 3 to 5 watt each . Integrated potted driver as a unique BIS R number having efficiency more than 85 % and in compliance to BIS certified and Trade mark certificate. The System level Luminaire efficacy >=125 lm/wt. LED driver Input Voltage AC 120 to 270 V AC with High voltage Cutoff @>=300 V AC and Auto resetting Safety .Power Factor >0.95 , THD(I) <10% , driver current <=750mA. driver should be Phase to phase protection of 440 V for 4 Hrs. Electrical Connector , Surge Protection Min >=4KV internal and 10KV external but inside driver compartment, System life of 50000 Burning hours with 70% of Initial Lumens maintained, CRI>70 and CCT 5700K ±355K. Manufactures Word Mark/Name Engraved/Embossing/Screen printing on die cast housing to allow traceability/authenticity. Fixture shall be IS 10322 Complied.OEM Must have its own in house NABL lab setup for all testing facilities for LED fixtures. (LM79/LM80) Certificate/ report with liable warranty of product/accessories from OEM shall be submitted. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
a	1	Each	High Power LED Flood Light Minimum lumen output 3700 lm	2659.00	Each	2659.00
b	1	Each	High Power LED Flood Light Minimum lumen output 6200 lm	3213.00	Each	3213.00
c	1	Each	High Power LED Flood Light Minimum lumen output 8700 lm	3739.00	Each	3739.00
d	1	Each	High Power LED Flood Light Minimum lumen output 10000 lm	4820.00	Each	4820.00
e	1	Each	High Power LED Flood Light Minimum lumen output 18650 lm	10857.00	Each	10857.00
f	1	Each	High Power LED Flood Light Minimum lumen output 30000 lm	18797.00	Each	18797.00
g	1	Each	High Power LED Flood Light Minimum lumen output 37500 lm	21457.00	Each	21457.00
h	1	Each	High Power LED Flood Light Minimum lumen output 43750 lm	27237.00	Each	27237.00

Sanitary Work

70	1.00	Nos	P & F Indian type white glazed vitreous china 1st quality W.C. orissa pan (IS :2556 Mark) with 100 mm vitreous china P or S trap including cutting and making good the wall and floor: Size 580x440mm.	3080.00	Nos	3080.00
71	1.00	Nos	P & F European type white glazed vitreous china 1st quality W.C pan (IS : 2556 Mark) with P or S trap including cutting and making good the wall and floor.	2420.00	Nos	2420.00
72	1.00	Nos	P & F water closet Seat Cover, With brass hinges complete : Solid PVC (IS 2548 marked) grade I EWC.			

Signature valid
 Digitally signed by Rajendra Singh
 Designation: Secretary
 Date: 2024.12.16 10:52:32 IST
 Reason: Approved

RajKaj Ref
12457806

73	1.00	Nos	Labour charges for removing W.C. pan (any type) of all sizes with care including all necessary fittings P or S trap.	286.00	Nos	286.00
74	1.00	Nos	P & F 1st quality WVC Urinal (IS:2556 mark) with 25mm dia G.I. waste pipe, dome waste couplings, concealed iron brackets or screws etc complete. Flat Back (large) or half stall size 610x400x80mm.	4637.00	Nos	4637.00
75	1.00	Nos	P&F Marble Urinal Partition slab both sides polished of approved design cut from marble size 900x600mm. Makrana II quality marble having light spots	923.00	Nos	923.00
76	1.00	Nos	Labour charges for removing and refixing of urinals (all type & sizes) including all necessary fittings.	339.00	Nos	339.00
77			P & F Flush Cock / Flush Valve (IS : 9758 Mark) for WC of approved quality make :	975.00	Each	975.00
a	1.00	Each	(-do-) concealed 25mm nominal bore.	551.00	Each	551.00
b	1.00	Each	Brass / Gun metal Half-turn wt. 1 Kg. of approved quality / make, 25mm nominal bore.	239.00	Nos	239.00
78	1.00	Nos	Removing and re-fixing of wash hand basin including all necessary fittings.			
79			P & F WVC wash basin (1 st quality, I.S. : 2556 Mark) of approved make with C.I. brackets duly painted, 1 No. 15 mm C.P. Pillar cock (IS : 8934 Mark) & 32 mm C.P. brass waste coupling of approved make, 25 mm G.I. waste pipe complete including cutting & making good the wall.:	2745.00	Each	2745.00
a	1.00	Each	Size 580 mm x 450 mm	2994.00	Each	2994.00
b	1.00	Each	Size 550 mm x 400 mm dia for counter top			
80			P & F Bottle Trap of approved make :	584.00	Each	584.00
a	1.00	Each	C.P Brass 40 mm	145.00	Nos	145.00
81	1.00	Nos	P& F waste Pipe with all fitting P.V.C with C.P nut 32 mm			
82			P & F Bevelled edge Mirror/mirror with teak wood lipping around of special glass of approved make as per direction of Engineer-in-charge complete with 6mm thick commercial ply base fixed to wooden screws & washers.	575.00	Nos	575.00
a	1.00	Nos	Size 600 x 450mm x 4 mm thick	1538.00	Sqm	1538.00
b	1.00	Sqm	Other sizes			
83			P & F Towel Rail or Ring of approved quality/make:	516.00	Nos	516.00
a	1.00	Nos	C.P. brass Towel Rail elbow type with concealed screws size 600 mm (Heavy duty).	254.00	Nos	254.00
b	1.00	Nos	C.P. Brass Towel Ring revolving type	97.00	Nos	97.00
84	1.00	Nos	P & F Grating of approved quality/make:Stainless Steel Sheet size 125mm dia. Heavy Quality of approved make	156.00	Nos	156.00
85	1.00	Nos	P & F Soap Dish or Tray of approved quality/make C.P. brass heavy and superior quality.	376.00	Nos	376.00
86	1.00	Nos	P & F Shower arm 15mm dia of approved quality/make. C.P.brass heavy & superior quality 370mm Projection.	573.00	Nos	573.00
87	1.00	Nos	P & F Bath Shower of approved quality/make. C.P. brass of Heavy & superior quality, revolving with adjustable key 150mm.	119.00	Nos	119.00
88	1.00	Nos	P & F Extension Pipe for bib cocks of approved quality/make. C.P. brass of Heavy & Superior quality 5100x15mm	18.00	Nos	18.00
89	1.00	Nos	Providing & fixing C.P.flange for 15mm dia taps.			
90	1.00	Cum	Filling of sunk portion of roof with earthen pots of required height including filling voids with 1:3:6 light concrete, using brick bats complete levelling and dressing the surface by 50mm thick cement concrete 1:2:4 as per specification.	1775.00	Cum	1775.00
91			P & F G.I. pipes (Internal Work) with G.I. Fittings excluding union (IS:1239 Mark) & MS clamps including cutting and making good the walls and floors:			
a	1.00	Mtr	Concealed pipe in wall including painting with anticorrosive bitumen paint 15 mm dia nominal bore Class B class			
b	1.00	Mtr	Exposed on wall 25 mm dia nominal bore			

Signature valid

Digitally signed by Rajendra Singh
 Designation: Secretary
 Date: 2024.12.06 12:52:32 IST
 Reason: Approved

RajKaj Ref
 12457806

92			Making connection of G.I. distribution branch with G.I. main including all fitting.			
a	1.00	Nos	Upto 25mm dia	265.00	Nos	265.00
b	1.00	Nos	Beyond 25mm & upto 100mm dia	389.00	Nos	389.00
93			P & F Pillar Cocks (IS :8934 Mark) of superior quality and approved make:			
a	1.00	Nos	C.P. Pillar cock, 15 mm dia nominal bore	779.00	Nos	779.00
b	1.00	Nos	Synthetic Material (PTMT) Pillar cock of approved quality / make 15mm nominal bore.	388.00	Nos	388.00
94			P & F Bib Cock (IS : 8931 Mark), Superior quality of approved make:			
a	1.00	Each	C.P. Brass bib cock, 15mm nominal bore.	590.00	Each	590.00
b	1.00	Each	(-do-) Long body, 15mm nominal bore weight not less than 690 gm	783.00	Each	783.00
c	1.00	Each	Synthetic Material(PTMT) bib cock of approved quality/ make, Long Body, 175 mm long	295.00	Each	295.00
95			P & F <i>Push Cock</i> superior quality, of approved make			
a	1.00	Each	C.P. Brass 15 mm.	370.00	Each	370.00
b	1.00	Each	Synthetic Material (PTMT) push cock of approved quality/make 15mm.	205.00	Each	205.00
96			P & F Ball Cock (IS :1703 Mark) with Rod & P.V.C. Ball complete :			
a	1.00	Each	Brass wt. Not less than 300 gm, 15mm.	314.00	Each	314.00
b	1.00	Each	(-do-) wt. Not less than 600 gm, 25mm.	440.00	Each	440.00
c	1.00	Each	(-do-) wt. Not less than 800 gm, 32mm.	480.00	Each	480.00
97			P & F <i>Inlet Connection</i> (Angle Valves) Superior quality, of approved make, for Wash basin, Gyser etc.			
a	1.00	Each	---do--- with 37 cm long thread and nut	590.00	Each	590.00
b	1.00	Each	Synthetic Material (PTMT) Inlet connection of approved quality/make 15 mm nominal size.	240.00	Each	240.00
98	1.00	Nos	P & F 15 mm. Dia Connection Pipe of approved quality/make : PVC pipe with C.P. Brass nuts upto length, 450mm	101.00	Nos	101.00
99			P & F <i>Full-way Valve</i> (IS:778 Mark) or wheel valve of approved make :			
a	1.00	Each	Gun-metal 15mm nominal bore.	227.00	Each	227.00
b	1.00	Each	(-do-) 25mm nominal bore.	529.00	Each	529.00
c	1.00	Each	(-do-) 50mm nominal bore.	1464.00	Each	1464.00
100			P & F <i>PVC Storage Tank</i> ISI Marked (IS : 12701) indicating the BIS license No), of approved make with cover, 25mm dia 1M long G.I. over-flow pipe & 25 Cm. long wash out pipe with plug & socket, including making connection etc., complete of approved design:			
a	1.00	Nos	300 litres capacity	2352.00	Nos	2352.00
b	1.00	Nos	500 (-do-)	3920.00	Nos	3920.00
c	1.00	Nos	1000 (-do-)	7841.00	Nos	7841.00
101	1.00	Nos	Hoisting Charges for each floor : For water tanks	157.00	Nos	157.00
102			Supply & fixing G.I. Union ISI marked in G.I. pipe line as required complete in all respect of size :			
a	1.00	Nos	15mm dia nominal bore	101.00	Nos	101.00
b	1.00	Nos	25mm dia nominal bore	164.00	Nos	164.00
c	1.00	Nos	50mm dia nominal bore	463.00	Nos	463.00
103	1.00	Nos	P & F <i>Square-mouth</i> gully trap 'A' grade (IS 651-1992 :marked) of approved make complete with C.I. grating, frame & Cover masonry chamber in C.M. 1:6, 100mm thick C.C. 1:5:10 base concrete, 40mm thick C.C.M-15 grade coping, 12mm thick cement plaster in CM 1:3 complete as per approved design & type. Trap size 225 X 150 mm, ferrow cement cover with frame Internal Chamber size 450 X 450mm.	1529.00	Nos	1529.00

RajKaj Ref
12457806

Signature valid

Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.16 10:52:32 IST
Reason: Approved

104	1.00	Nos	Raising manhole cover and frames slab to required level including dismantling existing slab and making good the damage as required (raising depth of manhole masonry to be paid separately). Rectangular manhole 150x120 cm	1487.00	Nos	1487.00
105			Construction of manhole in all type of soil inner size 90 X 60 Cm. 300 mm thick masonry in CM 1:6, 10 Cm. thick cement concrete 1:5:10 in foundation, 20 mm thick inside plaster in CM 1:6, finished with floating neat cement, 50mm thick M-15 grade C.C. flooring, making channels, 80mm thick stone slab covering with 40mm thick M-15 grade C.C. flooring. Cement cover with frame of 450mm dia, earthwork etc. complete as per design including disposal of surplus earth within 50 mtr. lead.	5489.00	Nos	5489.00
(a)	1.00	Nos	Depth up to 0.5 M	206.00	Nos	206.00
(b)	1.00	Nos	Add extra over item 3.19.1 for every additional 0.10m depth above 0.5 m depth.			
106	1.00	Sqm	Dismantling tile work in floors and roofs laid in cement mortar including stacking of serviceable material and disposal of unserviceable material within 50 meter lead: For thickness of tiles 10mm to 25mm.	20.00	Sqm	20.00
107	1.00	Mtr	Dismantling GI pipes (external work) including excavation and refilling trenches after taking out the pipes and including stacking of pipes within 50 meter lead: 15mm to 40mm nominal bore.	41.00	Mtr	41.00
108	1.00	Nos	Making of hole (width up to 150 mm) in R.C.C. slab/wall/beams by power driven drilling machine complete as per direction of EI above 150 mm thick	270.00	Nos	270.00
109	1.00	Sqm	Plaster on new surface on walls in cement sand mortar 1:4 including racking of joints etc. complete fine finish : 25mm thick	227.00	Sqm	227.00
110	1.00	Sqm	Finishing with neat cement (punning).	36.00	Sqm	36.00
111	1.00	Sqm	Half brick masonry in Superstructure , above plinth level upto floor V level using bricks of designation 75 Cement mortar 1 : 4 (1 cement : 4 coarse sand)	553.00	Sqm	553.00
112	1.00	Sqm	Providing and fixing Granite stone slab mirror polished and machine edge cut in walls, pillars, steps, Shelves, Sills Counters, Floors etc. laid on 12mm (Av.) thick base of cement mortar 1:3 (1 cement : 3 coarse sand) jointing with white cement mortar 1:2 (1white cement : 2 marble dust) with pigment to match the shade of the marble slab including grinding, rubbing and polishing complete. South zed Black Above 3601 Cm2 Slabs	4076.00	Sqm	4076.00
113	1.00	Mtr	Extra for providing edge moulding to 15-18mm thick marble/ Granite stone counters, Vanities etc. including machine polishing to edge to give high gloss finish etc. complete as per design approved by Engineer-in-Charge. Granite/ Kota stone Work. Full edge moulding.	146.00	Mtr	146.00
114	1.00	Cum	Providing and laying in position cement concrete including curing, compaction etc. complete in specified grade excluding the cost of centering and shuttering - All work up to plinth level. M15 grade Nominal Mix 1: 2: 4 (1 cement : 2 coarse sand : 4 graded stone aggregate 40mm nominal size).	4544.00	Cum	4544.00
115			P&F rigid PVC pipe fittings (IS: 4985 mark) of approved quality /make including joining the pipe with solvent cement rubber ring and lubricant:			
a			Plain Tee			
i	1.00	Each	75mm dia	114.00	Each	114.00
ii	1.00	Each	110mm dia	187.00	Each	187.00
b			Plain floor trap			
i	1.00	Each	110mm dia	230.00	Each	230.00
c			Vent Cowel			
i	1.00	Each	110mm dia			
d			Bend 87.5			
i	1.00	Each	110mm dia			

RajKaj Ref
12457806

Signature valid

Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.16 10:52:32 IST
Reason: Approved

116			Providing and Fixing Unplasticized Poly Vinyl Chloride (UPVC) SWR Pipes fittings type B for sciland waste discharge system (IS:13592 : 1992 Marked) of approved quality /make	282.00	Each	282.00
a	1.00	Each	Offset 110mm dia			
117			P & F Stop Cock (IS :8931 Mark), superior quality & of approved make:	477.00	Each	477.00
a	1.00	Each	C.P. Brass 15mm nominal bore.	1009.00	Each	1009.00
b	1.00	Each	C.P. Brass Concealed Stop Cock 15mm			
118			P&F rigid PVC Pipe (IS:4985 mark) class II/ (4 Kg./Cm ²) approved quality /make including joining the pipe with solvent cement rubber ring and lubricant.			
a	1.00	Mtr	75 mm dia	177.00	Mtr	177.00
b	1.00	Mtr	110 mm dia	282.00	Mtr	282.00
119			P & F Low level Flushing Cistern of 10 litres capacity (IS : 2556mark). Of approved make with complete fittings C.I. brackets duly painted, brass ball cock with ball, (IS: 1703 mark) complete including cutting and making good the wall:			
a	1.00	Each	PVC with CP brass long band.	1491.00	Each	1491.00
120	1.00	Each	P & F Jet spray for water closet with C.P. Copper Tube flange of approved make.	381.00	Each	381.00
121	1.00	Mtr.	P & F G.I. Pipes (External Work) with G.I. fittings excluding union (IS : 1239 Mark) including trenching & refilling earth etc. 50mm dia nominal bore 'B' Class	491.00	Mtr.	491.00
122	1.00	Each	P & F Gun-metal Non-return Valve or Check Valve (IS :Make) of approved make, superior quality: (a) 15mm nominal bore- Horizontal	272.00	Each	272.00
123	1.00	Each	P & F Mixing Range (15mm) C.P. One hole/close hole basin mixer with casted spout.	1740.00	Each	1740.00
124	1.00	Each	P & F C.P. brass Urinal Spreader for stall urinal of approved make.	363.00	Each	363.00
125	1.00	Each	P& F waste Coupling with fittings of approved quality /make: C.P Brass 40 mm dia	218.00	Each	218.00
126	1.00	Mtr.	Providing Laying & jointing glazed S.W. pipes grade 'A' (IS:651 marked) of approved make with spun yarn & stiff mixture of cement mortar 1:1, excavation & refilling of earth in all types of soil upto 1.2m depth, S.W. fittings, including testing of joints etc. complete. 150mm dia	406.00	Mtr.	406.00
127	1.00	Mtr.	Providing & Laying C.C. 1:5:10 (Stone aggregate 40mm nominal size) upto haunches of S.W. pipes including 150 mm thick bed concrete (Width W= Dia of pipe in Cm+ 30Cm.) concrete width to be reduced from width W at center of pipe to '0' at top of pipe. (Excluding cost of pipe) 150mm dia S.W. pipe	353.00	Mtr.	353.00
128	1.00	Each	Construction of chamber in all type of soil with 300 mm thick masonry in CM 1:6 m, 10 cm thick C.C. 1:5:10 in foundation, 20mm thick insider plaster in Cm 1:6, finished with floating neat cement, 50mm thick M-15 grade C.C. flooring, earthwork etc. complete as per design including disposal of surplus earth within a lead of 50 mtr. Inside size 450 x 450mm depth upto 0.5 M Cement cover with frame	2332.00	Each	2332.00
129	1.00	Each	P & F foot valve of superior quality and approved make with fittings : Brass 25 mm.	172.00	Each	172.00
130	1.00	Each	P & F Kitchen & Lab. Sink of approved make with C.I. brackets duly painted, 40 mm C.P. waste coupling, C.P. Brass chain with rubber plug, 40 mm G.I. waste pipe up-to floor level complete including cutting and making good the wall & floor : 1.0 mm thick Salem stainless steel AISI - 304 & IS 13983-1994 kitchen sink of approved make as per Engineer-in-charge with large waste coupling. 200 x 8 x 8 20x16x8	5062.00	Each	5062.00
131	1.00	Each	P & F C.P. Health Faucet with IMtr. long Tube & Hook of approved make and heavy as per direction of Engineer-in-Charge			

Signature valid

Digitally signed by Rajendra Singh
 Designation: Secretary
 Date: 2024.12.26 11:52:32 TST
 Reason: Approved

RajKaj Ref
12457806

132	1.00	Each	C.P. Pillar cock, Swan-neck with casted spout, 15mm nominal bore.	1246.00	Each	1246.00
133	1.00	Each	Providing and fixing Superior quality CP Brass fittings of approved make as per direction of Engineer-in-charge Angular stop cock with long thread 15 mm nominal size	762.00	Each	762.00
134	1.00	Each	Providing and fixing Superior quality CP Brass fittings of approved make as per direction of Engineer-in-charge Two way Bib Cock 15 mm nominal size	1174.00	Each	1174.00
135	1.00	Mtr	P&F rigid PVC Pipe (IS:4985 mark) class II/ (4 Kg./Cm2.) approved quality /make including joining the pipe with solvent cement rubber ring and lubricant. 160 mm dia	463.00	Mtr	463.00
136	1.00	Each	Construction of chamber in all type of soil with 300 mm thick masonry in CM 1:6 m, 10 cm thick C.C. 1:5:10 in foundation, 20mm thick insider plaster in Cm 1:6, finished with floating neat cement, 50mm thick M-15 grade C.C. flooring, earthwork etc. complete as per design including disposal of surplus earth within a lead of 50 mtr. Inside size 300 X 300 mm depth upto 0.5 M Cement cover with frame.	1049.00	Each	1049.00
137	1.00	Rm	Supply & fixing Pre-cast RCC Rinngs at the mouth of recharge shaft of M20 mix with 40 mm thickness Diameter 750 mm	666.00	Rm	666.00
138	1.00	Sqm	Cement concrete flooring 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate) finished with a floating coat of neat cement including cement slurry, making of lines or groove etc complete but excluding the cost of nosing of steps etc. complete. 75mm thick with 20mm thick nominal size aggregate.	458.00	Sqm	458.00
139	1.00	Cum	Brick work with F.P.S. bricks of class designation 75 in superstructure above plinth level upto floor V level in all shapes and sizes in : Cement mortar 1 : 4 (1 cement : 4 coarse sand)	5196.00	Cum	5196.00
140	1.00	Cum	Random Rubble stone masonry for with hard stone in foundation and plinth in Cement Sand mortar above 30 CM thick wall in: Cement Mortar 1:6 (1-Cement : 6-Sand).	2838.00	Cum	2838.00
141	1.00	Sqm	Stone slab roofing on ground floor with fine grained stone slab from approved quarry including filling of joints of parapet and slab on both sides in cement sand mortar 1:4, with ceiling pointing in cement sand mortar 1 : 3 complete as per specification and instruction of Engineer In Charge	1648.00	Sqm	1648.00
142	1.00	Sqm	Add extra for subsequent story (Rs. 1648 of 20% Rate)	329.60	Sqm	329.60
143	1.00	Cum	Providing and laying in position cement concrete including curing, compaction etc. complete in specified grade excluding the cost of centering and shuttering - All work up to plinth level. M15 grade Nominal Mix 1: 2: 4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm nominal size).	4624.00	Cum	4624.00
144	1.00	Sqm	P & F 1st quality Vitrified Porcelain Polished tiles on floor, skirting and steps etc. in different sizes (thickness to be specified by manufacturer) with water absorption less than 0.08% and conforming to IS 15622 of approved make in all colour and shade, laid with 20 mm thick CM 1 : 4 including grouting the joints with white cement and matching pigment etc complete. size 600 mm X 600 mm	911.00	Sqm	911.00
145	1.00	Sqm	Add extra for Fixing glazed/ Ceramic/ Vitrified floor tiles with cement based high polymer modified quick-set tile adhesive (Water based) conforming to IS: 15477, using 5kg. adhesive per sum of tile area, in average 3mm thickness instead of cement mortar.	128.00	Sqm	128.00
146	1.00	Sqm	Providing and laying water proofing treatment in sunken portion of WCs, bathroom etc., by applying cement slurry mixed with water proofing cement compound consisting of applying a) first layer of slurry of cement @ 0.488 kg/sqm, mixed with water proffing cement compound @ 0.253 kg/sqm. This layer will be allowed for 4 hours. b) Second layer of slurry of cement @ 0.242 kg/sqm mixed with water proffing cement compound @ 0.126 kg/sqm.	275.00	Sqm	275.00

Signature valid

Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.16 10:52:32 IST
Reason: Approved

			kg/sqm This layer will be allowed to air cure for 4 hours followed by water curing for 48 hours. The rates includes preparation of surface treatment & sealing of all joints ,corners, junction with polymer mixed slurry.			
147	1.00	Cum	Carriage of Building Rubbish Stone metal (Grit and ballast etc.) including loading unloading etc. complete with all lead. 1 Km.	80.00	Cum	80.00
Painting Work						
148	1.00	Sqm	Providing and applying plaster of paris putty of 2 mm thickness over plastered surface to prepare the surface even and smooth complete	69.00	Sqm	69.00
149			Finishing wall with water proofing cement paint of approved brand and manufacture and or required shade to give an even shade including all scaffolding:	53.00	Sqm	53.00
			New work (Two or more coats applied @ 3.84 kg/10 sqm).	20.00	Sqm	20.00
a	1.00	Sqm	Old work (One or more coats).			
b	1.00	Sqm	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade :	69.00	Sqm	69.00
150			Two or more coats on new work	34.00	Sqm	34.00
a	1.00	Sqm	One or more coats on old work.			
b	1.00	Sqm	Painting (two or more coats) on rain water soil, waste and vent pipes and fitting with black anticorrosive bitumastic paint of approved brand and manufacture over and including a priming coat of ready mixed zinc chromate yellow primer on new work : 100mm dia. Pipes	26.00	Mtr.	26.00
151	1.00	Mtr.	Old work (one or more coats) including scrapping old surface and repairing with putty where ever necessary.	3.00	Sqm	3.00
b	1.00	Sqm	Removing dry or oil bound distemper by scrapping sand papering and preparing surface smooth including necessary repairs to scratches by sandla/loi and all scaffolding (for colour changing only)	4.00	Sqm	4.00
152	1.00	Sqm	Distemping with oil bound washable distemper of approved brand and manufacture to give an even shade including all scaffolding:			
153			New work (two or more coats) over and including scrapping and priming coat with cement primer.	75.00	Sqm	75.00
a	1.00	Sqm	Old work (one or more coats) including scrapping surface and necessary repairs. Colour change.	15.00	Sqm	15.00
b	1.00	Sqm	Wall painting with plastic emulsion paint of approved brand and manufacture to give an even shade including all scaffolding:			
154			Two or more coats on new work including preparation of base with primer, putty, lippy etc complete in all respect.	80.00	Sqm	80.00
a	1.00	Sqm	Old work (One or more coats)	40.00	Sqm	40.00
b	1.00	Sqm	Applying priming coat :			
155			With ready mix pink or gray primer of approved brand and manufacture on wood work hard and soft wood.	29.00	Sqm	29.00
a	1.00	Sqm	With ready mixed red oxide zinc chromate primer of approved brand and manufacture on steel work (second coat)	12.00	Sqm	12.00
b	1.00	Sqm	Providing and applying white cement based putty over plastered surface to prepare the surface even and smooth complete			
156			New Plastered Surface (three or more coats)	84.00	Sqm	84.00
a	1.00	Sqm	Old Plastered Surface (two or more coats)	46.00	Sqm	46.00
b	1.00	Sqm	Lettering with black Japan paint of approved brand and manufacture.			
157	1.00	P. Letter Per cm. height	Finishing walls with Acrylic Smooth exterior paint of approved brand and required shade including all scaffolding. New work			
158	1.00	Sqm				

RajKaj Ref
12457806

Signature valid

Digitally signed by Rajendra Sin
Designation: Secretary
Date: 2024.12.06 12:52:32 IST
Reason: Approved

			or more coat applied @ 1.67 ltr/10 sqm over and including base coat of water proofing cement paint applied @ 2.20 kg/ 10 sqm).			
159			Finishing walls with textured exterior paint of required shade as per approved colour complete as per manufacturers specifications including primer coat and protecting coat	171.00	Sqm	171.00
a	1.00	Sqm	Roller Finish av. thickness 400 to 500 microns.	404.00	Sqm	404.00
b	1.00	Sqm	Trowel Finish av. thickness 1500 to 2000 microns.			
160			Painting exterior surface of Wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade with two or more coats including preparation of base with sand papering, primer, putty, etc complete in all respect including scaffolding and safety provision	123.00	Sqm	123.00
a	1.00	Sqm	New Work	50.00	Sqm	50.00
b	1.00	Sqm	Old Work			
161			Providing and applying superior quality wall painting with Velvet touch emulsion paint of approved brand and manufacture to give an even shade with putty and preparation of surface applying with the help of paint roller the work complete in all respect as per direction of Engineer-in-charge.	246.00	Sqm	246.00
a	1.00	Sqm	New Work Three or More coat	162.00	Sqm	162.00
b	1.00	Sqm	Old Work Analysis			
162			Providing and applying Melamine polish on teak wood work of approved brand and manufacture to give an even shade with two or more coats by compressor including sand papering, wood filler coat etc complete in all respect:	887.00	Sqm	887.00
a	1.00	Sqm	New Surface	606.00	Sqm	606.00
b	1.00	Sqm	Old Surface			
163	1.00	Sqm	Spray painting in approved shade and approved quality with Duco paint of required colour to give even shade with two or more coats by compressor including sand papering, NC putty filler coat etc complete in all respect as per design given by Engineer incharge on new work.	1859.00	Sqm	1859.00

Joinery Work

164	1.00	Sqm	Providing and fixing fully panelled /partly panelled double leaf shutters frame for windows and ventilators as per approved design and drawings with approved steel fittings as per Annexure 'A' and width of styles, bottom and top rails 75mm including intermediate rails 50mm wide, beading of 25mm x 15mm size on both faces : 35 mm thick Ivory coast wood grade I	2976.00	Sqm	2976.00
165	1.00	Sqm	Providing and fixing fully panelled /partly panelled double leaf shutters frame for windows and ventilators as per approved design and drawings with approved steel fittings as per Annexure 'A' and width of styles, bottom and top rails 75mm including intermediate rails 50mm wide, beading of 25mm x 15mm size on both faces : 30 mm thick Ivory coast wood grade I	2627.00	Sqm	2627.00
166			Providing and fixing wood panelling or panelling and glazing in panelled or panelled and glazed shutters for doors, windows and clerestory windows (Area of opening for panel inserts excluding portion inside grooves or rebates to be measured). Panelling for panelled and glazed shutter 25 mm to 40 mm thick			
i	1.00	Sqm	IS 710- 1976 marked 9 mm thick Teak BWR ply both side	1821.00	Sqm	1821.00
ii	1.00	Sqm	IS 710- 1976 marked 12 mm thick Teak ply BWR one side	1821.00	Sqm	1821.00
iii	1.00	Sqm	IS 710- 1976 marked 12 mm thick Teak ply BWR both side	2074.00	Sqm	2074.00
iv	1.00	Sqm	SS wire gauge 14 mesh x 24 gauge	927.00	Sqm	927.00
v	1.00	Sqm	5 mm float glass	1020.00	Sqm	1020.00
vi	1.00	Sqm	8 mm thick glass	1694.00	Sqm	1694.00
vii	1.00	Sqm	6 mm thick glass	128.00	Sqm	128.00
viii	1.00	Sqm	12 mm thick glass			
ix	1.00	Sqm	5 mm tinted glass			

RajKaj Ref
12457806

Signature valid

Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.26 10:52:32 IST
Reason: Approved

167	1.00	Sqm	Providing and fixing external grade board solid core single leaf flush door shutters ISI 2202-67 marked using Phenol formal dehyderesin in glue both sides with approved steel fittings complete as per annexure 'A' : 30 mm thick , Commercial Veneer both side	1841.00	Sqm	1841.00
168	1.00	Sqm	Extra for providing external lipping with 2nd class teak wood battens 6 mm minimum depth on all edges of shutters (over all area of door shutter to be measured) Over item no. 8.13.	141.00	Sqm	141.00
169	1.00	Sqm	Extra for providing other type of fittings as mention in annexure A (as approved by EI) : Stainless steel fittings	10.00%	Sqm	0.10
170	1.00	Sqm	Providing and fixing Nigeria / Ghana /Ivory Coast Teak wood grade-I mouldings and beadings in doors and windows size :-50x20 mm	127.00	Sqm	127.00
171	1.00	Each	Providing & Fixing drawer lock of approved make for drawers with screws complete as per approved by engineer in charge.	448.00	Each	448.00
172	1.00	Sqm	Providing and Fixing Cushion Vinyl/Fully flexible Vinyl Flooring confirming to I.S.-3462 Flooring of approved make with fibre base using rubber base adhesives including rolling with light wooden roller complete : 2.0 mm thick.	990.00	Sqm	990.00
173	1.00	Sqm	Renewing glass panes, with putty and nails wherever necessary: Float glass panes of thickness 4 mm	617.00	Sqm	617.00
174	1.00	Sqm	Renewing glass panes with wooden fillets wherever necessary : 4mm thick plain glass panes.	765.00	Sqm	765.00
175	1.00	Sqm	Renewing glass panes and refixing existing wooden fillets : 4mm thick plain glass panes.	636.00	Sqm	636.00
176	1.00	Sqm	Repair of existing steel glazed doors, windows and ventilator, MS sheet door, garge doors, compound wall gates etc. by welding drilling complete include. Cost of welding rods and hire charge of welding meachine and TP etc complete	332.00	Sqm	332.00
177	1.00	Sqm	Labour charges for repair to door / window without using any material such as applying randha (finishing) tightening of bolts & screw etc.	220.00	Sqm	220.00
178			Repair of door, window shutters including cost of material and labour for change of damaged :			
(a)			Style / rail of teak wood 30mm thick/ Aluminium Section	266.00	Rmt.	266.00
(i)	1.00	Rmt.	4"wide	367.00	Rmt.	367.00
(ii)	1.00	Rmt.	6" wide			
(b)			Panel by			
(i)	1.00	Sqm.	Shuttering Ply - 9mm thick (Commercial)	598.00	Sqm.	598.00
(ii)	1.00	Sqm.	Wire Gauge 14 mesh x 24 gauge	534.00	Sqm.	534.00
(iii)	1.00	Sqm.	Plain Glass Panes 4mm thick	431.00	Sqm.	431.00
(c)			Aldrop of mild Steel			
(i)	1.00	Each	12" long x12mm dia	147.00	Each	147.00
(ii)	1.00	Each	8" long x 10mm dia	106.00	Each	106.00
(d)			Stopper of Aluminium with			
(i)	1.00	Each	Single Rubber Gutka	33.00	Each	33.00
(ii)	1.00	Each	Double Rubber Gutka	47.00	Each	47.00
(e)	1.00	Each	Door Springs of mild Steel	160.00	Each	160.00
(f)			Steel Hinges			
(i)	1.00	Each	For Wooden Chowkhat 3" size.	24.00	Each	24.00
(ii)	1.00	Each	For Wooden Chowkhat 4" size	34.00	Each	34.00
(iii)	1.00	Each	For Stone Chowkhat ,4"size	29.00	Each	29.00
(g)	1.00	Each	Mild Steel Tower Bolt 6" long	39.00	Each	39.00
(h)	1.00	Each	Steel Locking Bolt	53.00	Each	53.00
(i)	1.00	Each	Steel Handle 6" size			

RajKaj Ref
12457806

Signature valid

Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.26 14:52:32 IST
Reason: Approved

Secretary
Rajasthan State Sports Council
Jaipur

RajKaj Ref
12457806

Signature valid

Digitally signed by Rajendra Singh
Designation: Secretary
Date: 2024.12.16 10:52:32 IST
Reason: Approved

