



राजस्थान राज्य क्रीडा परिषद

सवाई मानसिंह स्टेडियम, जनपथ, जयपुर

कार्यालय दूरभाष नं० 0141-2744283, फ़ैक्स नं० 0141-2740568, ईमेल आईडी-rsscjaipur@gmail.com

No. : F.8/T.C./Khelo India/2026/Kapren-Kota/Raj-Kaj

Date : (E-Signed)

निविदा सूचना संख्या 28/2026-27

राजस्थान राज्य क्रीडा परिषद, जयपुर की ओर से भारत सरकार की खेलों इंडिया योजनान्तर्गत कॉपरेन-कोटा में मल्टीपरपज इन्डोर हॉल निर्माण कार्य हेतु राज्य/केन्द्र सरकार के संगठनों/विभागों में पंजीकृत संवेदकों से ई-प्रोक्यूरमेंट प्रक्रिया हेतु ऑनलाइन निविदा आमंत्रित की जाती है।

निविदा से संबंधित अन्य आवश्यक विवरण वेबसाइट <http://sppp.rajasthan.gov.in>, <http://eproc.rajasthan.gov.in> व www.rssc.in पर देखी जा सकती है।

सचिव

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605



M e-Sign



RAJASTHAN STATE SPORTS COUNCIL

TENDER DOCUMENT FOR CONSTRUCTION OF MULTIPURPOSE INDOOR HALL AT KAPREN DIST. KOTA, RAJASTHAN.

NIT NO.	:	NIT No. 28/2026-27
ESTIMATED COST	:	Rs. 487.00 Lacs
EARNEST MONEY	:	Rs. 9,74,000/-
DATE OF SALE / DOWNLOADING	:	From Friday August 07, 2026 to Friday August 14, 2026 11:00 Hours
DATE OF RECEIPT (D.D. & DOCUMENTS)	:	From Friday August 07, 2026 to Friday August 14, 2026 13:00 Hours
DATE OF OPENING OF TENDER	:	Friday August 14, 2026 17:00 Hours
COMPLETION PERIOD	:	12 Months
COST OF TENDER	:	Rs. 5000/- in favour of Secretary, RSSC, Jaipur
PROCESSING FEES	:	Rs 2500/- in favour of MD, RISL, Jaipur
DLP Period	:	5 Years

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

Rajasthan State Sports Council. Jaipur

Important Dates of Bids

1. Completion Period	12 Months
2. Date of Issue of Notice Inviting Tender	Friday August 07, 2026
3. Period and Places of Sale/ Download of Bidding Documents -	From Friday August 07, 2026 to Friday August 14, 2026 11:00 Hours http://sppp.rajasthan.gov.in, www.rssc.in & http://eproc.rajasthan.gov.in
4. Deadline for uploading	From Friday August 07, 2026 to Friday August 14, 2026 11:00 Hours
5. Time and Date for Opening of Bids	Friday August 14, 2026 17:00 Hours
6. Place of Opening of Bids	Rajasthan State Sports Council, SMS Stadium, Jaipur-302005
7. Officer Inviting Bids	Secretary, Rajasthan State Sports Council. Jaipur. Address: SMS Stadium, Jaipur-302005
8. Earnest money to be deposited	As per NIT

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

Instructions and information to bidder regarding Fee, EMD etc.

District	Name of Work Package No.	Estimated Cost (Rs.)	Earnest Money	Time Allowed for completion	End date and time for downloading Tender	Time and date of opening of tender	Place of Sale of documents	Class of contractor.
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
Jaipur	CONSTRUCTION OF MULTIPURPOSE INDOOR HALL AT KAPREN DIST. KOTA, RAJASTHAN.	487.00 Laacs	Rs. 9,74,000/-	12 Months	Friday August 14, 2026 11:00 Hours	Friday August 14, 2026 17:00 Hours	http://spppp.rajasthan.gov.in , http://eproc.rajasthan.gov.in & www.rssc.in	B and Above category for Civil works

1. The Tender Fee and earnest money as mentioned above should be deposited in the appropriate form as per the tender documents in favour of **Secretary, Rajasthan State Sports Council, Jaipur** payable at **Jaipur** and **Processing Fees** payable at **MD, RISL, Jaipur** payable at Jaipur and must be uploaded scan copy of Registration of Firm, Demand Draft of Tender Cost, Processing Fee & Earnest Money on the site.
2. The tender can be viewed and downloaded from web site <http://spppp.rajasthan.gov.in>, <http://eproc.rajasthan.gov.in> & www.rssc.in.
3. The authorized tender documents are available for inspection in the office of **Rajasthan State Sports Council, SMS Stadium, Jaipur** from all working days.

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

**RajKaj Ref No.:
23881605**

M e-Sign

Annexure A: Compliance with the Code of Integrity and No Conflict of Interest

Any person participating in a procurement process shall-

- (a) Not offer any bribe, reward or gift or any material benefit either directly or indirectly in exchange for an unfair advantage in procurement process or to otherwise influence the procurement process;
- (b) Not misrepresent or omit that misleads or attempts to mislead so as to obtain a financial or other benefit or avoid an obligation;
- (c) Not indulge in any collusion, Bid rigging or anticompetitive behavior to impair the transparency, fairness and progress of the procurement process;
- (d) Not misuse any information shared between the procuring entity and the bidders with an intent to gain unfair advantage in the procurement process;
- (e) Not indulge in any coercion including impairing or harming or threatening to do the same, directly or indirectly, to any party or to its property to influence the procurement process;
- (f) Not obstruct any investigation or audit of a procurement process;
- (g) Disclose conflict of interest, if any; and
- (h) Disclose any previous transgressions with any entity in India or any other country during the last three years or any debarment by any other procuring entity.

Conflict of interest

The Bidder participating in a bidding process must not have a Conflict of Interest.

A Conflict of interest is considered to be a situation in which a party has interests that could improperly influence that party's performance of official duties or responsibilities, contractual obligations, or compliance with applicable laws and regulations.

(i) A bidder may be considered to be in conflict of interest with one or more parties in the bidding process if, including but not limited to:

- (a) Have controlling partners/shareholders in common; or
- (b) Receive or have received any direct or indirect subsidy from any of them; or
- (c) Have the same legal representative for purposes of the bid; or
- (d) have a relationship with each other, directly or through common third parties, that puts them in a position to have access to information about or influence on the bid of another bidder, or influence the decisions of the procuring Entity regarding the bidding process; or
- (e) The bidder participates in more than one bid in a bidding process. Participation by a bidder in more than one bid will result in the disqualification of all bids in which the bidder is involved. However, this does not limit the inclusion of the same subcontractor, not otherwise participating as a bidder, in more than one bid; or
- (f) the bidder or any of its affiliates participated as a consultant in the preparation of the design or technical specifications of the goods, Works or services that are the subject of the Bid; or
- (g) Bidder or any of its affiliates has been hired (or proposed to be hired) by the procuring entity as engineer-in-charge/consultant for the contract.

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

Annexure B: Declaration by the Bidder regarding Qualifications

Declaration by the Bidder

In relation to my/our Bid submitted tofor procurement ofin response to their Notice inviting Bids No.....Dated.....I/wehereby declare under Section 7 of Rajasthan Transparency in Public Procurement Act, 2012 that :

1. I/we possess the necessary professional, technical, financial and managerial resources and competence required by the Bidding Document issued by the Procuring Entry;
2. I/we have fulfilled my/our obligation to pay such of the taxes payable to the union and the state government or any local authority as specified in the Bidding Document.
3. I/we are not insolvent, in receivership, bankrupt or being wound up, not have my/our affairs administered by a court or a judicial officer, not have my/our business activities suspended and not the subject of legal proceedings for any of the foregoing reasons;
4. I/we do not have, and our directors and officers not have, been convicted of any criminal offence related to my/our professional conduct or the making of false statements or misrepresentations as to my/our qualifications to enter into a procurement contract within a period of three years preceding the commencement of this procurement process, or not have been otherwise disqualified pursuant to debarment proceedings;
5. I/we do not have a conflict of interest as specified in the Act, Rules and the Bidding Document, which materially affects fair competition;

Date:
Place:

Signature of bidder
Name:
Designation:
Address:

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

**RajKaj Ref No.:
23881605**

M e-Sign

Annexure C: Grievance Redressed during Procurement Process

The designation and address of the First Appellate Authority is **Joint Secretary**, Youth Affairs & Sports Department Govt. of Rajasthan. The designation and address of the Second Appellate Authority is **Secretary**, Youth Affairs & Sports Department Govt. of Rajasthan, Jaipur.

(1) Filing an appeal:-

if any bidder or prospective bidder is aggrieved that any decision, action or omission of the procuring entity is in contravention to the provisions of the Act or the rules or the guidelines issued there under, he may file an appeal to First Appellate authority, as specified in the Bidding document within a period of ten days from the date of such decision or action, omission, as the case may be, clearly giving the specific ground or grounds on which he feels aggrieved:

Provided that after the declaration of a bidder as successful the appeal may be filed only by a bidder who has participated in procurement proceedings:

Provided further that in case a procuring entity evaluates the technical bids before the opening of the financial bids, an appeal related to the matter of financial bids may be filed only by a bidder whose technical bid is found to be acceptable.

(2) The officer to whom an appeal is filed under Para (1) shall deal with the appeal as expeditiously as possible and shall endeavor to dispose it of within thirty days from the date of the appeal.

(3) If the officer designated under Para (1) fails to dispose of the appeal filed within the period specified in Para (2), or if the bidder or prospective bidder or the procuring entity is aggrieved by the order passed by the first appellate authority, the bidder or prospective bidder or the procuring entity, as the case may be, may file a second appeal to second appellate authority specified in the bidding document in this behalf within fifteen days from the expiry of the period specified in Para (2) or of the date of receipt of the order passed by the first appellate authority, as the case may be.

(4) Appeals not to lie in certain cases:-

No appeal shall lie against any decision of the procuring entity relating to the following matters, namely:-

- (a) Determination of need of procurement
- (b) Provisions limiting participation of bidders in the bid process
- (c) The decision of whether or not to enter into negotiations
- (d) Cancellation of a procurement process
- (e) Applicability of the provisions of confidentiality

(5) Form of Appeals:-

- (a) An appeal under Para (1) or (3) above shall be in the annexed form along with as many copies as there are respondents in the appeal.
- (b) Every appeal shall be accompanied by an order appealed against, if any, Affidavit verifying the facts stated in the appeal and proof of payment of fee,
- (c) Every appeal may be presented to first appellate authority or second Appellate authority, as the case may be, in person or through registered post Or authorized representative.

(6) Fee for filing Appeal:-

- (a) Fee for first appeal shall be rupees two thousand five hundred and for second appeal shall be rupees ten thousand, which shall be non-refundable.
- (b) The fee shall be paid in the form of bank demand draft or banker's cheque of a scheduled bank in India payable in the name of appellate authority concerned.

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 11:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

(7) Procedure for disposal of Appeal:-

- (a) The first appellate authority or second appellate authority as the case may be, upon filing of appeal, shall issue notice accompanied by copy of appeal, affidavit and documents, if any, to the respondents and fix date of hearing
- (b) On the date fixed for hearing, the first appellate authority or second appellate authority, as the case may be shall-
 - (i) Hear all the parties to appeal present before him; and
 - (ii) Peruse or inspect documents, relevant records or copies thereof relating to the matter.
- (c) After hearing the parties, perusal or inspection of documents and relevant records or copies thereof relating to the matter, the appellate authority concerned shall pass an order in writing and provide the copy of order to the parties to appeal free of cost.
- (d) The order passed under sub-clause (c) above shall also be placed on the state public procurement portal.

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

**RajKaj Ref No.:
23881605**

M e-Sign

Annexure D: Additional Conditions of Contract

1. Correction of arithmetical errors

Provided that a Financial Bid is substantially responsive, the Procuring Entity will correct arithmetical errors during evaluation of Financial Bids on the following basis:

- i. If there is a discrepancy between the unit price and the total price that is obtained by multiplying the unit price and quantity, the unit price shall prevail and the total price shall be corrected, unless in the opinion of the Procuring Entity there is an obvious misplacement of the decimal point in the unit price, in which case the total price as quoted shall govern and the unit price shall be corrected;
- ii. If there is an error in a total corresponding to the addition or subtraction of subtotals, the subtotals shall prevail and the total shall be corrected; and
- iii. If there is a discrepancy between words and figures, the amount in words shall prevail, unless the amount expressed in words is related to an arithmetic error, in which case the amount in figures shall prevail subject to (i) and (ii) above.

If the Bidder that submitted the lowest evaluated Bid does not accept the correction of errors, its Bid shall be disqualified and its Bid Security shall be forfeited or its Bid Securing Declaration shall be executed.

2. Procuring Entity's Right to Vary Quantities

- (i) At the time of award of contract, the quantity of Goods, Works or services originally specified in the Bidding Document may be increased or decreased by a specified percentage, but such increase or decrease shall not exceed Five percent, of the quantity specified in the Bidding Document. It shall be without any change in the unit prices or other terms and conditions of the Bid and the conditions of contract.
- (ii) If the Procuring Entity does not procure any subject matter of procurement or procures less than the quantity specified in the Bidding Document due to change in circumstances, the Bidder shall not be entitled for any claim or compensation except otherwise provided in the Conditions of Contract.
- (iii) In case of procurement of Goods or services, additional quantity may be procured by placing a repeat order on the rates and conditions of the original order. However, the additional quantity shall not be more than 50% of the value of Goods of the original contract and shall be within one month from the date of expiry of last supply. If the supplier fails to do so, the Procuring Entity shall be free to arrange for the balance supply by limited Bidding or otherwise and the extra cost incurred shall be recovered from the supplier.

3. Dividing quantities among more than one Bidder at the time of award (In case of procurement of Goods)

As a general rule all the quantities of the subject matter of procurement shall be procured from the Bidder, whose Bid is accepted. However, when it is considered that the quantity of the subject matter of procurement to be procured is very large and it may not be in the capacity of the Bidder, whose Bid is accepted, to deliver the entire quantity or when it is considered that the subject matter of procurement to be procured is of critical and vital nature, in such cases, the quantity may be divided between the Bidder, whose Bid is accepted and the second lowest Bidder or even more Bidders in that order, in a fair, transparent and equitable manner at the rates of the Bidder, whose Bid is accepted.

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 11:37:31 IST
Reason: Approved

**RajKaj Ref No.:
23881605**

M e-Sign

राजस्थान राज्य क्रीडा परिषद

सवाई मानसिंह स्टेडियम, जनपथ, जयपुर

कार्यालय दूरभाष नं० 0141-2744283, फ़ैक्स नं० 0141-2740568, ईमेल आईडी—rsscjaipur@gmail.com

बोली की शर्तें

विशेष टिप्पणी :- बोलीदाताओं को इन शर्तों को सावधानी पूर्वक पढ़ना चाहिए तथा अपनी ई-बोलियां भेजते समय इनकी पूर्ण रूपेण पालना करनी चाहिए।

1. तकनीकी प्रस्तावों में सफल बोलीदाताओं के ही वित्तीय प्रस्ताव खोले जावेंगे जो निविदादाता तकनीकी बिड में सफल नहीं पाये गये उनकी वित्तीय बोली नहीं खोली जायेगी।
2. कोई भी फर्म/संवेदक यदि जी.एस.टी. अधिनियम के अन्तर्गत पंजीकृत नहीं है तो वह बोली नहीं देगा। इनके अभाव में बोलियों पर विचार नहीं किया जायेगा। जी. एस. टी. देयता प्रमाण पत्र मार्च, 2026 का संलग्न करना आवश्यक है।
3. दरें जी.एस.टी. तथा केन्द्र व राज्य सरकार द्वारा देय समस्त करों सहित देनी होगी।
4. बोली ऑन-लाईन प्रस्तुत की जावेगी एवं निर्दिष्ट कॉलमों में प्रविष्टि की जावेगी।
5. दरें गन्तव्य स्थान तक एफ.ओ.आर. सवाई मानसिंह स्टेडियम जयपुर के आधार पर होगीं अर्थात् परिवहन संबंधी कोई राशि परिषद द्वारा पृथक से देय नहीं होगी।
6. बोलियां उपापन अधिनियम/पारदर्शिता अधिनियम के तत्संबंधी प्रावधानों (धारा-28 आदि) के अध्वधीन रहते हुये उनके खोले जाने की दिनांक से एक वर्ष की अवधि के लिए विधि मान्य होंगी।
7. बोलीदाता अपनी संविदा या उसके किसी भाग को किसी अन्य एजेन्सी के लिए नहीं सौंपेगा या उपभाडे पर नहीं देगा।
8. बोलीदाता का उसके प्रतिनिधि की ओर से प्रत्यक्ष अथवा अप्रत्यक्ष रूप से अपना पक्ष समर्थन करना एक प्रकार की अनर्हता होगी। हित विरोधी धारा 80 होगी।
9. विहित समय एवं तारीख के पश्चात् जो भी बोलियां प्राप्त होंगी उन्हें किसी स्थिति में स्वीकार नहीं किया जावेगा।
10. यदि बोलीदाता ऐसी कोई शर्त आरोपित करता है जो उसमें वर्णित शर्तों के अतिरिक्त है या उनके विरोध में है तो उसकी बोली को संक्षिप्त रूप में कार्यवाही कर रद्द कर दिया जावेगा।
11. तकनीकी बोली के साथ बोलीदाता को निम्न दस्तावेज संलग्न करने अनिवार्य होंगे (जिसके आधार पर तकनीकी बिड का मूल्यांकन किया जायेगा) :-
 - i. बोली में अंकित पते के प्रमाण हेतु पानी/बिजली/टेलीफोन/मोबाईल के बिल, पेन कार्ड, पासपोर्ट, आधार कार्ड अथवा ड्राईविंग लाईसेन्स में से कोई एक की प्रमाणित छाया प्रतियां।
 - i. बोलीदाता/फर्म का विगत 5 वित्तीय वर्षों (2021-22, 2022-23, 2023-24, 2024-25 एवं 2025-26) में औसत वार्षिक टर्न ओवर 487.00 लाख से कम नहीं होना चाहिये। इस हेतु बोलीदाता को उक्त वर्षों का सीए से प्रमाणित प्रमाण पत्र की प्रति मय यूडीआई नम्बर सहित संलग्न करनी होगी।

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 11:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

- ii. गत 5 वर्षों (2021-22 से 2025-26) में राजकीय विभागों में परियोजना लागत का 75 प्रतिशत रुपये 365.25 लाख अथवा अधिक की लागत के कम से कम दो या 50 प्रतिशत रुपये 243.50 लाख अथवा अधिक की लागत के कम से कम तीन भवन निर्माण कार्य (Similar Work) का होना अनुभव होना आवश्यक है। इसके प्रमाणीकरण हेतु कार्यादेश एवं कार्य के सन्तोषजनक होने का प्रमाण पत्र आदि आवश्यक दस्तावेज संलग्न करने होंगे।
- iii. बोलीदाता को माल एवं सेवाकर (GST) के रजिस्ट्रेशन की प्रति संलग्न करनी होगी।
- iv. अमानत राशि एवं बोली प्रपत्र शुल्क का डी.डी. संलग्न करना होगा।

12. बयाना राशि :-

- (क) बोली से पूर्व (2%) नियमानुसार बयाना राशि ऑफ-लाईन प्रस्तुत की जायेगी। इसके बिना बोलीओं पर विचार नहीं किया जायेगा। यह राशि सचिव, राजस्थान राज्य क्रीड़ा परिषद, जयपुर के पक्ष में बैंक ड्राफ्ट/बैंकर्स चेक में से किसी रूप में जमा करायी जा सकती है।
- (ख) असफल बोलीदाता की बयाना राशि बोली को अंतिम रूप से स्वीकार करने के बाद यथा संभव शीघ्र लौटा दी जावेगी।
- (ग) अनुमोदन की प्रतीक्षा करने वाली या रद्द की गई या संविदाओं के पूर्ण हो जाने के कारण परिषद कार्यालय के पास जमा बयानाराशि/प्रतिभूति निक्षेप को नवीन निविदा के लिए बयाना राशि/प्रतिभूति राशि के प्रति समायोजित नहीं किया जायेगा।

13. बयाना राशि का समपहरण:- बयाना राशि को निम्नलिखित मामलों में समपहरत कर लिया जायेगा:-

- (क) जब बोलीदाता बोली खोलने के बाद किन्तु बोली को स्वीकार करने के पूर्व प्रस्ताव को वापस लेता है या उसमें उपान्तरण करता है।
- (ख) जब बोलीदाता विनिर्णित समय के भीतर विहित करार को निष्पादित नहीं करता है।
- (ग) जब बोलीदाता प्रदायगी के लिए आदेश देने के बाद प्रतिभूति राशि जमा नहीं कराता हो।
- (घ) जब वह निर्धारित समय के अन्तर्गत आदेशों के अनुसार कार्य करने में असफल रहता है अथवा संतोषजनक सेवाएं देने में असमर्थ रहता है।

14. करार एवं प्रतिभूति निक्षेप :-

- (क) सफल बोलीदाता को आदेश दिनांक से 7 दिन की अवधि के भीतर नियमानुसार मूल्य के नॉन ज्यूडिशियन स्टॉम्प पेपर पर (जिसका व्यय स्वयं बोलीदाता द्वारा वहन किया जावेगा) एक करार-पत्र निष्पादित करना होगा तथा प्रावधित मूल्य जिसके लिए बोली स्वीकार की गई है।
- (ख) बोली के समय जमा कराई गई बयाना राशि को प्रतिभूति की राशि के लिए समायोजित किया जायेगा।
- (ग) बयाना/प्रतिभूति राशि पर परिषद द्वारा कोई ब्याज का भुगतान नहीं किया जायेगा।
- (घ) प्रतिभूति राशि के रूप में नकद रसीद पत्र/शिड्यूल बैंक का ड्राफ्ट/बैंकर्स चेक मान्य होंगे।

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 11:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

15. **प्रतिभूति राशि का समपहरण** :- प्रतिभूति की राशि को पूर्ण अथवा आंशिक रूप से निम्नलिखित मामलों में समपहरत किया जायेगा:-
- (क) जब संविदा की किसी शर्त/अथवा शर्तों का उल्लंघन किया गया हो।
 - (ख) जब बोलीदाता सम्पूर्ण कार्य संतोषजनक ढंग से करने में असफल रहा हो।
 - (ग) प्रतिभूति निक्षेप को समपहरत करने के मामले में युक्तियुक्त नोटिस दिया जावेगा इस सम्बन्ध में परिषद के अधिकारी का निर्णय अन्तिम होगा।
 - (घ) कार्य में असफल रहने पर परिषद द्वारा वैकल्पिक व्यवस्था किये जाने पर उसमें जो भी व्यय होगा बोलीदाता से उसकी प्रतिभूति राशि में से अथवा उसको देय बिल की राशि के भुगतान में से की जायेगी। यदि वसूली करना सम्भव न हो तो राजस्थान पी.डी.आर.एक्ट या प्रवृत्त अन्य किसी कानून के अन्तर्गत कार्यवाही की जावेगी।
16. करार पत्र को पूर्ण करने एवं उस पर स्टाम्प लगाने का व्यय बोलीदाता द्वारा वहन किया जायेगा तथा परिषद को उस करार पत्र की निष्पादित स्टाम्प शुदा प्रति पडत निःशुल्क प्रस्तुत की जायेगी।
17. परिषद के प्राधिकृत अधिकारी या उसका विधिवत् प्राधिकृत प्रतिनिधि सभी युक्तियुक्त उचित समयों पर ठेकेदार के परिसर में जायेगा तथा वह विनिर्माण की प्रक्रिया के दौरान या उसके बाद जैसे भी हो किसी भी समय सामग्री का निरीक्षण एवं जांच करने की शक्ति रखेगा।
18. परीक्षण प्रभार परिषद द्वारा वहन किये जायेंगे। यदि बोलीदाता अत्यावश्यक तत्काल परीक्षण कराना चाहता है या यदि परिणामों से यह ज्ञात होता है कि प्रदाय किया गया सामान विहित स्तरों या विनिर्देशों के अनुसार नहीं है तो परीक्षण प्रभार बोलीदाता द्वारा वहन किये जायेंगे।
19. अनुमोदित कार्य के लिए यह समझा जाएगा कि उसने कार्य किये जाने वाले विनिर्देशों की सावधानीपूर्वक जांच कर ली है यदि उसे इन शर्तों, विनिर्देशों, रेखाचित्रों आदि के किसी भाग के आशय के बारे में कोई सन्देह हो तो वह संविदा पर हस्ताक्षर करने से पूर्व परिषद से स्पष्टीकरण प्राप्त करेगा।
20. सफल बोलीदाता को कार्य आदेश जारी तिथि के 10 दिवस के अन्दर कार्य प्रारम्भ करना होगा।
21. यदि निविदा सूचना में दर्शित मात्रा से अधिक के लिए आदेश दिया जाता है, तो निविदादाता अपेक्षित कार्य करने के लिए बाध्य होगा। पुनः आदेश भी निविदा में दी गयी शर्तों पर दिए जा सकेंगे परन्तु शर्त यह है, कि ऐसे पुनःआदेश मूल रूप से खरीदी गयी मात्रा की 50 प्रतिशत तक के अतिरिक्त प्रदाय के लिए ही होंगे।
22. **गारन्टी** :- गारन्टी नियमानुसार होगी।
23. **परिसमापित नुकसानी** :-
- (1) परिसमापित नुकसानी के साथ कार्य अवधि में वृद्धि करने के मामले में, वसूली राजस्थान लोक उपापन पारदर्शिता अधिनियम, 2012 एवं राजस्थान लोक उपापन पारदर्शिता नियम 2013 के प्रावधान अनुसार होगी।
 - (2) यदि प्रदायकर्ता किन्हीं बाधाओं के कारण संविदान्तर्गत कार्य का प्रदाय पूरा करने के लिए समय में वृद्धि कराना चाहता है, तो वह लिखित में परिषद को आवेदन करेगा। किन्तु वह उसके लिए निवेदन बाधा के घटित होने पर तुरन्त उसी समय करेगा न कि प्रदाय पूर्ण होने की निर्धारित तारीख के बाद करेगा।

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 11:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

(3) यदि कार्य प्रदाय करने में उत्पन्न हुई बाधा बोलीदाता के नियन्त्रण से परे कारणों से हुई हो तो कार्य की अवधि में वृद्धि परिसमापित नुकसानी सहित या रहित की जा सकेगी।

24. **वसूली** :-परिसमापित नुकसानी, कम प्रदाय, टूट-फूट, रद्द की गई वस्तुओं के लिए वसूली साधारण रूप से बिल में से की जाएगी। संवेदक कम प्रदाय, टूट-फूट, रद्द किए गए कार्यों की सीमा तक राशि को भी रोका जा सकेगा तथा यदि सेवा सन्तोषजनक ढंग से उनको कार्य करता है तो परिसमापित नुकसानी के साथ वसूली उसे देय राशि एवं विभाग के पास उपलब्ध प्रतिभूति निक्षेप से की जाएगी। यदि वसूली करना सम्भव न हो तो राजस्थान पी डी आर एक्ट या प्रवृत्त अन्य कानून के अन्तर्गत कार्रवाई की जाएगी।

25. भुगतान :-

(क) बोलीदाता द्वारा क्रेता अधिकारी को उचित प्रारूप में लोक उपापन नियमों के अनुसार बिल प्रस्तुत करने पर भुगतान किया जायेगा। सभी प्रेषण प्रभार बोलीदाता द्वारा वहन किये जायेंगे। किसी भी सूरत में अग्रिम भुगतान नहीं किया जायेगा।

(ख) विवादास्पद मदों में राशि का 10 प्रतिशत से 25 प्रतिशत तक को रोका जायेगा तथा उस विवाद का निपटारा हो जाने पर उसका भुगतान कर दिया जायेगा।

(ग) उन मामलों में, जिनमें परीक्षण करने की जरूरत है, भुगतान तभी किया जायेगा जब उनका परीक्षण कर लिया जाये तथा प्राप्त हुए परीक्षण परिणाम विहित निर्देशों के अनुरूप हों।

26. यदि कार्य की तात्कालिक आवश्यकता के कारण पूर्ण या आंशिक रूप में उन कार्यों को बदलना साध्य नहीं समझा जाए तो राजस्थान राज्य क्रीडा परिषद द्वारा बोलीदाता को सुनवाई किये जाने का एक उचित अवसर देकर, ऐसे कारणों से जो अभिलिखित किये जायेंगे, अनुमोदित दरों में से उपयुक्त राशि की कटौती करेगा। इस प्रकार की गई कटौती अन्तिम होगी।

27. निविदादाता करार को निष्पादित करते समय निम्नलिखित दस्तावेज प्रस्तुत करेगा :-

(i) यदि भागीदारी फर्म हो तो "पार्टनरशिप डीड" की अनुप्रमाणित प्रति।

(ii) यदि भागीदारी फर्म रजिस्ट्रार ऑन फर्म्स के पास पंजीकृत हो तो पंजीयन संख्या एवं उसका वर्ष।

(iii) एक मात्र स्वामित्व के मामले में आवास एवं कार्यालय का पता, टेलीफोन नम्बर।

(iv) कम्पनी के मामले में कम्पनी के रजिस्ट्रार के द्वारा जारी किया गया प्रमाण-पत्र।

28. संविदा के निर्वचन, आशय या संविदा की शर्तों के उल्लंघन के सम्बन्ध में या अन्य किसी भी प्रकार का विवाद होने पर परिषद का निर्णय अन्तिम होगा।

29. समस्त विधिक कार्यवाहियां यदि संस्थित किया जाना आवश्यक हो तो जयपुर स्थित न्यायालय में ही की जाएगी। अन्यत्र नहीं की जाएगी।

30. बोलीदाता द्वारा अपलोड किये जाने वाले दस्तावेजों पर नम्बरिंग होनी चाही एवं चैक लिस्ट भर कर प्रस्तुत करनी होगी।

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 11:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

31. परियोजना में उपयोग में लिये जाने वाले आईटमों की दरें सानिवि की भवन बीएसआर-2022 विद्युत बीएसआर-2025 एवं सडक बीएसआर-2026 पर आधारित है। सभी दरों में किसी प्रकार की त्रुटि उक्त बीएसआर दरों से संशोधित मानी जावेगी।
32. सचिव, राजस्थान राज्य क्रीडा परिषद, जयपुर को बिना कारण बताये किसी भी बोली को स्वीकार/अस्वीकार करने का अधिकार होगा।
33. जी.एफ. एण्ड ए.आर., राजस्थान लोक उपापन पारदर्शिता अधिनियम, 2012 एवं राजस्थान लोक उपापन पारदर्शिता नियम 2013 के प्रावधान लागू होंगे।
- 34. Special Conditions of Contract:**
1. Joint ventures and consortium are not accepted.
 2. The Engineer-in-Charge / Rajasthan State Sports Council shall have the full and exclusive right to require testing of any material, at any stage and prior to final acceptance, in laboratories of their choice, including approved laboratories. The bidder/contractor shall, at his own cost, make all necessary arrangements for such testing (except those specified elsewhere in the tender documents) and shall bear all expenses towards sampling, testing, packing, transportation, loading, unloading and all incidental charges whatsoever. Any material found not conforming to the prescribed specifications, standards or quality requirements shall be rejected and shall not be accepted for use in the work.
 3. Contractor Must Established quality control lab at site.
 4. In case any material/work is found substandard the same shall be rejected by the Engineer-in Charge and the same shall be removed from the site of work within 48 hours, failing which the same shall be got removed by the Engineer-in-Charge at the risk & cost of the Contractor without giving any further notice and time.
 5. The Bidder shall ensure quality control measures on different aspects of construction including materials, workmanship and correct construction methodologies to be adopted.
 6. The Malba/Garbage generated at site due to construction activities shall be removed from the site immediately & shall be disposed off by the contractor to the approved dumping site from local bodies shall be a sole responsibility of contractor.
 7. The contractor shall make his own arrangement to get permission with respect to trucks from the Traffic Police.
 8. The Bidder in its name should have an authorisation certificate from the manufacturer of the proposed product to bid for this specific work, without which their bids shall stand disqualified.
 9. The bidder should be not present time blacklisted or debarred by any Central Government department, State Government department, Public Sector undertaking in India.
 10. The contractor must provide vehicle own cost for inspection of project site as a when required by Engineer-In-Charge.
 11. Contractor must provide own cost Supervisor (Maximum pay Rs. 16500) advised by RSSC Engineer In-Charge. No Additional payment done by RSSC.

**बोलीदाता के हस्ताक्षर
(मय नाम पता एवं मोहर)**

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

**RajKaj Ref No.:
23881605**

M e-Sign

घोषणा

मैंने/हमने राजस्थान राज्य क्रीडा परिषद, जयपुर की ओर से भारत सरकार की खेलों इंडिया योजनान्तर्गत कॉपरेन-कोटा में मल्टीपरपज इन्डोर हॉल निर्माण कार्य हेतु (मय सामग्री) की बोली के नियम एवं शर्तों को भली-भाँति पढ़ व समझ लिया है। मुझे/हमारी फर्म को किसी भी विभाग द्वारा ब्लैक-लिस्ट नहीं किया गया है। इन शर्तों एवं नियमों के अधीन मैं/हम उक्त निर्माण कार्य करने हेतु सहमत एवं वचनबद्ध हूँ/हैं। यदि मेरे/हमारे द्वारा की किसी बोली की शर्तों, नियमों अथवा आदेशों का उल्लंघन किया जावेगा तो सक्षम अधिकारी द्वारा मेरे/हमारे विरुद्ध बोली के नियम/शर्तों के उल्लंघन की कार्यवाही करने के लिए अधिकृत होगा। इस सम्बन्ध में मुझे/हमें सक्षम/अधिकृत अधिकारी द्वारा लिया गया निर्णय मान्य होगा तथा इसमें मुझे/हमको कोई आपत्ति/हस्तक्षेप नहीं है।

हस्ताक्षर बोलीदाता.....

नाम/पता

टेलीफोन नं.

दिनांक

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

General Instructions for Filling of Bid

The complete bidding document has been published on the website www.rssc.in, <http://sppp.raj.nic.in>, <http://eproc.raj.gov.in>, for the purpose of downloading.

1. Bidders who wish to participate in this bidding process must register on www.rssc.in & <http://sppp.raj.nic.in>,
2. To participate in online bidding process, Bidders must procure a Digital Signature Certificate (Type III) as per Information Technology Act-2000 using which they can digitally sign their electronic bids. Bidders can procure the same from any CCA approved certifying agency, i.e. TCS, safe crypt, Node etc. Bidders who already have a valid Digital Signature Certificate (DSC) need not procure a new DSC.
3. Bidder (authorized signatory) shall submit their offer on-line in electronic formats both for Technical and financial proposal. However, DD for Tender Fees, EMD payable in favor of SECRETARY RAJASTHAN STATE SPORTS COUNCIL, JAIPUR, payable at Jaipur and Processing Fees payable in favor of Managing Director, RAJCOMP Info Services Limited, payable at JAIPUR. **Tender fee, EMD and processing fee DD should be submitted physically at the office of RAJASTHAN STATE SPORTS COUNCIL, JAIPUR, and Scanned copy of same should also be uploaded along with the technical bid.**
4. RAJASTHAN STATE SPORTS COUNCIL, JAIPUR will not be responsible for delay in online submission due to any reason. For this, bidders are requested to upload the complete bid well advance in time so as to avoid Last hours issues like slow speed; choking of web site due to heavy load or any other unforeseen problems.
5. Bidders are also advised to refer “Bidders Manual Kit” available at e-Proc website for further details about the e-tendering process.
6. No contractual obligation, whatsoever shall arise from the bidding process unless and until a formal contract is signed and executed between the tendering authority and the successful Bidder.

SECRETARY

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

UNDERTAKING BY THE BIDDER

This is to certify that I/we before signing this tender have read and fully understood all the terms and conditions contained herein and undertake myself/ourselves to abide by them. I/We have signed all the pages in acceptance of the terms and conditions.

I/We also undertake that I/We will not adopt any malpractices at any stage of bidding/execution.

Signature of the Bidder with Seal

Name:

Designation:

Address:

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

**RajKaj Ref No.:
23881605**

M e-Sign

BIDDER'S AUTHORIZATION CERTIFICATE {to be filled by the bidder}

To,
{Tendering Authority},

_____,

I/
We.....{Name/Designatio
n} hereby declare/ certify that

..... {Name/ Designation} is hereby authorized to sign
relevant documents on behalf of the company/ firm in dealing with Tender with
RAJASTHAN STATE SPORTS COUNCIL, JAIPUR.

He/ She is also authorized to attend meetings & submit technical & commercial
information/ clarifications as may be required by you in the course of processing the Bid.
For the purpose of validation, his/ her verified signatures are as under.

Thanking you,

Name of the Bidder: -
Authorized Signatory: -
Seal of the Organization: -
Date:
Place:

Verified Signature:

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

CHECKLIST OF DOCUMENTS SUBMITTED

S. No.	Documents to be submitted	Submitted	Not Submitted	Page No.
1.	Scanned Copies of tender document fee, EMD and processing fees			
2.	Copy of Registration of firms.			
3.	Copy of GST Registration			
4.	Copy of PAN Card			
5.	Proof of Work order and Satisfactory Completion (Similar Work) of work should be as per tender document condition no. 11 (iii) in financial Year 2021-22 to 2025-26.			
6.	Certificate from Chartered Accountant having UDIN for the proof of average annual Turnover that must be equal/more than the cost of work (bid cost) in the last Five Financial Years from 2021-22 to 2025-26			
7.	Annexure A to D duly signed in context to RTPP Rules-2013.			
8.	Authorization certificate If the tender is signed other than owners			
9.	Copy of GST paid certificate filed by March, 2026 Financial Year 2025-26 in GSTR-3B Performa			
10.	Tender document and Technical Bid and undertaking all three duly signed			
11.	Any other Document			

Note: -

1. Work means the work executed under Public Sector/Autonomous Bodies/ Development Authority/Municipal Corporation of Central/State Government.
2. For the purpose of evaluating Building Work (similar work) experience considered.
3. The contractor should ensure that the Registration should be latest or updated.

Signature of Bidder Seal of Establishment
Full Name of Bidder with address and
date

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

PART-B (FINANCIAL BID)**Bill of Quantities**

NAME OF WORK :- CONSTRUCTION OF MULTIPURPOSE INDOOR HALL AT
KAPREN DIST. KOTA, RAJASTHAN

S. No.	Quantity	Particular	Rate		Amount
1	800.00	Supplying and Installation of synthetic Indoor Sports Flooring system PAVISINT SL 75 of 12mm thick composed of spormat high quality recycled rubber granules and polyurethane elastomers of thickness 10mm, tensile strength DIN 53571: 0.6-1 mPa coated with PU pore sealer and self leveling wear coat and top coat with 2 mm Polyurethane system , Approved by BWF, FIBA / AENA category 3 With specifications of (i) Force Reduction (EN 14808): > 25% ; (ii) Standard Deformation :>0.5mm ; (iii) Rolling load : 1500N; (iv) Ball Bounce : 100 % . (v) Impact Resistance: 18Nm (Total thickness 12mm +2mm)		Sqm	

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

Schedule "G"

S. No.	Quantity	Praticular	Rate		Amount
1	3300.00	Clearing jungle including uprooting of rank vegetation, grass, brush wood, trees and saplings of girth upto 30 cm measured at a height of 1 m above ground level and removal of rubbish upto a distance of 50 m outside the periphery of the area cleared.	5.00	Sqm	16500.00
2	3300.00	Surface dressing of the ground including removing vegetation and inequalities not exceeding 15cm deep and disposal of rubbish lead up to 50 Mtr. and lift up to 1.5 Mtr. : All kinds of soil	9.00	Sqm	29700.00
3	2028.00	Earth work in excavation by mechanical means (Hydraulic excavator)/ manual means over areas (exceeding 30cm in depth. 1.5m in width as well as 10 sqm on plan) including disposal of excavated earth, lead upto 50m and lift upto 1.5 m , disposed earth to be levelled and neatly dressed: All kinds of soil	175.00	Cum.	354900.00
4	359.00	Earth work in excavation by mechanical means (Hydraulic Excavator)/ manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan) including dressing of sides and ramming of bottoms, lift upto 1.5 m, including taking out the excavated soil and depositing and refilling of jhiri with watering & ramming and disposal of surplus excavated soil as directed with in a lead of 50 meter. All kinds of soils	178.00	Cum.	63902.00
5	2028.00	CARRIAGEOFMATERIALS Earth,Sand ,line morrum,manure or sludge sludge etc. upto 10 km	165.00	Cum.	334620.00
6	448.00	Supplying and Filling in plinth with river sand under floors including watering ramming consolidating and dressing complete including cost of sand	1024.00	Cum.	458752.00
7	80.00	Supplying chemical emulsion in sealed containers including delivery as specified. Chlorpyriphos/Lindane emulsifiable concentrate of 20%	243.00	Ltr.	19440.00
8	2292.00	Diluting and injection Chloropyrifos Emulsifiable concentrate 20% with 1% concentration for PRE-CONSTRUCTIONAL Anti termite treatment as per IS 6313 part III as amended from time to time and creating a continuous chemical barrier under and around the column pits, wall trenches, basement excavation, top surface of plinth filling, junction	47.00	Sqm	107724.00

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

		of wall and floor along the external perimeter of building expansion joints, over the top surface of consolidated earth of which aproch is to be laid surrounding of pipes and conduits etc. complete as per specification (Plinth floor area only shall be measured for payment and excluding the cost of chemical emulsion) .			
9	480.00	Providing and laying in position cement concrete including curing, compaction etc. complete in specified grade excluding the cost of centering and shuttering - All work up to plinth level. 1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size).	3302.00	Cum	1584960.00
10	429.00	Random Rubble stone masonry for with hard stone in foundation and plinth in Cement Sand mortar above 30 CM thick wall in:Cement Mortar 1:6 (1-Cement : 6-Sand).	2838.00	Cum.	1217502.00
11	498.00	Providing and laying in position specified grade of cement concrete for all RCC structural elements upto plinth level including curing, compaction, finishing with rendering in cement sand mortar 1:3 (1 cement: 3 coarse sand) and making good the joints and cost of plastizers(if required) excluding the cost of centering, shuttering and reinforcement. M20 grade Nominal Mix / Design Mix	4934.00	Cum	2457132.00
12	1043.00	Centering and shuttering with plywood or steel sheets including strutting, propping, bracing both ways and removal of formwork for foundations in basements rafts, footings, strap beams, bases of columns , etc. up to plinth level.	157.00	Sqm.	163751.00
13	490.00	Random rubble dry stone Kharanja under floor.	932.00	Cum.	456680.00
14	117.00	Providing and laying in position cement concrete including curing, compaction etc. complete in specified grade excluding the cost of centering and shuttering - All work up to plinth level. M10 grade Nominal Mix 1: 3: 6 (1 cement : 3 coarse sand : 6 graded stone aggregate 20mm nominal size).	3847.00	Cum	450099.00
15	125.00	Providing and laying in position specified grade of cement concrete for RCC structural elements upto floor five level including curing, compaction, finishing with rendering in cement sand mortar 1:3 (1 cement: 3 coarse sand) and making good the joints and cost of plastizers (if required) excluding the cost of centering, shuttering and reinforcement for Walls (any thickness) including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts	5609.00	Cum	701125.00

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

		M20 grade Nominal Mix / Design Mix			
16	299.00	Providing and laying in position specified grade of cement concrete for RCC structural elements upto floor five level including curing, compaction, finishing with rendering in cement sand mortar 1:3 (1 cement: 3 coarse sand) and making good the joints and cost of plastizers(if required) excluding the cost of centering, shuttering and reinforcement for Beams, suspended floors, roofs, grids having slopes up to 15°, landings, balconies, shelves, chajjas, lintels, bands, plain windows sills, staircases and spiral staircases etc. M20 grade Nominal Mix / Design Mix	5185.00	Cum	1550315.00
17	922.00	Add extra for providing richer mixes respectively at all floor levels Providing M-25 grade concrete by using cement as per codal provision instead of M-20 grade design mix.	69.00	Cum	63618.00
18	84133.00	Providing and fabricating reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding (including cost of binding wire) all complete up to floor five level. (Original producers' who manufacture billet directly from iron ores and roll the billets to produce steel conforming to IS:1786)Thermo-mechanically Treated bars (Conforming of relevent IS code)	77.00	Kg.	6478241.00
19	1469.00	Centering & shuttering with plywood or steel sheets including strutting, propping bracing both ways with steel props and removal of formwork for upto floor five level for :Suspended floors, roofs, landings, staircases, balconies, girders, cantilevers, bands, coping bed plates, anchor blocks, sills, chhajjas, lintel, beam, plinth beam etc.	340.00	Sqm.	499460.00
a	965.00	Columns, pillars, posts and struts etc.	375.00	Sqm.	361875.00
20	587.00	Brick work with F.P.S. bricks of class designation 75 in superstructure above plinth level upto floor V level in all shapes and sizes in : Cement mortar 1 : 6 (1 cement : 6 coarse sand)	4990.00	Cum.	2929130.00
21	384.00	Half brick masonry in Superstructure , above plinth level upto floor V level using bricks of designation 75 Cement mortar 1 : 4 (1 cement : 4 coarse sand)	553.00	Sqm.	212352.00
22	1998.00	Providing and Fixing Chiken wire mesh at the joint of masonry members/ R.C.C. Members with Nails complete in all respect.	77.00	Sqm	153846.00
23	6589.00	Plaster on new surface on walls in cement sand mortar 1:6	190.00	Sqm.	12570.00

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

		including racking of joint etc. complete fine finish :: 20 mm thick.			
24	751.00	6mm cement plaster to ceiling of mix 1:3 (1 Cement : 3 fine sand)	139.00	Sqm.	104389.00
25	6547.00	Providing and applying white cement based putty over plastered surface to prepare the surface even and smooth complete New Plastered Surface (three or more coats)	84.00	sqm	549948.00
26	5006.00	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade : Two or more coats on new work	69.00	Sqm.	345414.00
27	3897.00	Wall painting with plastic emulsion paint of approved brand and manufacture to give an even shade including all scaffolding:Two or more coats on new work including preparation of base with primer, putty, lippy etc complete in all respect.	80.00	Sqm.	311760.00
28	2692.00	Finishing walls with Acrylic Smooth exterior paint of required shade including all scaffolding. ew work (Two or more coat applied @ 1.67 ltr/10 sqm over and including base coat of water proofing cement paint applied @ 2.20 kg/ 10 sqm).	86.00	sqm	231512.00
29	400.00	Providing and fixing Square bars or other flat welded to window, ventilations etc.	65.00	Kg.	26000.00
30		Providing and fixing pressed steel door frames confirming to IS 4351 manufactured from commercial mild steel sheet of 1.25 mm thickness including hinges jamb, lock jamb, bead and if required angle threshold of mild steel angle of section 50x25mm, or base ties of 1.25mm pressed mild steel welded or rigidly fixed together by mechanical means, adjustable lugs with split end tail to each jamb including steel butt hinges 2.5mm thick with mortar guards, lock strike-plate and shock absorbers as specified and applying a coat of approved steel primer after pre-treatment of the surface including filling with CC 1:2:4(M15 grade) complete as directed by Engineer-in-charge :			
	42.00	Profile C	469.00	Mtr.	19698.00
31	214.00	Providing and fixing single paitam (rebated) stone doors windows and ventilator frames of approved quarry in cement sand mortar 1:4:size 100x75 mm	271.00	Mtr.	57994.00
32		P & F 1st quality Heavy Duty Vitrified Double Charged tiles on floor, skirting and steps etc.in different sizes (thickness minimum 10mm) with water absortion less than or equal 0.08% and conforming to IS 15622 of approved make in all			

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 11:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

		colour and shade, laid with 20 mm thick CM 1: 4 including grouting the joints with white cement and matching pigment etc complete.			
	242.00	size 600 mm X 600mm	1041.00	Sqm	251922.00
33	210.00	Providing and fixing 1st quality MAT finished ceramic tile size 300x300mm confirming to IS : 13755 and IS : 15622 colour such as white, grey, ivory, fume red brown, light green, light blue and other light shades in floors, steps, pillars etc. laid on a bed of neat cement slurry finished with flush pointing in the white cement mixed with pigment to match the shade of the tile complete (including the cost of cement mortar bed 1:4).	748.00	Sqm.	157080.00
34	210.00	Extra for using Marble printed / Granite shade or dark shade tiles instead of white, grey, ivory, fume red brown, light green, light blue and other light shades in glazed tiles and MAT finished tiles.	74.80	Sqm.	15708.00
35	210.00	Extra for using size above 200x300mm in glazed tiles and for using 400mm x 400mm MAT finished tiles in place of 300mm x 300mm size.	74.80	Sqm.	15708.00
36	793.00	Providing and fixing 1st quality MAT & GLOSSY finished ceramic tile confirming to IS : 13755 and IS : 15622 colour such as white, grey, ivory, fume red brown, light green, light blue and other light shades in floors, steps, pillars etc. laid on a bed of neat cement slurry finished with flush pointing in the white cement mixed with pigment to match the shade of the tile complete (including the cost of cement mortar bed 1:4).Size 300mm x 450mm	809.00	Sqm.	641537.00
37	357.00	Providing and fixing Granite stone slab mirror polished and machine edge cut in walls, pillars, steps, Shelves, Sills Counters, Floors etc. laid on 12mm (Av.) thick base of cement mortar 1:3 (1 cement : 3 coarse sand) jointing with white cement mortar 1:2 (1white cement : 2 marble dust) with pigment to match the shade of the marble slab including grinding, rubbing and polishing complete.Rajasthan Black Above 3601 Cm2 Slabs	3100.00	Sqm.	1106700.00
38	438.00	Providing and fixing Granite stone slab mirror polished and machine edge cut in walls, pillars, steps, Shelves, Sills Counters, Floors etc. laid on 12mm (Av.) thick base of cement mortar 1:3 (1 cement : 3 coarse sand) jointing with white cement mortar 1:2 (1white cement : 2 marble dust) with pigment to match the shade of the marble slab including grinding, rubbing and polishing complete.Jhunjhunu / Jalore (Red/Choclote/Black/Pink Colour) Above 3601 Cm2 Slabs	3028.00	Sqm.	1326264.00

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

39	404.00	Extra for providing edge moulding to 15-18mm thick marble/ Granite/Kota stone counters, Vanities etc. including machine polishing to edge to give high gloss finish etc. complete as per design approved by Engineer-in-Charge. Granite/Kota Stone Work Full Edge moulding	233.00	Mtr.	94132.00
40	61.00	Grading roof for water proofing treatment with water proffing compound Cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size)	4483.00	Cum	273463.00
41	265.80	Providing gola 75x75 mm in cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 stone aggregate 10mm and down gauge) including finishing with cement mortar 1:3 (1 cement : 3 fine sand) as per standard design :	111.00	Mtr.	29503.80
42	935.00	Providing and fixing 20 mm thick precast terrazo tiles of approved make, with marble chips of size upto 6mm laid over roof with neat cement slurry mixed with pigment to match the shade of the tiles, including cutting ,grinding rubbing with machine complete on 20 mm thick bed of cement sand mortar 1 : 4.Light shade using white cement	542.00	Sqm	506770.00
43	54.00	Providing & fixing precast cement concrete coping 1: 2:4 mix 50mm thick complete as per specification	367.00	Sqm	19818.00
44	59.00	Providing and fixing external grade board solid core single leaf flush door shutters ISI 2202-67 marked using Phenol formal dehyderesin in glue both sides with approved steel fittings complete as per annexure 'A' 35 mm thick .Commercial Veneer both side	1991.00	Sqm.	117469.00
45	31.00	Providing and fixing fully panelled/partly panelled/ double leaf shutter frames for doors as per approved design and drawings with approved ordinary C.P./ oxidised steel fittings as per Annexure - 'A' and width of styles & top rails of 100mm and lock rails width of 150mm and bottom rails of 200mm width including teak wood beading of size 19mm x 12mm on both faces complete :35 mm thick Ghana wood grade I	2968.00	Sqm.	92008.00
46	90.00	Extra for providing external lipping with 2nd class teak wood battens 6 mm minimum depth on all edges of shutters (over all area of door shutter to be measured) Over item no. 8.13.	141.00	Sqm	12690.00
47	32.00	Providing and fixing aluminum work for doors ,windows, ventilators and partition with extruded built up standard tubular / appropriate Z sections and other sections of approved make conforming to IS :733 and IS :1285, fixed with rawl plugs and screws or with fixing clips ,or	351.00	Kg.	11232.00

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 11:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

		with expansion hold fasteners including necessary filling up of gap. at junctions , at top ,bottom and sides with required PVC/neoprene felt etc. Aluminium section shall be smooth ,rust free, straight ,mitered and jointed mechanically wherever required including cleat angle Aluminium snap beading for glazing /paneling , C.P. brass/ stainless steel screws Al. Tower bolt & Al. handle & Al. Aldrop etc.,all complete as per architectural drawings and the directions of Engineer- in – charge .(Glazing and paneling to be paid for separately).For fixed portion Powder coating aluminum (minimum thickness of powder coating 50 micron)			
48	465.00	For shutters builtup standard tubular sections of openable doors ,windows & ventilators including providing & fixing hinges / rollers etc. and making provision for fixing of fittings wherever required (lockes shall be paid for separately).Powder coating aluminum (minimum thickness of powder coating 50 micron)	381.00	Kg.	177165.00
49	4.00	Providing and fixing glazing in aluminium door, window, vintilator shutters and partitions etc. with PVS/ neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge (Cost. of aluminium snap beading shall be paid in basic item.)With float glass panes of 5.0 mm thickness (weight not less than 13.50 kg/sqm)	902.00	Sqm.	3608.00
50	46.00	Providing and fixing expanded grill made of aluminum as per design and drawing having members section of size 7.5mm x 6.0mm and opening of size 102mm x 99mm to aluminum window/vent with required screws, Y and H aluminium sec (as per drawing) at the ends and middle joints respectively complete in all respect as per direction of engineer in charge. Powder coating aluminum (minimum thickness of powder coating 50 micron)	1843.00	Sqm.	84778.00
51	10.00	Providing and fixing 12 mm thick prelaminated three layer medium density (exterior grade) particle board Grade I, Type II conforming to IS : 12823 bonded formaldehyde synthetic resin ,of approved brand and manufacture in paneling fixed in aluminium doors ,windowsshutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and direction of engineer-in-charge.Prelaminated particle board with decorative lamination on both sides.	1092.00	Sqm.	10920.00
52	213.00	Providing and fixing stainless steel (Grade 304) railing made of Hollow tubes, channels, plates	503.00	Kg.	107109.00

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 11:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

		etc., including welding, grinding, buffing, polishing and making curvature (wherever required) and fitting the same with necessary stainless steel nuts and bolts complete, i/c fixing the railing with necessary accessories & stainless steel dash fasteners, stainless steel bolts etc., of required size, on the top of the floor or the side of waist slab with suitable arrangement as per approval of Engineer-in-charge, (for payment purpose only weight of stainless steel members shall be considered excluding fixing accessories such as nuts, bolts, fasteners etc.).			
53	20.00	Providing and fixing IS : 3564 marked aluminium extruded section body tubular type universal hydraulic door closer with double speed adjustment with necessary accessories and screws etc. complete.	1478.00	Each	29560.00
54	8.00	Providing and fixing bright finished Mortice lock of approved make Godrej or equivalent with pair of CP handles for doors with necessary screws etc complete (Best make of approved quality) as per direction of Engineer-in-charge.	629.00	Each	5032.00
55	8.00	Providing and fixing double action hydraulic floor spring of approved brand and manufacture IS : 6315 marked, for doors including cost of cutting floors as required, embedding in floors and cover plates with brass pivot and single piece M.S. With brass cover plate	1976.00	Each	15808.00
56	371.00	Providing and Fixing at all height all false ceiling of 12.5 mm thick tapered edge Gypsum board conforming to IS : 2095 including providing and fixing of frame work made of special section power pressed from M.S. sheet and galvanized in accordance with zinc coating 600 as per IS : 277 and consisting of angle cleats of thick 25 mm wide x 16 mm thick with flanges of 22 mm and 37 mm at 1200 mm center to center one flange fixed to the ceiling with dash fastner 12.5 mmdia x 40 mm long with 6 mm dia bolts to the hangers of 25x25x5mm of required length, and other end of angle hanger being fixed with nut and bolts to G.I. channels 45 mm x 15 mm x 0.9 mm running at the rate of 1200 mm center to center to which the ceiling section 0.5 mm thick bottom wedge of 80 mm with tapered flanges of 26 mm each having clips of 10.5 mm at 450 mm center to center shall be fixed in a direction perpendicular to G.I. channel with connecting clips made out of 2.64mm dia x 230mm long G.I. wire at every junction including fixing the gypsum board with ceiling section and perimeter channels 0.5mm thick 27 mm high having flanges of 20 mm and	825.00	Sqm.	306075.00

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

		30 mm long, the perimeter of ceiling fixed to wall / partition with the help of rawl plugs at 450 mm center to center with 25 mm long drive-all screws @ 230mm interval including jointing and fixing to a flush finish of tapered and square edges of gypsum board with recommended filler paper tapes, finisher and two coats of primer suitable for gypsum board as per manufactures specifications and also including the cost of making openings for right fittings, grills, diffusers, cutouts made with frame of perimeter channels suitably fixed all complete as per drawing and specifications and direction of the Engineer-in-charge but the excluding the cost of painting.			
57	177.00	Providing & laying Chequerred terrazzo tiles of approved make 22 mm thick with marble chips of size upto 6mm, in floors, jointed with neat cement slurry mixed with pigment to match the shade of tiles including rubbing and polishing complete in all respect as per specification, on 28 mm thick bed of C.M. 1:4 Dark shade using ordinary cement	618.00	sqm	109386.00
58	120.00	Providing and laying M30 grade controlled cement concrete pavements including mixing and vibrations concrete with necessary needle vibrators and surface with screed board vibrating complete in all respect with 20/25 mm stone aggregate (crusher broken) including anti-skid textured finish to required camber/ super lavation and grade including curing etc. as per specification with cement concrete M-30 grade including cost of Steel frame work for sides of C.C. pavement consisting of M. S. channels flats and angles with required steel pegs (some of them may left embedded in concrete/ including providing frame work	5514.00	Cum.	661680.00
59	800.00	Extra for vacuum processed concrete including cost of equipments LABOUR etc.	101.00	sqm	80800.00
60	3.00	Providing and laying at or near ground level factory made kerb stone of M-25 grade cement in position to the required line, level and curvature jointed with cement mortar 1:3 (1 cement : 3 coarse sand) including making joints with without grooves (thickness of joints except at sharp curve shall not to more than 5mm) including making drainage opening wherever required complete including painting etc. as per direction of Engineer-in-charge (length of finished kerb edging shall be measured for payment). (Precast C.C. kerb stone shall be approved by Engineerin- charge).	6103.00	Cum.	18309.00
61	340.00	Cutting of construction joint/ longitudinal joint 4	94.00	Mtr	3200.00

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 11:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

		to 6 mm. wide using mechanical concrete cutter including cost of diamond bit cutting wheel and filling of bitumen sealing compound in groove including cost of sealing compound (50 mm depth)			
62	500.00	Providing and fixing steel gate, grating , and grills made of angles, tees, square bars, flats, or black pipe with holdfast and fittings complete as per design and drawing including cutting welding and fabrication with priming coat of red oxide	96.00	Kg	48000.00
63	4.41	Providing and fixing M.S.sheet single leaf door shutter in angle iron frame 35x35x5mm suitably diagonally bracked with 25x3mm flat iron above and below lock rail of size 50x5mm beading extra including all fittings, as per direction of Engineer-in-charge but excluding cost of chowkhats: including two coats of anti-corrosive red oxide primer paint.	2869.00	Sqm	12652.29
64		Providing and laying of paver block as per IS 15658 : 2006 (Indian standard for Precast concrete block for Paving -specification) and IRC :SP:63-2004(guidelines for the use of interlocking concrete block Pavement) (from BIS approved manufacturers			
		M-35, 60mm thick to be used in light traffic (Light traffic is defined as a daily traffic up to 150 commercial vehicles exceeding 30 KN laden weight, or an equivalent up to 0.5 million standard axles (MSA) for a design life of 20 years (A standard axle is defined as a single axle load of 81.6 KN) like pedestrian plazas, shopping complexes ramps, car Parks, office driveways , housing colonies , office complexes , rural roads with low volume traffic , farm houses, beach sites, tourist resorts, local authority footways , residential roads, etc.			
a	188.00	Category 'C' not denoted on any of its face like Hexagon, Rectangular, square shape as per IRC SP 63:2004	736.00	Sqm	138368.00
b	188.00	Add extra over item No. 11.38, A to C if reflective paver block, manufactured with wet cast vibration system in two layers is used.	73.60	Sqm	13836.80
c	47.00	Add extra over rates of item No. 11.38, A to C if colored paver blocks are used	147.20	Sqm	6918.40
65	8.64	Providing and fixing in position collapsible steel shutters with vertical M.S. Channels 20 x 10 x 2mm and bracket with flat iron diagonals 20 x 5mm. size with top and bottom rail of T-iron 40 x 40 x 6mm. with 40mm dia steel pulleys/ball	5174.00	Sqm	44703.36

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 11:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

		bearing complete with bolts, nuts locking arrangements inside and outside stoppers, handles etc. as per specification including applying a priming coat of approved steel primer. (To be measured and paid as per outer dimension).With 75 mm opening when closed.			
66	57950.00	Steel work in built up tubular trusses including cutting, hoisting (height upto 10 m)fixing in position and applying a priming coat of approved steel primer, welded and bolted including special shaped washers etc. complete. Hot finished seamless type tubes	109.00	Kg	6316550.00
67	57950.00	Extra for hoisting and fixing for every additional one metre or part thereof beyond 10 mtr height.	6.00	Kg	347700.00
68	2225.00	Supply and installation of Multi Rib Proofing/cladding Sheet Manufacture out of 0.50mm TCT (Total Coated Thickness) high tensile Zinc aluminum alloy coated galvalume steel (as per 150gsm zinc aluminum coated 550Mpa tuekd strength) confirming to IS: 1397/astm A-792 sheet to have wide pens 30mm high NB at 250 centre and centre width of 1020mm sheets be casted with regular modified polyster system on a continuous with line on centre for face and with a polyster coating respectively sheet shall have proportionality with siphoned plate made to prevent leakage sheet shall be fixed by more of sell drilling lift tapping hot dip zinc coated hox head fasterner of size 12x14x55mm long. The sheet shall be supplied in cost one length and for a minimum up to 12mts with all scaffolding.	689.00	Sqm	1533025.00
69	2225.00	Extra for hoisting and fixing for every additional one metre or part thereof beyond 10 mtr height.	310.05	Sqm	689861.25
70		Providing & Fixing Premium Quality white glazed vitreous china Sanitary Wares (IS:2556 Mark) of approved make as per direction of Engineer-in-charge including cutting and making good the wall and floor.			
a	6.00	W.C. orissa pan with 100 mm vitreous china P or S trap	3065.00	Each	18390.00
b	12.00	Wall Mounting European type W.C.	9072.00	Each	108864.00
71		Providing & Fixing premium qulaity WVC Urinal with PVC waste pipe, dome couplings, concealed iron brackets or screws etc. complete.			
	9.00	Flat Back (large) or half stall size 590x375x390 mm.	6246.00	Each	56214.00
72	9.00	Providing & Fixing premium qulaity W.V.C. Urinal Partition plate of size 630x315 mm	2636.00	Each	23724.00

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

73	12.00	P & F C.P. Health Faucet with 1Mtr. Long Tube & Hook of approved make and heavy as per direction of Enginner-in-Charge	605.00	Each	7260.00
74	9.00	P & F C.P. brass Urinal Spreader for Large Urinal of heavy duty of approved make as per direction of Enginner-in-Charge	617.00	Each	5553.00
75		Providing & Fixing premium qulaity WVC Wash basin with C.I. brackets duly painted & 32 mm C.P. brass waste coupling of approved make with PVC waste pipe complete			
	8.00	Size 550 mm x 400 mm dia for counter top.	3372.00	Each	26976.00
76	6.00	P&F Looking Mirror 5mm thick of approved make with ornamental frame size 50x12 with 6mm Ply Board on Back Side Complete as per approved sample	2544.00	Sqm	15264.00
77	12.00	Supply of Hydraulic Seat Cover for European WC of superior quality approved make in white Colour	4057.00	Each	48684.00
78	12.00	Providing & Fixing Concealed cistern with Floor mounting frame and flush plate of superior quality and approved sample by Engineer-in-charge.	8187.00	Each	98244.00
79	12.00	Providing & Fixing premium quality waste coupling 32mm half thread as per approved by Engineer in Charge.	519.00	Each	6228.00
80	8.00	Providing & Fixing Premium quality Bottle trap internal portion 32mm, size 250mm long wall connection pipe & wall flange as per approved by Engineer in Charge.	1599.00	Each	12792.00
81		P & F Grating of approved quality/make:			
a	20.00	(-do-) Square 150 x 150 x 8mm. (Anti Cockroach)	358.00	Each	7160.00
b	10.00	Stainless Steel Sheet size 125mm dia. Heavy Quality of approved make	97.00	Each	970.00
82		P & F Liquid Soap Container with brackets complete of approved make:			
	4.00	C.P. brass	238.00	Each	952.00
83		Providing and fixing Superior quality CP Brass fittings of approved make as per direction of Engineer-in-charge			
a	8.00	Swan neck pillar cock 15 mm nominal size	1580.00	Each	12640.00
b	14.00	Bib Cock with long thread 15 mm nominal size	823.00	Each	11522.00
c	24.00	Angular stop cock with long thread 15 mm nominal size	762.00	Each	18288.00
d	10.00	Concealed stop cock 15 mm nominal size	1162.00	Each	11620.00
e	4.00	Wall mixer 3 in 1 system with provision of teteponic bath shower with bend pipe	3743.00	Each	14972.00
f	6.00	600 mm long towel rail	1881.00	Each	10896.00
g	5.00	Revolving type towel ring	1101.00	Each	5505.00

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

h	8.00	Soap dish (MCH/IVC)	1071.00	Each	8568.00
i	12.00	Paper holder (MCH/IVC)	1125.00	Each	13500.00
84		P & F Extension Pipe for bib cocks of approved quality/make.			
a	14.00	C.P. brass of Heavy & Superior quality 150x15m	168.00	Each	2352.00
85	36.00	Providing & fixing C.P.flange for 15mm dia taps.	18.00	Each	648.00
86		Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply including all CPVC plain & brass threaded fittings i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge. (Concealed work including cutting chases and making good the walls etc.,)			
a	90.00	15mm nominal outer dia pipe	279.00	Mtr.	25110.00
b	30.00	25 mm nominal outer dia pipes	376.00	Rm	11280.00
87		Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply including all CPVC plain & brass threaded fittings, this included jointing of pipes & fittings with one step CPVC solvent cement , trenching refilling & testing of joints complete as per direction of Engineer in Charge. (External work).			
a	60.00	15 mm nominal outer dia pipes	167.00	Rm	10020.00
b	170.00	25 mm nominal outer dia pipes	262.00	Rm	44540.00
88		P & F Ball Cock (IS :1703 Mark) with Rod & P.V.C. Ball complete :			
	5.00	(-do-) wt.Not less than 600 gm, 25mm.	440.00	Each	2200.00
89		P & F 15 mm. Dia Connection Pipe of approved quality/make :			
a	20.00	PVC pipe with C.P. Brass nuts upto length 600mm.	116.00	Each	2320.00
90		P & F Full-way Valve (IS:778 Mark) or wheel valve of approved make :			
a	4.00	Gun-metal 15mm nominal bore.	227.00	Each	908.00
b	4.00	Gun-metal 25 mm nominal bore.	529.00	Each	2116.00
91		P & F PVC Storage Tank ISI Marked (IS : 12701) indicating the BIS license No), of approved make with cover, 25mm dia 1M long G.I. over-flow pipe & 25 Cm. long wash out pipe with plug & socket, including making connection etc., complete of approved design:			
	5.00	1000 litres capacity.	7841.00	Each	39205.00
92		Hoisting Charges for each floor :			
	5.00	For items 2.26.5 to 2.26.8	157.00	Each	785.00

RajKaj Ref No.:
23881605

M e-Sign

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

93		Providing, Laying & Jointing R.C.C. class NP-2 Non-Pressure pipes (IS : 458mark) of approved make with collars, jointed with C.M. 1:2 or having Spigot and socket ends with flexible rubber rings joint including testing of joints etc. complete :			
a	20.00	200mm dia Internal	674.00	Mtr.	13480.00
b	18.00	300mm dia Internal	991.00	Mtr.	17838.00
94		P&F rigid PVC Pipe (IS:4985 mark) class II/ (4 Kg. /Cm2.) approved quality /make including joining the pipe with solvent cement rubber ring and lubricant.			
a	60.00	110 mm dia	282.00	Mtr.	16920.00
b	110.00	160 mm dia	463.00	Mtr.	50930.00
95		P&F rigid PVC pipe fittings (IS: 4985 mark) of approved quality /make including joining the pipe with solvent cement rubber ring and lubricant:			
a		Coupler (socket)			
	15.00	110mm dia	108.00	Each	1620.00
	45.00	160 mm dia	119.00	Each	5355.00
b		Bend 87.5			
	15.00	110mm dia	161.00	Each	2415.00
	45.00	160 mm dia	177.00	Each	7965.00
c		Pipe clip			
	20.00	110mm dia	36.00	Each	720.00
	80.00	160 mm dia	53.00	Each	4240.00
96		Construction of chamber in all type of soil with 300 mm thick masonry in CM 1:6 m,10 cm thick C.C. 1:5:10 in foundation, 20mm thick insider plaster in Cm 1:6, finished with floating neat cement, 50mm thick M-15 grade C.C. flooring , earthwork etc. complete as per design including disposal of surplus earth within a lead of 50 mtr.			
	10.00	Inside size 450 x 450mm depth upto 0.5 M Cement cover with frame. Deduct for using brick work 230 mm thick in place of 300 mm thick stone masonry	1824.00	Each	18240.00
97	80.00	Providing and fixing unplasticized Poly Vinyl Chloride (UPVC) SWR pipes type 'B' for sciland waste dischareg system (IS : 13592: 1992 marked) of approved quality/ make. 110mm dia	336.00	Mtr.	26880.00
98		Providing and Fixing Unplasticized Poly Vinyl Chloride (UPVC) SWR Pipes fittings type B for sciland waste discharge system (IS:13592 : 1992 Marked) of approved quality /make			
a		Coupler			
	30.00	110mm dia	108.00	Each	3240.00
b		Bend 87.5 Dg.			

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

	30.00	110mm dia	155.00	Each	4650.00
c		Single Tee			
	30.00	110mm dia	210.00	Each	6300.00
d		Gully Trap			
	4.00	110mm dia	685.00	Each	2740.00
e		Nahni Trap with Jali 4"			
	24.00	110mm dia	171.00	Each	4104.00
f		Vent Cowel			
	4.00	110mm dia	59.00	Each	236.00
99		Construction of Open Surface Drain with 112mm thick brick masonry in CM 1:4, 110mm thick base concrete 1:5:10, 37mm thick M-15 grade C.C. flooring, 12mm 1:4 cement plaster on all exposed faces of walls including top surface excavation & disposal of earth complete as per approved design/drawing:			
	150.00	250mm drain, 300mm Av. depth	380.00	Mtr.	57000.00
100	2.00	Construction of septic Tank in all types of soil with 40 Cm .thick masonry in CM 1:6, 15 Cm thick C.C bed of 1:5:10, M-15 grade C.C floor & RCC slab covering with M15 grade c.c. floor , 50 mm thick stone slab partition walls, 20 mm thick plaster in CM 1:6 finished with neat floating cement, 4 Nos stone foot rests of approved design, two No. 450 mm dia each Ferro cement cover with frame, earth work etc. complete as per approved drawing including disposal of surplus earth within a lead of 50 mtr:- Size 400 x140x150 cm.(for 50 users)	59860.00	Each	119720.00
101		Construction of soakage well in all type of soil with 300 mm thick dry masonry, top and bottom 300 mm course in CM 1:6, 80mm thick stone slab, jointing of slab in CM 1 : 3, Ralthal, Kharanja, 40 mm thick M-15 grade C.C flooring, earthwork complete as per approved drawing including disposal of earth within a lead of 50 mtr.:			
	2.00	Size 300 Cm. dia outside & 300 Cm. depth .	24135.00	Each	48270.00
102		Wiring of light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper conductor 1.1 kV grade and 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper earth conductor 1.1 kV grade (IS:694) in recessed ISI marked MMS (IS:9537 P - III) virgin material PVC conduit & it's ISI marked (IS:3419-1988) accessories, round tiles, 1.2 mm thick Hot Dipped Galvanized Modular Box with earth terminal, 10A Modular switch, Modular face plate with grid plate, 3 pin ceiling rose / Holder /3 way connector, screws,			

Signature valid

Digitally signed by Rajkaj Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

		making connections, testing etc. as required. For specification of copper Conductor, Phenolic Laminated sheet's & Electrical/ Wiring accessories refer Chapter E - 04, E - 05 & E - 07 For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
	20.00	Short point (up to 3 mtr.)	343.00	P. point	6860.00
	25.00	Medium point (up to 6 mtr.)	601.00	P. point	15025.00
	80.00	Long point (up to 10 mtr.)	825.00	P. point	66000.00
103		Wiring of 3/5 pin 6 amp. Light plug point with 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper conductor 1.1 kV grade and 1.5 sq. mm nominal size FR PVC insulated unsheathed flexible copper earth conductor 1.1 kV grade (IS:694) in recessed ISI marked MMS (IS:9537 P - III) PVC conduit & it's ISI marked (IS:3419-1988) accessories, Hot Dipped Galvanized Modular box of 1.2 mm thick with earth terminal, 10 A modular switch, 3/5 pin 6 A modular socket, Modular face plate with grid plate, screws, making connections, testing etc. as required. For specification of copper Conductor, Phenolic Laminated sheet's & Electrical/ Wiring accessories refer Chapter E - 04, E - 05 & E - 07 For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
	24.00	On board	382.00	P. point	9168.00
	10.00	Short point (up to 3 mtr.)	551.00	P. point	5510.00
104		S&F following sizes (dia.) of ISI marked virgin material MMS (IS:9537 P - III) PVC conduit along with ISI marked (IS:3419-1988) accessories as required in recess including cutting the wall, covering conduit and making good the same as required. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
	350.00	20 mm	39.00	R. mtr.	13650.00
	800.00	25 mm	55.00	R. mtr.	44000.00
105		Supplying and drawing FR PVC insulated & unsheathed flexible copper conductor as per PWD specification for electrical Works with ISI marked (IS:694) and as per IS 8130 : 2013 of 1.1 kV grade . Wire should be made from 99.90 % purity copper, class 5 stranding in acc. to IS:8130/IEC 60228 for lower watt loss , oxygen			

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

		free for less chances of oxidization, insulation PVC type A/C/D , flame retardant as per IS 10810-53, better amperage rating as per IS:3961 part 5, in existing surface or recessed PVC/ MS conduit/casing capping making connections with Copper Lugs of suitable size, Ferrules,testing etc. as required. OEM Must have its own in house NABL lab setup for all testing facilities for wires. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
	300.00	3x 1.5 sq.mm	76.00	Mtr.	22800.00
	650.00	2 x 2.5 sq. mm. + 1x1.5sqmm	106.00	Mtr.	68900.00
	700.00	2 x 4.0 sq. mm. + 1 x 2.5 sq. mm.	168.00	Mtr.	117600.00
	250.00	2 x 6.0 sq.mm	176.00	Mtr.	44000.00
106	21.00	P & F 1.2mm thick M.S. Recessed fan box, hexagonal/ round of size 130 mm dia, depth 75mm, 12 mm dia rod fan hook with 100 mm length extended on each side . All as per pre approved by Engineer in charge. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR	112.00	Each	2352.00
107		Providing & Fixing of 240/415 V AC MCB with positive isolation of 10 kA breaking capacity (B/ C/D tripping characteristic as per type of load and site requirement) 4 KV impulse withstand voltage, ISI marked IS 8828(1996) / conforming to IEC 60898-1 2002, IEC 60947-2, low watt losses, trip free mechanism , energy limiting of class 3 as per IEC, minimum phase termination capacity of 35sq.mm. , conductor line load reversibility , IP 20 contact protection and fitted in existing distribution board/sheets, minimum electrical operation 20,000 upto 20 A rating and 10,000 upto 63 A, 5000 for 80 A & above rating including making connections, testing etc. as required. OEM shall have submit NABL / CPRI / ERDA accredited lab type test reports & All as per pre approved by Engineer in charge. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a		Single pole MCB (With B/C curve tripping Characteristics)			
i	50.00	6 A to 32 A rating	199.00	Each	9950.00
b		Triple pole MCB (With D curve tripping Characteristics)			
i	12.00	6 A to 32 A rating	1087.00	Each	13044.00

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

108		Providing & Fixing of Recessed/surface mounting heavy duty horizontal type Double Door (Metal / Glazed)Distribution board with Metal end box made out from Galvanized steel / CRCA sheet not less then 1.2 mm thick conforming to IS-8623-1 & 3 / IEC 61439- 1 & 3, powder painted complete with reversible door (for double door DB only)100 amp. insulated copper bus bar/shorting link , copper neutral link, copper earth link , color coded interconnecting wire set of suitable rating and din bar,masking sheet, making internal DB terminations with copper lugs, Ferrules, detachable gland plate, including making connections, testing etc. as required. OEM shall have submit NABL / CPRI / ERDA accredited lab type test reports & All as per pre approved by Engineer in charge. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
		Metal door (Three phase) IK-09 and IP-43 with Metal end box			
a	2.00	8 Way (8 incomer + 24 Outgoing)	6787.00	Each	13574.00
b	2.00	12 Way (8 incomer + 36 Outgoing)	9742.00	Each	19484.00
109		Providing & Fixing of modular type switch/ bell push duly ISI marked (IS :3854) with CM/L no. printed and made out of unbreakable and fire retardant vergin UV Stabilized Polycarbonate with brass terminals and captive screws & silver alloy contact tip with IP-20 rating ,minimum width of switch toggle(PUSH PART) should not less then 20mm, including all as per pre approved by Engineer in charge,making connections, testing etc. as required. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a	30.00	10 A one way switch	41.00	Each	1230.00
b	50.00	16 A one way switch With Led Indicator	55.00	Each	2750.00
110		Providing & Fixing of modular type lockable feature socket duly made out of unbreakable and fire retardant vergin poly carbonate with brass terminals and captive screws & silver alloy contact tip with IP-20 rating , including all as per pre approved by Engineer in charge,making connections, testing etc. as required. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a	28.00	6 A 3/5 pin shuttered socket	99.00	Each	2772.00
b	45.00	6/16 A shuttered socket	170.00	Each	7650.00

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

111		Providing & Fixing of following size mounting grid plates with cover plates made from fire retardant UV established high performance engineering plastic suitable for all universal metal boxes for front installation & removal direct fit type complete in all respect.All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
a	20.00	3 Module	97.00	Each	1940.00
b	20.00	8 Module	202.00	Each	4040.00
c	10.00	12 Module	242.00	Each	2420.00
112		Providing & Fixing of Wiring Accessories OEM fabricated following size virgin material UPVC modular boxes on surface suitable for modular accessories as required.All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
a	22.00	1-2 Module	96.00	Each	2112.00
b	25.00	6-8 Module	198.00	Each	4950.00
c	10.00	10-12 Module	269.00	Each	2690.00
113	21.00	Providing & Fixing of modular type 100W Step Fan regulator duly ISI marked (IS 11037) with CM/L no. printed made out of unbreakable and fire retardant virgin poly carbonate with brass terminals and captive screws & silver alloy contact tip with IP-20 rating , including making connections, testing etc as required.5 step fan regulator 2 Module	387.00	Each	8127.00
114	36.00	Providing and fixing of power plug point with non modular accessories with Galvanized box of 1.2 mm thick with earth terminal with suitable size 3.0 mm thick phenolic laminated sheet (IS : 2036 - 1995) cover including cost of 16 amp. Switch (IS :3854) and 3/6 pin 16 amp. socket outlet making connection , testing , etc. as required.	293.00	Each	10548.00
115		SITC of IP-42 and general construction confirming to IS:8623 : 1993, wall/ free standing floor mounted dust and vermin proof compartmentalised cubical panel as specifications and Other parameters required as per point (a) ,(b), (c),(d), (e), (f), (g), (h) as below:-			
a		(a)Thickness of CRCA sheet shall be 2.0 mm, cable alley compartments having concealed hinged type doors with key type lock with / without detachable extension type structure. Removable 3 mm. thick sheet steel gland plates with appropriate size of knockouts for cables shall be provided			

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

b	(b)complete panel shall undergo a process of degreasing, Water rinsing, Activation, derusting, pickling in acid bath, phosphatising & shall be subjected to nine tank process and then Powder coated with approved shade of minimum 70 microns on both side of panel. The panel having PE foam/ Neoprene rubber gasket of not less than 3mm thickness ,required hardware , concealed hinged door with key type locking arrangement for equipment/switchgear earthed with 2.5 sq.mm braided copper wire.			
c	[c] Interconnection between bus bar and switchgears /cable shall be rigidly supported and made out by flexible copper wires (up to 63 amp) and by solid bus bar (>63 amp) . control wiring will be carried out with 1.5 Sq.mm, Earth wire with 2.5 Sq.mm and CT with 2.5 sq.mm flexible copper wire only. All joints / interconnections of copper bus bar shall be dully tinned . Clearance between main bus bar and risers / metal parts shall be at least 10 mm additional to width of bus bar Bus bar is insulated by Heat Shrinkable sleeves . Earth and Neutral bus bar shall be half of the size of phase bus bar. (Cost of Bus bar / Flexible wire for Interconnection between Main busbar and Switchgear is to be Paid Extra)			
d	(d)Wiring between components within switchgear and Incoming / outgoing cable shall be done through the terminal block only. Direct connection shall not be permitted. Each terminal block shall be one piece moulded, barrier type, 650 volt grade, complete with washers, heads, studs with two nuts and identification strips and shall have adequate continuous current rating. For tap-offs, adjacent terminals with shorting strips shall be used. 10% Spare terminal blocks shall be provided. Wire identification on marking strip shall correspond to the designation of the wiring diagrams. All wire terminals on the equipment shall also be marked with designation corresponding to those of the wiring diagram.			
e	(e)All wiring shall be enclosed in plastic channels and neatly bunched and closed in metering chamber, Wiring between terminals of various devices shall be ‘point to point’ (no wire splitting or tee connections) with wires neatly trucked along the back of the panels, adequately supported to prevent sagging.			
f	(f)Floor mounted panel shall be mounted on Base frame of ISMC channel size 100 x 50 x 5 mm (to be paid Extra)			

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

g		(g) Tests: The insulation resistance (with 1000 V Megger) and High voltage Power frequency test (by applying a voltage of 2.5KV for one minute) shall be measured between phases, between phase and neutral and between phase and earth. both before and after high voltage power frequency test. The insulation resistance shall not be less than three megaohm. CT Secondary current injection test shall also be carried out.			
h	18.00	(h) only outer surface area on all sides shall be measured & panel to be fabricated only from CPRI approved fabricator only (CPRI Test certificates to be submitted)All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .	6578.00	Sq. Mtr	118404.00
116		Supplying and fixing of Aluminium (IEC 60105 ISO 209-1,2) / Copper (IEC 60028) bus bar by means of SMC / DMC type insulator with standard short circuit withstand capacity , high tensile nuts and bolts spring washers in existing panel including bending , cutting in required shape and size and colour coding with heat shrinkable PVC sleeves. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
a	32.00	Electrolytic grade Aluminium bus bar 6010 grade	660.00	Kg.	21120.00
117		Providing & Fixing of IS: 13875 & IEC :61326 confirming LED Digital type (up to 500) V range Volt meter / Direct- Ammeter / CT oertated ammeter/ Frequency meter / KWH meter / Multi Function Meter / Power analyzer of class 1 accuracy as per IS : 1248 of size 96mm x 96 mm including making connection by PVC insulated copper conductor with PVC sleeves / channel etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
a	1.00	Three phase Ammeter with Inbuilt Selector Switch	1777.00	Each	1777.00
b	1.00	Three phase Voltmeter with Inbuilt Selector Switch	1777.00	Each	1777.00
c	1.00	Three phase AMP+ HZ+PF+ KW+KVA+ KVAR+T.ENERGY+ THD-I, THD-V & RUN HRS	3460.00	Each	3460.00
118		Providing & Fixing of BIS approved Current Transformer as per PWD specification for electrical Works ,ISI marked as per IS 2705-1992/ conforming to IEC 60044-1, with secondary terminal of CT shall be brought out			

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

		suitable to a terminal block which shall be easier accessible for testing and terminal connection , with all necessary support in existing panel including connection etc. as required Current transformer Ring Type Tape Wound/Resin Cast Wound as per IS 16227 with, Accuracy CI, CT ratio and burden as specified. ISF<=5, Cu cross section of secondary wire 1.5sqmm (minimum), including all necessary support in existing panel including connection etc. as required . All as per pre approved by Engineer in charge.All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
		Resin cast wound type CT			
a	3.00	C T Class 1, Ratio 200/5 to 600/5, Burden 15 VA	1748.00	Each	5244.00
119	3.00	Providing & Fixing of 10 A Cam operated rotary (Local- Remote, Auto - manual) switches on existing panel with 1 pole 2 way and off position using high grade engineering material to international standards with cam assembly insulation of glass filled polyamide with high tracking index. For reliable and stable electrical and mechanical endurance double butt contacts with silver bi-metal on copper should provided . contact assembly is of operating temp range -25 degree C to 55 degree C, frequency upto 10 KHz. switch life under std. op. conditions shall be mechanically minimum 50000 operations @300 cycles/ hour and electrically 10,000 operations at 100% rated duty for 100 cycles/ hour including making connection etc. as required .	440.00	Each	1320.00
120		Providing & Fixing of 110/220 V, unibody LED Indicating lamp IEC 60947 with integral circuit, IP 65 above panel & IP 20 terminal block, Approx. body dia for panel not less then 20 mm, length min. 50mm, front LED cover dia min. 29 mm, contact material phosphor bronze for Led, PCB contacts shall be of brass (tin plated), impulse dielectric tested for 2.5 KV, Rated insulation resistance shall be 100 M ohm at 500VDC including connection etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
a	9.00	Red/yellow/Green colour	173.00	Each	1557.00
b	3.00	Blue / white Colour	274.00	Each	822.00

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

121		Providing & Fixing of Electrical insulating rubber matts as per PWD specification for electrical Works, ISI marked confirming to IS: 15652 / 2006 with one side anti skid abberation marks and pasting the mat with synthetic rubber adhesive as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
a	5.00	3.3 KV, class A 2 mm thick with proof voltage 10 KV AC (rms) and Break Down Voltage 30 KV AC (rms)	1502.00	SQ.Mtr	7510.00
122		SITC of 3 /4 pole current limiting Moulded case circuit breaker (MCCB) made of flame retardent & heat resistant material having following current rating, short circuit breaking capacity at 440/415 V, 50 Hz; O/L & S/C settings , conforming to IS/IEC 60947 P -2 :2003 with front face and centralised adjustable, trip free mechanisum, true contact position indicator, line load interchangeability, designed for both horizontal & vertical mounting without any adverse effect on electrical performance, suitable for operation upto 55 degree and without derating upto 40 degree, pollution degree 3, having positive isolation capability, push (test) to trip, trip time less then 10 ms under s/c condition, Breaking capacity Ics = 100% Icu. U imp =8 KV, rated insulation voltage 690 V. provision for UVR , shunt trip , earth fault trip, door interlock, pad lock & rotary handle , including making connections etc. as required.OEM shall have submit NABL / CPRI / ERDA accredited lab type test certificate before execution All as per pre approved by Engineer in charge. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
		3 pole MCCB With Thermal Magnetic release			
a	6.00	up to 100 Amp , 10 kA, fixed O/L & fixed S/C setting	1777.00	Each	10662.00
b	2.00	160 Amp , 25 kA, adjustable O/L & adjustable S/C setting,	10409.00	Each	20818.00
i		4 pole MCCB With Thermal Magnetic release			
c	1.00	250 Amp , 35 kA, adjustable O/L & adjustable S/C setting,	20608.00	Each	20608.00
123	1.00	Providing & Fixing of off load change over switch four pole/two pole, 230/ 415 V ,side handle operated confirming to IS:13947 P-III in sheet steel enclosure complete with connections with lugs, testing etc. as required in the following rating: 200 A Four pole	16632.00	Each	16632.00

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

124		Providing & Laying P.V.C. / XLPE insulated & P.V.C. sheathed Armoured Aluminium cable confirming to IS:1554 P-I / IS :7098 P - I of 1.1 KV with H4- Grade electrolytic aluminium conductor confirming to IS 8130 of purity >99.6 %, round / flat strip armouring of cables, Inner / outer sheath confirming to IS:5831 in existing RCC / Hume / Stoneware / PVC pipe/ open duct/cable trench / Cable tray(with cable tie) including testing etc. as required of following size. OEM must have it's own in house NABL accredited Laboratory for testing procedure as per IS:10810.For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a		10.0 Sq. mm			
i	380.00	4 core	211.00	Mtr	80180.00
b		25.0 Sq. mm			
i	170.00	3.5 core	381.00	Mtr	64770.00
c		70.0 Sq. mm			
i	120.00	3.5 core	686.00	Mtr	82320.00
d		120.0 Sq. mm			
i	100.00	3.5 core	964.00	Mtr	96400.00
125		Add Extra in item no. 11.1 to 11.4 for Laying and fixing of one number PVC insulated and PVC sheathed / XLPE power cable of 1.1 KV grade of following size on wall surface as required.			
a	550.00	Up to 35 Sq.mm fixed with 25 mm x 2 mm thick suitable length red oxide and enamel painted MS clamp and base, pvc rawl plug and screws of sufficient size with spacing 0.6 Mtr. Between Clamps.	37.00	Mtr	20350.00
126		Supplying and making one end termination with Nickel plated heavy duty brass single compression gland (as per IS 12943-1990)) SIBG type consisting of Check Nut, Gland Body, Metal Washer(3 Nos.), Outer Seal Rubber Ring, Compression Nut, heavy duty aluminium lugs (as per IS 8309 -1993) duly crimped with crimping tool, PVC tape as per IS 8337-1976 of following size of PVC insulated & PVC sheathed/ XLPE aluminium conductor cable of 1100 volt grade as required.All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
a	24.00	4 x 10.0 sq.mm	182.00	Set	4368.00
b	20.00	3.5 x 25.0 sq.mm	228.00	Set	4560.00
c	16.00	3.5 x 70.0 sq.mm	417.00	Set	6672.00
d	8.00	3.5 x 120.0 sq.mm	795.00	Set	6360.00

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 11:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

127		Supply, Fabricating & installing following sizes of perforated Hot dipped Galvanized iron cable tray (Galvanized thickness not less then 50 microns) with perforation not more then 17.5% in convenient section including horizontal and vertical bends, reducers tees,cross members and other accessories as required and duly suspended from the ceiling with GI suspenders including GI bolts & nuts , fastners, supports etc. as required.All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
a	70.00	150mm x 50mm x 1.6mm	706.00	Mtr	49420.00
b	30.00	300mm x 50mm x 1.6mm	1129.00	Mtr	33870.00
128	2.00	Plate Earthing as per IS:3043 with copper Earth plate of purity >95% of size 600mm x 600mm x 3.0mm by embodying 3 mtr. below the ground level with 20 mm dia. G.I. 'B' class watering Pipe ,including all accessories like nut, bolts, reducer, nipple, wire meshed funnel, and Heavy duty weather proof poly-propylene earth pit chamber with lockable Jam free lid suitable for safe working load 5000 Kg or more of size Top Dia. 225 to 260 mm, Bottom Dia 300 to 350 mm. and Height 250 to 300 mm. and embodying the pipe complete with alternate layers salt and coke/ charcoal, testing of earth resistance for value of 5 ohms or less as required & must record by engineer in charge during site visit and ensure to enter in measurment book. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .	18604.00	Set	37208.00
129		Providing & Fixing of BEE Star rated copper wounded double ball bearing capacitor start, aluminium body & Metallic blade ceiling fan Conforming to all the performance requirements laid down in IS 374:2019 including all amendments, as applicable ; & Carry BIS licensing (i.e. ISI marking) with down rod up to 80 cm with secondary support safety cable (steel rope) , cotter pin with 3 x 1.5 sq.mm pvc insulated flexible copper conductor making connection testing etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
a	21.00	1200 mm Sweep BEE 3 Star rated (service value >=5.0 to < 5.5)	2364.00	Each	49644.00
130		Providing & Fixing of Heavy duty capacitor start, copper wound Double ball bearing			

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

		900/1400 RPM single phase Exhaust fan conforming to IS:2312 marked in existing opening including making connections testing etc. as required.			
a	2.00	300 mm sweep(900 RPM)	3487.00	Each	6974.00
131		Providing & Fixing of 450 mm Sweep Oscillating type Wall mounting / Pedestal type fans with Three speed, ON and OFF position, Sintered Iron bush oil impregnated, with metal front and back 120 or more ribs guard; Three no. Aluminium blades, minimum Air delivery 100 Cum. / Minute , Minimum Service Value 1.11 Cum./min/watt, noise level should be <= 75 dB, power consumption <= 120 watts, motor protection through thermal overload protection device, including fixing with anchor bolts, making connection testing etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
a	20.00	Wall mounting type with Adjustable Vertical Angle	5721.00	Each	114420.00
132	21.00	Providing & Fixing of extra down rod of 15 mm dia . ERW (Electrical resistance welded) of 1.6mm nominal thick medium duty steel pipe including cutting, threading, drilling, fixing quarter pin etc as reqd. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .	257.00	Mtr.	5397.00
133		Providing & Fixing of Vertical(BEE 5 star rated) / Horizontal(BEE 3 star rated) storage water heater with outer casing made of Engineering Plastic sheet (Upto 25 Ltr) / Metal rust proof Body (35 & 50 Ltr), Glass - line / Titanium Enamel coated Pressure Pump Compatible 8 bar pressure Inner tank, Glass Line Coated , mineral filled heating element, stem type, snap action adjustable thermostat , Dual indicating lamps Injected PUF insulation, Multi Function Valve etc. as required held in position with 2/4 no. 10/12 mm anchor Fastener, duly wired with 3 core 2.5/4.0 Sqmm PVC insulated & sheathed copper conductor and 16 A/25A three pin plug top with Portable Residual Current Device (PRCD) , including making inlet, outlet Flexible alloy connection, testing etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
a	2.00	25 Ltr.	12584.00	Each	25168.00
134		Providing & Fixing of IP20 SMD Mid Power			

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

		LED batten type integrated light fixture made from Powder coated Extruded aluminium housing with in built driver , System lumen efficacy ≥ 110 lm/Watt output, internal surge protection of 2.5 KV with Short & Open circuit protection ,THD < 10% , P. F. ≥ 0.95 , CRI >80 , life time of minimum 50000 Burning Hours with , 70% of intial Lumen maintaned till life ends , CCT 3000°K / 4000°K / 5700°K /6000°K/6500°K (As per ANSI Bin) , Maximum power consumption should not more than the specified rating and Fixture shall be of BIS standard and trade mark certificate (T.C.). Manufactures Word Mark/ Name Engraved/ Embossing/ Screen printing on housing. OEM must have its own in house NABL lab setup for all testing facilities for LED fixtures. (LM79 & LM80) certificate / Report from OEM shall be submitted. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
a	81.00	1170mm(+/-10%) LED batten with min. lumen output 2200 lm	467.00	Each	37827.00
135		Providing & Fixing of IP-20 LED Recessed / Surface Mounted, Round / Sqaure SMD Mid Power LED Downlight with power coated die-cast aluminum housing with UV Stabilized non yellowish Diffuser with BIS complience 2.5 KV surge protected Isolated driver, with Short & Open circuit protection, having efficiency > 85% . System Lumen efficacy of ≥ 110 lm / watt, THD < 10 % , Pf. ≥ 0.95 , CRI >80, life time of minimum 50000 Burning Hours with , 70% of intial Lumen maintaned till life ends , CCT 3000°K / 4000°K/ 5700°K /6000°K/6500°K (As per ANSI Bin) , maximum power consumption should not more than the specified rating and Fixture shall be of BIS standard and trade mark certificate (T.C.). Manufactures Word Mark/ Name Engraved/ Embossing/ Screen printing on housing.			
		OEM must have its own in house NABL lab setup for all testing facilities for LED fixtures. (LM79 & LM80) certificate / Report from OEM shall be submitted. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
		Surface Mounting (with extruded alumn. Housing)			
a	60.00	Minimum lumen output 1300 lm	1073.00	Each	64380.00

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

136		Providing & Fixing of IP20, 2'x2' LED Surface/ Recessed mounting Mid power SMD type LED Light fixture not less than 50mm housing depth made from CRCA sheet steel housing, high purity / transmissivity UV stabilized Non - yellowish diffuser for uniform light distribution. High efficiency with 4 KV internal/external surge protection BIS certified isolated driver having efficiency > 85% , with Short & Open circuit protection (Integral with light fixture). System lumen efficacy of ≥ 120 lm/Watt ,THD < 10 % , p.f. ≥ 0.95 ,CRI >80 , life time of minimum 50000 Burning Hours with , 70% of intial Lumen maintained till life ends , CCT 3000°K / 4000°K / 5700°K /6000°K/6500°K (As per ANSI Bin) , maximum power consumption should not more than the specified rating and Fixture shall be of BIS standard and trade mark certificate (T.C.). Manufactures Word Mark/ Name Engraved/ Embossing/ Screen printing on housing.			
		OEM must have its own in house NABL lab setup for all testing facilities for LED fixtures. (LM79 & LM80) certificate / Report from OEM shall be submitted. All as per pre approved by Engineer in charge. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
		Surface Moutning			
a	8.00	Minimum lumen output 4320 lm	2754.00	Each	22032.00
137		Providing & Fixing of IK08 IP-66 protected high power LED flood light system with single piece Pressure diecast aluminium housing, toughened glass with suitable lenses on LED / integrated lens diffuser to achieve various beam angles, of high power LED of 3 to 5 watt each . Integrated metal case potted driver as a unique BIS R number (as per IS 15885) having efficiency more than 85 % and in compliance to BIS certified and Trade mark certificate(Fitting & driver both have separate BIS R number). The System level Luminaire efficacy ≥ 130 lm/ wt. LED driver Input Voltage AC 120 to 270 V AC with High voltage Cutoff @ ≥ 300 V AC & Low Voltage cutoff @ ≥ 90 V AC and Auto resetting Safety .Power Factor >0.95 , THD(I) <10% , LED driving output current ≤ 750 mA. driver should be Phase to phase protection of 440 V for 4 Hrs. Electrical Connector , Surge Protection Min ≥ 4 KV internal and 10KV external but inside driver compartment, System life of 50000 Burning hours with 70% of Initial Lumens maintained, CRI>70 and CCT 5700K ± 355 K as			

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

		required.			
a	24.00	High Power LED Flood Light Minimum lumen output 32500 lm	11232.00	Each	269568.00
138		Providing & Fixing of IK08, IP 66 protected LED Street Light Luminaire on existing bracket/pole. Fixture made of powder coated single piece pressure die cast aluminum material with heat dissipation fins on housing with UV stabilized PC (UV stablization report submitted for UV cover) /Toughened Glass cover and secondary lens on each LED & should be SMD type of 3 to 5 watt each . The System efficacy >=125 lm/ wt and potted driver & has a unique BIS R number with Input Voltage AC 120 to 270 V AC with High voltage Cutoff @>=300 V AC and Auto resetting Safety , Power Factor >0.95 driver Efficiency >85% ,THD(I) <10% Humidity 10% to 90% RH Working Temp -5C to 45C . driver current <750mA. The luminaire shall be BIS certified and Trade mark certified. Life Expectancy Equal or more than 50000 burning hrs with Minimum 70% lumen maintained , CRI >70 and CCT 5700K +355K. Surge protection shall be min ≥ 4 KV internal and min 10 KV external inside driver compartment. driver should be Phase to phase protection of 440 V for 4 Hrs. Manufactures Word Mark/Name Engraved/Embossing on die cast housing to allow traceability/authenticity. Fixture shall be AS PER IS 10322 Complied.OEM Must have its own in house NABL lab setup for all testing facilities for LED fixtures. (LM79/LM80) Certificate/ report with liable warranty of product/accessories from OEM shall be submitted. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
a	8.00	LED Street Light fixture with Minimum lumen output 12150 lm	5476.00	Each	43808.00
139		Supply & Fixing of Dry Powder Agent (as per IS 4308:2019), ABC type Fire Extinguisher (Stored Pressure type) conforming to IS:15683:2018 , Powder coated Internal & External Surface Deep drawn cylinder body of Mild Steel CR2 grade conforming to IS: 513, Squeeze grip Forged brass release valve with Inbuilt safety release device, Diaphragm Type, 0 to 28 bar range pressure gauge, 450 mm long EPDM discharge tube, QR code for Product Traceability including Fixing on wall with suitable Anchor Fasteners as required of following capacity. Test Certificates			

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 11:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

		of all the Parameters along with Hydro test & Burst test (For Cylinder Body) Certificate from OEM / External NABL Accredited Lab is to be submitted.			
a	10.00	6 kg	4968.00	Each	49680.00
140	121.00	Providing & Fixing of ISI marked (IS:371) 6 amp surface type 3 pin ceiling rose with CM/L no. printed and made out from industrial grade Polycarbonate or fire resistant ABS material, brass terminal & captive screws including making connection testing etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work, refer Annexure "A" attached with this BSR.	33.00	Each	3993.00
141		Providing & Fixing of IS : 4985 - 2000 Class -4 (10 Kgf / Sqcm) UPVC drain water piping with fittings (IS:7834 & 10Kgf/sqcm) like elbow, socket, Tee, solvent cement jointing, support with MS hanger on ceiling or recessed in wall with chasing & plastering with 6 mm thick closed cell elastomeric nitrile rubber insulation including leakage testing etc. as required of following Nominal sizes.			
a	85.00	25 mm	183.00	Mtr.	15555.00
142		Supply, installation, testing and commissioning of interconnecting copper refrigerant piping of DHE Grade C12200- ASTM B68, B75, chemical composition of copper %- 99.0 Min and Phosphorus %- 0.015 to 0.040. For Annealed copper tube :- Tensile strength = 210 Mpa with elongation % = 40 Min. Ink Mark Brand Printing on Hard Tubes should be present. duly insulated with tubular elastomeric nitrile rubber FM/UL approved with high water vapor diffusion resistance and low thermal conductivity should be certified 'Class O' in Fire Propagation as per BS 476 Part 6 including chase cutting and filling with mortar, Slotted channel supports mounted on 10 mm threaded rod at suitable spacing the exposed piping shall be wrapped with glass woven cloth and lag coating for vapour barrier and weather protection. Joints shall be covered with nitrile rubber tape of 3 mm thick complete as required of following sizes. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work, refer Annexure "A" attached with this BSR.			
a	35.00	12.7 mm O.D., wall thickness $\geq$ 0.8mm (insulation – 13 mm thick)	843.00	Mtr.	29505.00
143		Supply, Installation, Testing and Commissioning of IS:1475 marked self contained drinking water cooler with hermetically sealed compressor, non			

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

		CFC refrigerent suitable for operation on 230V/1pH/50Hz AC supply, Full stainless steel (SS304) body (0.8 mm thick) and tank (0.5 mm thick), stainless steel water tray, minimum two nos Brass Chrome plated faucets and suitable drainage system complete in all respect with required height MS fabricated and Painted Angle iron frame (Cost of frame to be paid Extra) complete in all respect of the following capacity.			
a	1.00	cooling capacity 150 Ltr./Hr. and storage capacity 150 Ltrs	77925.00	Each	77925.00
144		Construction of tube-well from ground levels and upto 100 Meter depth and above to accommodate housing and assembly pipe of following sizes in all types of alluvium strata by percussion/ rotary drilling method and with gravel as per IS:4097-1967 and packing as per IS:2800 (Part I -& II) 1979 as amended upto date (the work includes the cost of gravel & its primary packing and packing during development, lowering of housing & strainer assembly pipes, with supply and wrapping of coir-rope, wherever necessary, for arresting fine sand particles. The work will not include cost of housing pipe and strainer pipe assembly and development work, but work would be completed after obtaining sand free water).			
a	100	250mm –do-.	1863	P.Rmt.	186300.00
145	6	Development of tube well as per IS specification using suitable compressor to give sand free water for required yield of the gravel packed tube well.	600	Hrs.	3600.00
146		Supply of <i>ERW M.S. black casing pipe</i> ISI marked (IS:4270/1992) of grade Fe410 of following sizes at site of work. Nominal bore of pipe (mm)			
a	50	200	1728	P.Rmt.	86400.00
147		Supply of <i>strainer pipes</i> made of ERW M.S. black pipe ISI mark of following sizes at the site of work including required size of slotting as per IS:8110-1985.			
a	10	200mm–do-.	2031	P.Rmt.	20310.00
148		S & F <i>tube well</i> cover of M.S. sheet (6mm thick) with nuts and bolts complete for casing size:			
a	1	200mm dia	373	Each	373.00
149	1	S & F M.S. <i>clamp</i> , set of 50 × 6mm flat iron with nuts and bolts etc. for holding the riser pipe assembly of submersible pump set.	266	Each	266.00
150		Providing & lowering of G.I. Pipes, flange pipe including rubber washer and nuts of 8 mm dia complete in all respect I.S.1239 Marked.			

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

a	50	B Class 50 mm dia	498	P.Rmt.	24900.00
151		SITC of Radial / mixed flow ISI marked water and anti-corrosive liquid filled submersible motor pump sets suitable for 100/150mm dia borewell. The size of adopter fixed on top of the motor should exceed the top of coupler , for safegaurd the coupler. The construction material of motor and pump should match IS: 8034 : 2018 and IS: 9283 guideline. The radial flow pumpset should operate at 5 star energy efficiency level of BEE and mixed flow pump set should operate at 3 star energy level of BEE, accompanied by valid BEE certificate. Motor should be IE2 class as per IEC 60034-2-1: 2007, IEC 60034-30: 2008, & IS12615:2011 with required accessories including making connection suitable for Bore well. The job includes labour part of lowering of riser pipe G.I./ H.D.P.E. with rope, cables & pump, installation of complete fitting and accessories, jointing of electrical cables up to Starter. All labour for testing of submersible pumps set and supply of water to water mains, complete in all respect. OEM shall have submit NABL / CPRI / ERDA accredited lab type test certificate before execution. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
a	1	150 mm diameter Submersible pump shall have following HP Rating, phase, Head range, Discharge range respectively.10.0 HP, 3-Ø, (91 - 115)Mtr, (285-180) LPM	82408	Each	82408.00
152	1	P & F Full way Valve (IS: 778 Mark) or wheel valve of approved make Gun metal 50mm nominal bore)	1464	Each	1464.00
153	1	SITC of IP 54 OEM Fabricated DOL/Star-Delta Starter panel with switchgear selection as per Type-2 Coordination Chart and made out from 1.6 mm thick powder coated CRCA sheet, enclosure comprising of over load protection relay, short circuit & single phasing protection(for three phase pumps), Illuminated ON / OFF push buttons, ammeter, voltmeter, indicating lamps, 2P/4P MCB etc. suitable for following rating motors complete in all respect. For Three phase Submersible / Mono block pump 7.5 HP to 10.0 HP (Star / Delta starter)	19601	Each	19601.00
154		Providing & Laying P.V.C. / XLPE insulated & P.V.C. sheathed Un-Armoured Aluminium cable confirming to IS:1554 P-I / IS :7098 P - I of 1.1 KV with H4- Grade electrolytic			

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign

		aluminium conductor confirming to IS 8130 of purity >99.6 %, Inner / outer sheath confirming to IS:5831 in existing RCC / Hume / Stoneware / PVC pipe/ open duct/cable trench / Cable tray (with cable tie) including testing etc. as required of following size. OEM must have it's own in house NABL accredited Laboratory for testing procedure as per IS:10810. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
a	100	6 Sqmm 3 Core Unarmoured.	103	P.Rmt	10300.00
b	50	10 Sqmm 4 Core armoured.	163	P.Rmt	8150.00

Secretary
Rajasthan State Sports Council
Jaipur

Signature valid

Digitally signed by Rajkesh Meena
Designation: Secretary
Date: 2026.08.07 12:37:31 IST
Reason: Approved

RajKaj Ref No.:
23881605

M e-Sign